

Oracle® Database

SQL Language Quick Reference

11g Release 2 (11.2)

E17119-05

August 2011

Copyright © 2003, 2011, Oracle and/or its affiliates. All rights reserved.

Primary Authors: Diana Lorentz, Mary Beth Roeser, Simon Watt

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	v
Audience	v
Documentation Accessibility	v
Related Documents	v
Conventions	vi
 1 SQL Statements	
Syntax for SQL Statements	1-1
 2 SQL Functions	
Syntax for SQL Functions	2-1
 3 SQL Expressions	
Syntax for SQL Expression Types	3-1
 4 SQL Conditions	
Syntax for SQL Condition Types	4-1
 5 Subclauses	
Syntax for Subclauses	5-1
 6 Data Types	
Overview of Data Types	6-1
Oracle Built-In Data Types	6-2
Oracle-Supplied Data Types	6-5
Converting to Oracle Data Types	6-5
 7 Format Models	
Overview of Format Models	7-1
Number Format Models	7-1
Number Format Elements	7-1
Datetime Format Models	7-3
Datetime Format Elements	7-3

A SQL*Plus Commands

SQL*Plus Commands	A-1
-------------------------	-----

Index

Preface

This reference contains a complete description of the Structured Query Language (SQL) used to manage information in an Oracle Database. Oracle SQL is a superset of the American National Standards Institute (ANSI) and the International Organization for Standardization (ISO) SQL:1999 standard.

This Preface contains these topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

The *Oracle Database SQL Language Quick Reference* is intended for all users of Oracle SQL.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit
<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see these Oracle resources:

- *Oracle Database PL/SQL Language Reference* for information on PL/SQL, the procedural language extension to Oracle SQL
- *Pro*C/C++ Programmer's Guide*, *Oracle SQL*Module for Ada Programmer's Guide*, and the *Pro*COBOL Programmer's Guide* for detailed descriptions of Oracle embedded SQL

Many of the examples in this book use the sample schemas, which are installed by default when you select the Basic Installation option with an Oracle Database installation. Refer to *Oracle Database Sample Schemas* for information on how these schemas were created and how you can use them yourself.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

SQL Statements

This chapter presents the syntax for Oracle SQL statements.

This chapter includes the following section:

- [Syntax for SQL Statements](#)

Syntax for SQL Statements

SQL statements are the means by which programs and users access data in an Oracle database.

The sections that follow show each SQL statement and its related syntax. Refer to [Chapter 5, "Subclauses"](#) for the syntax of the subclauses listed in the syntax for the statements.

See Also: *Oracle Database SQL Language Reference* for detailed information about Oracle SQL

ALTER CLUSTER

```
ALTER CLUSTER [ schema. ]cluster
  { physical_attributes_clause
  | SIZE size_clause
  | allocate_extent_clause
  | deallocate_unused_clause
  | { CACHE | NOCACHE }
  | ...
  [ parallel_clause ] ;
```

ALTER DATABASE

```
ALTER DATABASE [ database ]
  { startup_clauses
  | recovery_clauses
  | database_file_clauses
  | logfile_clauses
  | controlfile_clauses
  | standby_database_clauses
  | default_settings_clauses
  | instance_clauses
  | security_clause
  } ;
```

ALTER DATABASE LINK

```
ALTER DATABASE LINK dblink
  { CONNECT TO user IDENTIFIED BY password [ dblink_authentication ]
  | dblink_authentication
  } ;
```

ALTER DIMENSION

```
ALTER DIMENSION [ schema. ] dimension
  { ADD { level_clause
        | hierarchy_clause
        | attribute_clause
        | extended_attribute_clause
      }
  } ...
  |
  { DROP { LEVEL level [ RESTRICT | CASCADE ]
        | HIERARCHY hierarchy
        | ATTRIBUTE attribute [ LEVEL level [ COLUMN column ] ]...
      }
  } ...
  |
  COMPILE
;
```

ALTER DISKGROUP

```
ALTER DISKGROUP
  { { diskgroup_name
    { { add_disk_clause | drop_disk_clause }
      [, { add_disk_clause | drop_disk_clause } ]...
    | resize_disk_clauses
    } [ rebalance_diskgroup_clause ]
    | { disk_online_clause
      | disk_offline_clause
      | rebalance_diskgroup_clause
      | check_diskgroup_clause
      | diskgroup_template_clauses
      | diskgroup_directory_clauses
      | diskgroup_alias_clauses
      | diskgroup_volume_clauses
      | diskgroup_attributes
      | modify_diskgroup_file
      | drop_diskgroup_file_clause
      | usergroup_clauses
      | user_clauses
      | file_permissions_clause
      | file_owner_clause
    }
  } { diskgroup_name [, diskgroup_name ] ...
    | ALL
  } { undrop_disk_clause
    | diskgroup_availability
    | enable_disable_volume
  }
}
```

ALTER FLASHBACK ARCHIVE

```
ALTER FLASHBACK ARCHIVE flashback_archive
  { SET DEFAULT
  | { ADD | MODIFY } TABLESPACE tablespace [flashback_archive_quota]
  | REMOVE TABLESPACE tablespace_name
  | MODIFY RETENTION flashback_archive_retention
  | PURGE { ALL
          | BEFORE { SCN expr | TIMESTAMP expr}
        }
  };
```

ALTER FUNCTION

```
ALTER FUNCTION [ schema. ] function function_compile_clause
```


ALTER INDEX

```

ALTER INDEX [ schema. ] index
  { { deallocate_unused_clause
    | allocate_extent_clause
    | shrink_clause
    | parallel_clause
    | physical_attributes_clause
    | logging_clause
    } ...
  | rebuild_clause
  | PARAMETERS ( 'ODCI_parameters' )
    )
  | COMPILE
  | { ENABLE | DISABLE }
  | UNUSABLE
  | VISIBLE | INVISIBLE
  | RENAME TO new_name
  | COALESCE
  | { MONITORING | NOMONITORING } USAGE
  | UPDATE BLOCK REFERENCES
  | alter_index_partitioning
  }
;

```

ALTER INDEXTYPE

```

ALTER INDEXTYPE [ schema. ] indextype
  { { ADD | DROP } [ schema. ] operator ( parameter_types )
    [ , { ADD | DROP } [ schema. ] operator ( parameter_types ) ]... [ using_type_clause ]
  | COMPILE
  }
  [ WITH LOCAL [ RANGE ] PARTITION ] [ storage_table_clause ]
;

```

ALTER JAVA

```

ALTER JAVA
  { SOURCE | CLASS } [ schema. ] object_name
  [ RESOLVER
    ( ( match_string [, ] { schema_name | - } )... )
  ]
  { { COMPILE | RESOLVE }
  | invoker_rights_clause
  } ;

```

ALTER LIBRARY

```

ALTER LIBRARY [ schema. ] library_name library_compile_clause

```

ALTER MATERIALIZED VIEW

```

ALTER MATERIALIZED VIEW
  [ schema. ] materialized_view
  [ physical_attributes_clause
  | modify_mv_column_clause
  | table_compression
  | LOB_storage_clause [, LOB_storage_clause ]...
  | modify_LOB_storage_clause [, modify_LOB_storage_clause ]...
  | alter_table_partitioning
  | parallel_clause
  | logging_clause
  | allocate_extent_clause
  | deallocate_unused_clause
  | shrink_clause
  | { CACHE | NOCACHE }
  ]
  [ alter_iot_clauses ]

```

```
[ USING INDEX physical_attributes_clause ]
[ MODIFY scoped_table_ref_constraint
| alter_mv_refresh
]
[ { ENABLE | DISABLE } QUERY REWRITE
| COMPILE
| CONSIDER FRESH
] ;
```

ALTER MATERIALIZED VIEW LOG

```
ALTER MATERIALIZED VIEW LOG [ FORCE ]
ON [ schema. ]table
[ physical_attributes_clause
| add_mv_log_column_clause
| alter_table_partitioning
| parallel_clause
| logging_clause
| allocate_extent_clause
| shrink_clause
| move_mv_log_clause
| { CACHE | NOCACHE }
] [ mv_log_augmentation ] [ mv_log_purge_clause ]
;
```

ALTER OPERATOR

```
ALTER OPERATOR [ schema. ] operator
{ add_binding_clause
| drop_binding_clause
| COMPILE
} ;
```

ALTER OUTLINE

```
ALTER OUTLINE [ PUBLIC | PRIVATE ] outline
{ REBUILD
| RENAME TO new_outline_name
| CHANGE CATEGORY TO new_category_name
| { ENABLE | DISABLE }
} ...
;
```

ALTER PACKAGE

```
ALTER PACKAGE [ schema. ] package package_compile_clause
```

ALTER PROCEDURE

```
ALTER PROCEDURE [ schema. ] procedure procedure_compile_clause
```

ALTER PROFILE

```
ALTER PROFILE profile LIMIT
{ resource_parameters | password_parameters } ...
;
```

ALTER RESOURCE COST

```
ALTER RESOURCE COST
{ { CPU_PER_SESSION
| CONNECT_TIME
| LOGICAL_READS_PER_SESSION
| PRIVATE_SGA
} integer
} ...
;
```

ALTER ROLE

```

ALTER ROLE role
  { NOT IDENTIFIED
  | IDENTIFIED
    { BY password
    | USING [ schema. ] package
    | EXTERNALLY
    | GLOBALLY
    }
  }
;

```

ALTER ROLLBACK SEGMENT

```

ALTER ROLLBACK SEGMENT rollback_segment
  { ONLINE
  | OFFLINE
  | storage_clause
  | SHRINK [ TO size_clause ]
  };

```

ALTER SEQUENCE

```

ALTER SEQUENCE [ schema. ] sequence
  { INCREMENT BY integer
  | { MAXVALUE integer | NOMAXVALUE }
  | { MINVALUE integer | NOMINVALUE }
  | { CYCLE | NOCYCLE }
  | { CACHE integer | NOCACHE }
  | { ORDER | NOORDER }
  } ...
;

```

ALTER SESSION

```

ALTER SESSION
  { ADVISE { COMMIT | ROLLBACK | NOTHING }
  | CLOSE DATABASE LINK dblink
  | { ENABLE | DISABLE } COMMIT IN PROCEDURE
  | { ENABLE | DISABLE } GUARD
  | { ENABLE | DISABLE | FORCE } PARALLEL
  | { DML | DDL | QUERY } [ PARALLEL integer ]
  | { ENABLE RESUMABLE [ TIMEOUT integer ] [ NAME string ]
  | DISABLE RESUMABLE
  }
  | SYNC WITH PRIMARY
  | alter_session_set_clause
  } ;

```

ALTER SYSTEM

```

ALTER SYSTEM
  { archive_log_clause
  | checkpoint_clause
  | check_datafiles_clause
  | distributed_recov_clauses
  | FLUSH { SHARED_POOL | BUFFER_CACHE | REDO TO target_db_name [ [ NO ] CONFIRM APPLY ] }
  | end_session_clauses
  | SWITCH LOGFILE
  | { SUSPEND | RESUME }
  | quiesce_clauses
  | rolling_migration_clauses
  | security_clauses
  | shutdown_dispatcher_clause
  | REGISTER
  | SET alter_system_set_clause
  | [ alter_system_set_clause ]...
  | RESET alter_system_reset_clause
  } ;

```

```
        [ alter_system_reset_clause ]...
    } ;
```

ALTER TABLE

```
ALTER TABLE [ schema. ] table
    [ alter_table_properties
    | column_clauses
    | constraint_clauses
    | alter_table_partitioning
    | alter_external_table
    | move_table_clause
    ]
    [ enable_disable_clause
    | { ENABLE | DISABLE } { TABLE LOCK | ALL TRIGGERS }
    ] ...
;
```

ALTER TABLESPACE

```
ALTER TABLESPACE tablespace
    { DEFAULT [ table_compression ] storage_clause
    | MINIMUM EXTENT size_clause
    | RESIZE size_clause
    | COALESCE
    | SHRINK SPACE [ KEEP size_clause]
    | RENAME TO new_tablespace_name
    | { BEGIN | END } BACKUP
    | datafile_tempfile_clauses
    | tablespace_logging_clauses
    | tablespace_group_clause
    | tablespace_state_clauses
    | autoextend_clause
    | flashback_mode_clause
    | tablespace_retention_clause
    } ;
```

ALTER TRIGGER

```
ALTER TRIGGER [ schema. ] trigger
    { ENABLE
    | DISABLE
    | RENAME TO new_name
    | trigger_compile_clause
    } ;
```

ALTER TYPE

```
ALTER TYPE [ schema. ] type alter_type_clauses
```

ALTER USER

```
ALTER USER
    { user
    { IDENTIFIED
        { BY password [ REPLACE old_password ]
        | EXTERNALLY [ AS 'certificate_DN' | AS 'kerberos_principal_name' ]
        | GLOBALLY [ AS '[directory_DN]' ]
        }
    | DEFAULT TABLESPACE tablespace
    | TEMPORARY TABLESPACE { tablespace | tablespace_group_name }
    | { QUOTA { size_clause
        | UNLIMITED
        } ON tablespace
    } ...
    | PROFILE profile
    | DEFAULT ROLE { role [, role ]...
    }
```

```

        | ALL [ EXCEPT role [, role ] ... ]
        | NONE
      }
    | PASSWORD EXPIRE
    | ACCOUNT { LOCK | UNLOCK }
    | ENABLE EDITIONS [ FORCE ]
  } ...
| user [, user ]... proxy_clause
} ;

```

ALTER VIEW

```

ALTER VIEW [ schema. ] view
{ ADD out_of_line_constraint
| MODIFY CONSTRAINT constraint
  { RELY | NORELY }
| DROP { CONSTRAINT constraint
      | PRIMARY KEY
      | UNIQUE (column [, column ]...)
    }
| COMPILE
| { READ ONLY | READ WRITE }
} ;

```

ANALYZE

```

ANALYZE
{ { TABLE [ schema. ] table
  | INDEX [ schema. ] index
  } [ partition_extension_clause ]
| CLUSTER [ schema. ] cluster
}
{ validation_clauses
| LIST CHAINED ROWS [ into_clause ]
| DELETE [ SYSTEM ] STATISTICS
} ;

```

ASSOCIATE STATISTICS

```

ASSOCIATE STATISTICS WITH
{ column_association | function_association }
[ storage_table_clause ] ;

```

AUDIT

```

AUDIT
{ audit_operation_clause [ auditing_by_clause | IN SESSION CURRENT ]
| audit_schema_object_clause
| NETWORK
} [ BY { SESSION | ACCESS } ]
  [ WHENEVER [ NOT ] SUCCESSFUL ]
;

```

CALL

```

CALL
{ routine_clause
| object_access_expression
}
[ INTO :host_variable
  [ [ INDICATOR ] :indicator_variable ] ] ;

```

COMMENT

```

COMMENT ON
{ COLUMN [ schema. ]
  { table. | view. | materialized_view. } column
| EDITION edition_name

```

```
| INDEXTYPE [ schema. ] indextype
| MATERIALIZED VIEW materialized_view
| MINING MODEL [ schema. ] model
| OPERATOR [ schema. ] operator
| TABLE [ schema. ] { table | view }
}
IS string ;
```

COMMIT

```
COMMIT [ WORK ]
[ [ COMMENT string ]
  | [ WRITE [ WAIT | NOWAIT ] [ IMMEDIATE | BATCH ]
  ]
| FORCE { string [, integer ]
        | CORRUPT_XID string
        | CORRUPT_XID_ALL
      }
] ;
```

CREATE CLUSTER

```
CREATE CLUSTER [ schema. ] cluster
(column datatype [ SORT ]
[, column datatype [ SORT ] ]...
)
[ { physical_attributes_clause
  | SIZE size_clause
  | TABLESPACE tablespace
  | { INDEX
    | [ SINGLE TABLE ]
    HASHKEYS integer [ HASH IS expr ]
  }
}...
]
[ parallel_clause ]
[ NOROWDEPENDENCIES | ROWDEPENDENCIES ]
[ CACHE | NOCACHE ] ;
```

CREATE CONTEXT

```
CREATE [ OR REPLACE ] CONTEXT namespace
USING [ schema. ] package
[ INITIALIZED { EXTERNALLY | GLOBALLY }
| ACCESSED GLOBALLY
] ;
```

CREATE CONTROLFILE

```
CREATE CONTROLFILE
[ REUSE ] [ SET ] DATABASE database
[ logfile_clause ]
{ RESETLOGS | NORESETLOGS }
[ DATAFILE file_specification
[, file_specification ]... ]
[ MAXLOGFILES integer
| MAXLOGMEMBERS integer
| MAXLOGHISTORY integer
| MAXDATAFILES integer
| MAXINSTANCES integer
| { ARCHIVELOG | NOARCHIVELOG }
| FORCE LOGGING
]...
[ character_set_clause ] ;
```

CREATE DATABASE

```
CREATE DATABASE [ database ]
  { USER SYS IDENTIFIED BY password
  | USER SYSTEM IDENTIFIED BY password
  | CONTROLFILE REUSE
  | MAXDATAFILES integer
  | MAXINSTANCES integer
  | CHARACTER SET charset
  | NATIONAL CHARACTER SET charset
  | SET DEFAULT
    { BIGFILE | SMALLFILE } TABLESPACE
  | database_logging_clauses
  | tablespace_clauses
  | set_time_zone_clause
  }... ;
```

CREATE DATABASE LINK

```
CREATE [ SHARED ] [ PUBLIC ] DATABASE LINK dblink
  [ CONNECT TO
    { CURRENT_USER
    | user IDENTIFIED BY password [ dblink_authentication ]
    }
  | dblink_authentication
  ]...
  [ USING connect_string ] ;
```

CREATE DIMENSION

```
CREATE DIMENSION [ schema. ] dimension
  level_clause ...
  { hierarchy_clause
  | attribute_clause
  | extended_attribute_clause
  }...
;
```

CREATE DIRECTORY

```
CREATE [ OR REPLACE ] DIRECTORY directory
  AS 'path_name' ;
```

CREATE DISKGROUP

```
CREATE DISKGROUP diskgroup_name
  [ { HIGH | NORMAL | EXTERNAL } REDUNDANCY ]
  [ [ QUORUM | REGULAR ] [ FAILGROUP failgroup_name ]
  DISK qualified_disk_clause [, qualified_disk_clause]...
  ] ...
  [ ATTRIBUTE { 'attribute_name' = 'attribute_value' }... ]
;
```

CREATE EDITION

```
CREATE EDITION edition
  [ AS CHILD OF parent_edition ] ;
```

CREATE FLASHBACK ARCHIVE

```
CREATE FLASHBACK ARCHIVE [DEFAULT] flashback_archive
  TABLESPACE tablespace
  [flashback_archive_quota] flashback_archive_retention
;
```

CREATE FUNCTION

```
CREATE [ OR REPLACE ] FUNCTION plsql_source
```

CREATE INDEX

```
CREATE [ UNIQUE | BITMAP ] INDEX [ schema. ] index
  ON { cluster_index_clause
      | table_index_clause
      | bitmap_join_index_clause
  }
[ UNUSABLE ] ;
```

CREATE INDEXTYPE

```
CREATE [ OR REPLACE ] INDEXTYPE [ schema. ] indextype
  FOR [ schema. ] operator (paramater_type [, paramater_type ]...)
    [, [ schema. ] operator (paramater_type [, paramater_type ]...)
    ]...
  using_type_clause
  [WITH LOCAL [RANGE] PARTITION ]
  [ storage_table_clause ]
;
```

CREATE JAVA

```
CREATE [ OR REPLACE ] [ AND { RESOLVE | COMPILE } ] [ NOFORCE ]
  JAVA { { SOURCE | RESOURCE } NAMED [ schema. ] primary_name
        | CLASS [ SCHEMA schema ]
        }
  [ invoker_rights_clause ]
  [ RESOLVER ( (match_string [,] { schema_name | - })...) ]
  { USING { BFILE (directory_object_name, server_file_name)
          | { CLOB | BLOB | BFILE } subquery
          | 'key_for_BLOB'
        }
  | AS source_char
  }
```

CREATE LIBRARY

```
CREATE [ OR REPLACE ] LIBRARY plsql_source
```

CREATE MATERIALIZED VIEW

```
CREATE MATERIALIZED VIEW [ schema. ] materialized_view
  [ column_alias [ENCRYPT [encryption_spec]] [, column_alias [ENCRYPT [encryption_spec]] ]...
]
  [ OF [ schema. ] object_type ]
  [ (scoped_table_ref_constraint) ]
  { ON PREBUILT TABLE
    [ { WITH | WITHOUT } REDUCED PRECISION ]
  | physical_properties materialized_view_props
  }
  [ USING INDEX
    [ physical_attributes_clause
    | TABLESPACE tablespace
    ]...
  | USING NO INDEX
  ]
  [ create_mv_refresh ]
  [ FOR UPDATE ]
  [ { DISABLE | ENABLE } QUERY REWRITE ]
AS subquery ;
```

CREATE MATERIALIZED VIEW LOG

```
CREATE MATERIALIZED VIEW LOG ON [ schema. ] table
  [ physical_attributes_clause
  | TABLESPACE tablespace
  | logging_clause
  | { CACHE | NOCACHE }
  ]
```



```

]...
[ parallel_clause ]
[ table_partitioning_clauses ]
[ WITH { OBJECT ID
      | PRIMARY KEY
      | ROWID
      | SEQUENCE
      | COMMIT SCN
      | (column [, column ]...)
      }
      [ { , OBJECT ID
        | , PRIMARY KEY
        | , ROWID
        | , SEQUENCE
        | , COMMIT SCN
        | (column [, column ]...)
        }
      ]...
[ new_values_clause ]
] [ mv_log_purge_clause ]
;

```

CREATE OPERATOR

```

CREATE [ OR REPLACE ] OPERATOR
      [ schema. ] operator binding_clause ;

```

CREATE OUTLINE

```

CREATE [ OR REPLACE ]
      [ PUBLIC | PRIVATE ] OUTLINE [ outline ]
      [ FROM [ PUBLIC | PRIVATE ] source_outline ]
      [ FOR CATEGORY category ]
      [ ON statement ] ;

```

CREATE PACKAGE

```

CREATE [ OR REPLACE ] PACKAGE plsql_source

```

CREATE PACKAGE BODY

```

CREATE [ OR REPLACE ] PACKAGE BODY plsql_source

```

CREATE PFILE

```

CREATE PFILE [= 'pfile_name' ]
      FROM { SFILE [= 'spfile_name']
            | MEMORY
      } ;

```

CREATE PROCEDURE

```

CREATE [ OR REPLACE ] PROCEDURE plsql_source

```

CREATE PROFILE

```

CREATE PROFILE profile
      LIMIT { resource_parameters
            | password_parameters
            }...
;

```

CREATE RESTORE POINT

```

CREATE RESTORE POINT restore_point
      [ AS OF {TIMESTAMP | SCN} expr ]
      [ PRESERVE
      | GUARANTEE FLASHBACK DATABASE

```

```
];
```

CREATE ROLE

```
CREATE ROLE role
  [ NOT IDENTIFIED
  | IDENTIFIED { BY password
                  | USING [ schema. ] package
                  | EXTERNALLY
                  | GLOBALLY
                }
  ] ;
```

CREATE ROLLBACK SEGMENT

```
CREATE [ PUBLIC ] ROLLBACK SEGMENT rollback_segment
  [ TABLESPACE tablespace | storage_clause ]...;
```

CREATE SCHEMA

```
CREATE SCHEMA AUTHORIZATION schema
  { create_table_statement
  | create_view_statement
  | grant_statement
  }...
;
```

CREATE SEQUENCE

```
CREATE SEQUENCE [ schema. ] sequence
  [ { INCREMENT BY | START WITH } integer
  | { MAXVALUE integer | NOMAXVALUE }
  | { MINVALUE integer | NOMINVALUE }
  | { CYCLE | NOCYCLE }
  | { CACHE integer | NOCACHE }
  | { ORDER | NOORDER }
  ]...
;
```

CREATE SPFILE

```
CREATE SPFILE [= 'spfile_name' ]
  FROM { PFILE [= 'pfile_name' ]
        | MEMORY
      } ;
```

CREATE SYNONYM

```
CREATE [ OR REPLACE ] [ PUBLIC ] SYNONYM
  [ schema. ] synonym
  FOR [ schema. ] object [ @ dblink ] ;
```

CREATE TABLE

```
CREATE [ GLOBAL TEMPORARY ] TABLE [ schema. ] table
  { relational_table | object_table | XMLType_table }
```

CREATE TABLESPACE

```
CREATE
  [ BIGFILE | SMALLFILE ]
  { permanent_tablespace_clause
  | temporary_tablespace_clause
  | undo_tablespace_clause
  } ;
```

CREATE TRIGGER

```
CREATE [ OR REPLACE ] TRIGGER plsql_source
```

CREATE TYPE

```
CREATE [OR REPLACE] TYPE plsql_source
```

CREATE TYPE BODY

```
CREATE [ OR REPLACE ] TYPE BODY plsql_source
```

CREATE USER

```
CREATE USER user
  IDENTIFIED { BY password
              | EXTERNALLY [ AS 'certificate_DN' | AS 'kerberos_principal_name' ]
              | GLOBALLY [ AS '[ directory_DN ]' ]
              }
  [ DEFAULT TABLESPACE tablespace
  | TEMPORARY TABLESPACE
    { tablespace | tablespace_group_name }
  | { QUOTA { size_clause | UNLIMITED } ON tablespace }...
  | PROFILE profile
  | PASSWORD EXPIRE
  | ACCOUNT { LOCK | UNLOCK }
  [ DEFAULT TABLESPACE tablespace
  | TEMPORARY TABLESPACE
    { tablespace | tablespace_group_name }
  | { QUOTA { size_clause | UNLIMITED } ON tablespace }...
  | PROFILE profile
  | PASSWORD EXPIRE
  | ACCOUNT { LOCK | UNLOCK }
  | ENABLE EDITIONS
  ]...
] ;
```

CREATE VIEW

```
CREATE [OR REPLACE]
  [[NO] FORCE] [EDITIONING] VIEW [schema.] view
  [ ( { alias [ inline_constraint... ]
    | out_of_line_constraint
    }
    [, { alias [ inline_constraint... ]
    | out_of_line_constraint
    }
  ]
  )
  | object_view_clause
  | XMLType_view_clause
  ]
  AS subquery [ subquery_restriction_clause ] ;
```

DELETE

```
DELETE [ hint ]
  [ FROM ]
  { dml_table_expression_clause
  | ONLY (dml_table_expression_clause)
  } [ t_alias ]
  [ where_clause ]
  [ returning_clause ]
  [error_logging_clause];
```

DISASSOCIATE STATISTICS

```
DISASSOCIATE STATISTICS FROM
```

```
{ COLUMNS [ schema. ]table.column
      [, [ schema. ]table.column ]...
| FUNCTIONS [ schema. ]function
      [, [ schema. ]function ]...
| PACKAGES [ schema. ]package
      [, [ schema. ]package ]...
| TYPES [ schema. ]type
      [, [ schema. ]type ]...
| INDEXES [ schema. ]index
      [, [ schema. ]index ]...
| INDEXTYPES [ schema. ]indextype
      [, [ schema. ]indextype ]...
}
[ FORCE ] ;
```

DROP CLUSTER

```
DROP CLUSTER [ schema. ] cluster
      [ INCLUDING TABLES [ CASCADE CONSTRAINTS ] ] ;
```

DROP CONTEXT

```
DROP CONTEXT namespace ;
```

DROP DATABASE

```
DROP DATABASE ;
```

DROP DATABASE LINK

```
DROP [ PUBLIC ] DATABASE LINK dblink ;
```

DROP DIMENSION

```
DROP DIMENSION [ schema. ] dimension ;
```

DROP DIRECTORY

```
DROP DIRECTORY directory_name ;
```

DROP DISKGROUP

```
DROP DISKGROUP diskgroup_name
      [ FORCE INCLUDING CONTENTS
      | { INCLUDING | EXCLUDING } CONTENTS
      ];
```

DROP EDITION

```
DROP EDITION edition [CASCADE];
```

DROP FLASHBACK ARCHIVE

```
DROP FLASHBACK ARCHIVE flashback_archive;
```

DROP FUNCTION

```
DROP FUNCTION [ schema. ] function_name ;
```

DROP INDEX

```
DROP INDEX [ schema. ] index [ FORCE ] ;
```

DROP INDEXTYPE

```
DROP INDEXTYPE [ schema. ] indextype [ FORCE ] ;
```

DROP JAVA

```
DROP JAVA { SOURCE | CLASS | RESOURCE }  
  [ schema. ] object_name ;
```

DROP LIBRARY

```
DROP LIBRARY library_name ;
```

DROP MATERIALIZED VIEW

```
DROP MATERIALIZED VIEW [ schema. ] materialized_view  
  [ PRESERVE TABLE ] ;
```

DROP MATERIALIZED VIEW LOG

```
DROP MATERIALIZED VIEW LOG ON [ schema. ] table ;
```

DROP OPERATOR

```
DROP OPERATOR [ schema. ] operator [ FORCE ] ;
```

DROP OUTLINE

```
DROP OUTLINE outline ;
```

DROP PACKAGE

```
DROP PACKAGE [ BODY ] [ schema. ] package ;
```

DROP PROCEDURE

```
DROP PROCEDURE [ schema. ] procedure ;
```

DROP PROFILE

```
DROP PROFILE profile [ CASCADE ] ;
```

DROP RESTORE POINT

```
DROP RESTORE POINT restore_point ;
```

DROP ROLE

```
DROP ROLE role ;
```

DROP ROLLBACK SEGMENT

```
DROP ROLLBACK SEGMENT rollback_segment ;
```

DROP SEQUENCE

```
DROP SEQUENCE [ schema. ] sequence_name ;
```

DROP SYNONYM

```
DROP [PUBLIC] SYNONYM [ schema. ] synonym [FORCE] ;
```

DROP TABLE

```
DROP TABLE [ schema. ] table  
  [ CASCADE CONSTRAINTS ] [ PURGE ] ;
```

DROP TABLESPACE

```
DROP TABLESPACE tablespace  
  [ INCLUDING CONTENTS [ {AND | KEEP} DATAFILES ]  
  [ CASCADE CONSTRAINTS ]  
  ] ;
```

DROP TRIGGER

```
DROP TRIGGER [ schema. ] trigger ;
```

DROP TYPE

```
DROP TYPE [ schema. ] type_name [ FORCE | VALIDATE ] ;
```

DROP TYPE BODY

```
DROP TYPE BODY [ schema. ] type_name ;
```

DROP USER

```
DROP USER user [ CASCADE ] ;
```

DROP VIEW

```
DROP VIEW [ schema. ] view [ CASCADE CONSTRAINTS ] ;
```

EXPLAIN PLAN

```
EXPLAIN PLAN
  [ SET STATEMENT_ID = string ]
  [ INTO [ schema. ] table [ @ dblink ] ]
FOR statement ;
```

FLASHBACK DATABASE

```
FLASHBACK [ STANDBY ] DATABASE [ database ]
  { TO { { SCN | TIMESTAMP } expr
    | RESTORE POINT restore_point
  }
  | TO BEFORE { SCN | TIMESTAMP } expr
    | RESETLOGS
  }
}
```

FLASHBACK TABLE

```
FLASHBACK TABLE
  [ schema. ] table
  [, [ schema. ] table ]...
TO { { { SCN | TIMESTAMP } expr
  | RESTORE POINT restore_point
} [ { ENABLE | DISABLE } TRIGGERS ]
  | BEFORE DROP [ RENAME TO table ]
} ;
```

GRANT

```
GRANT { grant_system_privileges
  | grant_object_privileges
} ;
```

INSERT

```
INSERT [ hint ]
  { single_table_insert | multi_table_insert } ;
```

LOCK TABLE

```
LOCK TABLE [ schema. ] { table | view }
  [ partition_extension_clause
  | @ dblink
  ] [, [ schema. ] { table | view }
  [ partition_extension_clause
  | @ dblink
  ]
```

```

]...
IN lockmode MODE
[ NOWAIT
| WAIT integer
] ;

```

MERGE

```

MERGE [ hint ]
  INTO [ schema. ] { table | view } [ t_alias ]
  USING { [ schema. ] { table | view }
        | subquery
        } [ t_alias ]
  ON ( condition )
  [ merge_update_clause ]
  [ merge_insert_clause ]
  [ error_logging_clause ] ;

```

NOAUDIT

```

NOAUDIT
  { audit_operation_clause [ auditing_by_clause ]
  | audit_schema_object_clause
  | NETWORK
  }
  [ WHENEVER [ NOT ] SUCCESSFUL ] ;

```

PURGE

```

PURGE { { TABLE table | INDEX index }
        | { RECYCLEBIN | DBA_RECYCLEBIN }
        | TABLESPACE tablespace [ USER username ]
        } ;

```

RENAME

```

RENAME old_name TO new_name ;

```

REVOKE

```

REVOKE { revoke_system_privileges
        | revoke_object_privileges
        } ;

```

ROLLBACK

```

ROLLBACK [ WORK ]
  [ TO [ SAVEPOINT ] savepoint
  | FORCE string
  ] ;

```

SAVEPOINT

```

SAVEPOINT savepoint ;

```

SELECT

```

[ subquery_factoring_clause ] subquery [ for_update_clause ] ;

```

SET CONSTRAINT[S]

```

SET { CONSTRAINT | CONSTRAINTS }
  { constraint [, constraint ]...
  | ALL
  }
  { IMMEDIATE | DEFERRED } ;

```

SET ROLE

```
SET ROLE
  { role [ IDENTIFIED BY password ]
    [, role [ IDENTIFIED BY password ] ]...
  | ALL [ EXCEPT role [, role ]... ]
  | NONE
  } ;
```

SET TRANSACTION

```
SET TRANSACTION
  { { READ { ONLY | WRITE }
    | ISOLATION LEVEL
      { SERIALIZABLE | READ COMMITTED }
    | USE ROLLBACK SEGMENT rollback_segment
    } [ NAME string ]
  | NAME string
  } ;
```

TRUNCATE_CLUSTER

```
TRUNCATE CLUSTER [schema.] cluster
  [ {DROP | REUSE} STORAGE ] ;
```

TRUNCATE_TABLE

```
TRUNCATE TABLE [schema.] table
  [ {PRESERVE | PURGE} MATERIALIZED VIEW LOG ]
  [ {DROP [ ALL ] | REUSE} STORAGE ] ;
```

Note: You can specify the ALL keyword in this statement starting with Oracle Database 11g Release 2 (11.2.0.2).

UPDATE

```
UPDATE [ hint ]
  { dml_table_expression_clause
  | ONLY (dml_table_expression_clause)
  } [ t_alias ]
update_set_clause
[ where_clause ]
[ returning_clause ]
[error_logging_clause] ;
```

SQL Functions

This chapter presents the syntax for SQL functions.

This chapter includes the following section:

- [Syntax for SQL Functions](#)

Syntax for SQL Functions

A function is a command that manipulates data items and returns a single value.

The sections that follow show each SQL function and its related syntax. Refer to [Chapter 5, "Subclauses"](#) for the syntax of the subclauses.

See Also: Functions in *Oracle Database SQL Language Reference* for detailed information about SQL functions

ABS

ABS(n)

ACOS

ACOS(n)

ADD_MONTHS

ADD_MONTHS(date, integer)

aggregate_function

Aggregate functions return a single result row based on groups of rows, rather than on single rows.

analytic_function

```
analytic_function([ arguments ])
    OVER (analytic_clause)
```

APPENDCHILDXML

```
APPENDCHILDXML
    ( XMLType_instance, XPath_string, value_expr [, namespace_string ])
```

ASCII

ASCII(char)

ASCIISTR

ASCIISTR(char)

ASIN

ASIN(n)

ATAN

ATAN(n)

ATAN2

ATAN2(n1 , n2)

AVG

AVG([DISTINCT | ALL] expr) [OVER(analytic_clause)]

BFILENAME

BFILENAME('directory', 'filename')

BIN_TO_NUM

BIN_TO_NUM(expr [, expr]...)

BITAND

BITAND(expr1, expr2)

CARDINALITY

CARDINALITY(nested_table)

CAST

CAST({ expr | MULTISSET (subquery) } AS type_name)

CEIL

CEIL(n)

CHARTOROWID

CHARTOROWID(char)

CHR

CHR(n [USING NCHAR_CS])

CLUSTER_ID

CLUSTER_ID ([schema .] model mining_attribute_clause)

CLUSTER_PROBABILITY

CLUSTER_PROBABILITY ([schema .] model
[, cluster_id] mining_attribute_clause)

CLUSTER_SET

CLUSTER_SET ([schema .] model [, topN [, cutoff]] mining_attribute_clause)

COALESCE

COALESCE(expr [, expr]...)

COLLECT

COLLECT([DISTINCT | UNIQUE] column [ORDER BY expr])

COMPOSE

COMPOSE(char)

CONCAT

CONCAT(char1, char2)

CONVERT

CONVERT(char, dest_char_set[, source_char_set])

CORR

CORR(expr1, expr2) [OVER (analytic_clause)]

CORR_K, CORR_S

```
{ CORR_K | CORR_S }
(expr1, expr2
  [, { COEFFICIENT
      | ONE_SIDED_SIG
      | ONE_SIDED_SIG_POS
      | ONE_SIDED_SIG_NEG
      | TWO_SIDED_SIG
    }
  ]
)
```

COS

COS(n)

COSH

COSH(n)

COUNT

COUNT({ * | [DISTINCT | ALL] expr }) [OVER (analytic_clause)]

COVAR_POP

COVAR_POP(expr1, expr2)
 [OVER (analytic_clause)]

COVAR_SAMP

COVAR_SAMP(expr1, expr2) [OVER (analytic_clause)]

CUBE_TABLE

```
CUBE_TABLE
( ' { schema.cube [ {HIERARCHY | HRR} dimension hierarchy ]...
  | schema.dimension [ {HIERARCHY | HRR} [dimension] hierarchy ]
  }
  ,
)
```

CUME_DIST (aggregate)

```
CUME_DIST(expr[,expr ]...) WITHIN GROUP
  (ORDER BY expr [ DESC | ASC ]
    [ NULLS { FIRST | LAST } ]
    [, expr [ DESC | ASC ]
      [ NULLS { FIRST | LAST } ]
    ]...
  )
```

CUME_DIST (analytic)

```
CUME_DIST() OVER ([ query_partition_clause ] order_by_clause)
```

CURRENT_DATE

```
CURRENT_DATE
```

CURRENT_TIMESTAMP

```
CURRENT_TIMESTAMP [ (precision) ]
```

CV

```
CV([ dimension_column ])
```

DATAOBJ_TO_PARTITION

```
DATAOBJ_TO_PARTITION( table, partition_id )
```

DBTIMEZONE

```
DBTIMEZONE
```

DECODE

```
DECODE(expr, search, result [, search, result ]... [, default ])
```

DECOMPOSE

```
DECOMPOSE( string [ CANONICAL | COMPATIBILITY ] )
```

DELETEXML

```
DELETEXML( XMLType_instance, XPath_string [, namespace_string ])
```

DENSE_RANK (aggregate)

```
DENSE_RANK(expr [, expr ]...) WITHIN GROUP
  (ORDER BY expr [ DESC | ASC ]
    [ NULLS { FIRST | LAST } ]
    [,expr [ DESC | ASC ]
    [ NULLS { FIRST | LAST } ]
    ]...
  )
```

DENSE_RANK (analytic)

```
DENSE_RANK( ) OVER([ query_partition_clause ] order_by_clause)
```

DEPTH

```
DEPTH(correlation_integer)
```

DEREF

```
DEREF(expr)
```

DUMP

```
DUMP(expr[, return_fmt [, start_position [, length ] ]])
```

EMPTY_BLOB, EMPTY_CLOB

```
{ EMPTY_BLOB | EMPTY_CLOB }( )
```

EXISTSNODE

```
EXISTSNODE
  (XMLType_instance, XPath_string
```

```

        [, namespace_string ]
    )

```

EXP

EXP(n)

EXTRACT (datetime)

```

EXTRACT( { YEAR
        | MONTH
        | DAY
        | HOUR
        | MINUTE
        | SECOND
        | TIMEZONE_HOUR
        | TIMEZONE_MINUTE
        | TIMEZONE_REGION
        | TIMEZONE_ABBR
        }
        FROM { expr }
    )

```

EXTRACT (XML)

EXTRACT(XMLType_instance, XPath_string [, namespace_string])

EXTRACTVALUE

EXTRACTVALUE(XMLType_instance, XPath_string [, namespace_string])

FEATURE_ID

FEATURE_ID([schema .] model mining_attribute_clause)

FEATURE_SET

FEATURE_SET([schema .] model [, topN [, cutoff]] mining_attribute_clause)

FEATURE_VALUE

FEATURE_VALUE([schema .] model [, feature_id] mining_attribute_clause)

FIRST

```

aggregate_function
    KEEP
    (DENSE_RANK FIRST ORDER BY
    expr [ DESC | ASC ]
        [ NULLS { FIRST | LAST } ]
    [, expr [ DESC | ASC ]
        [ NULLS { FIRST | LAST } ]
    ]...
    )
    [ OVER ( [query_partition_clause] ) ]

```

FIRST_VALUE

```

FIRST_VALUE
    { (expr) [ {RESPECT | IGNORE} NULLS ]
    | (expr [ {RESPECT | IGNORE} NULLS ])
    }
    OVER (analytic_clause)

```

FLOOR

FLOOR(n)

FROM_TZ

FROM_TZ (timestamp_value, time_zone_value)

GREATEST

GREATEST(expr [, expr]...)

GROUP_ID

GROUP_ID()

GROUPING

GROUPING(expr)

GROUPING_ID

GROUPING_ID(expr [, expr]...)

HEXTORAW

HEXTORAW(char)

INITCAP

INITCAP(char)

INSERTCHILDXML

INSERTCHILDXML
(XMLType_instance, XPath_string, child_expr, value_expr [, namespace_string])

INSERTCHILDXMLAFTER

INSERTCHILDXMLAFTER
(XMLType_instance, XPath_string, child_expr, value_expr [, namespace_string])

INSERTCHILDXMLBEFORE

INSERTCHILDXMLBEFORE
(XMLType_instance, XPath_string, child_expr, value_expr [, namespace_string])

INSERTXMLAFTER

INSERTXMLAFTER
(XMLType_instance, XPath_string, value_expr [, namespace_string])

INSERTXMLBEFORE

INSERTXMLBEFORE
(XMLType_instance, XPath_string, value_expr [, namespace_string])

INSTR

```
{ INSTR
| INSTRB
| INSTRC
| INSTR2
| INSTR4
}
(string , substring [, position [, occurrence ] ])
```

ITERATION_NUMBER

ITERATION_NUMBER

LAG

```
LAG
  { ( value_expr [, offset [, default]] ) [ { RESPECT | IGNORE } NULLS ]
    | ( value_expr [ { RESPECT | IGNORE } NULLS ] [, offset [, default]] )
  }
OVER ([ query_partition_clause ] order_by_clause)
```

LAST

```
aggregate_function KEEP
  (DENSE_RANK LAST ORDER BY
    expr [ DESC | ASC ]
      [ NULLS { FIRST | LAST } ]
    [, expr [ DESC | ASC ]
      [ NULLS { FIRST | LAST } ]
    ]...
  )
[ OVER ( [query_partition_clause] ) ]
```

LAST_DAY

```
LAST_DAY(date)
```

LAST_VALUE

```
LAST_VALUE
  { (expr) [ { RESPECT | IGNORE } NULLS ]
    | (expr [ { RESPECT | IGNORE } NULLS ])
  }
OVER (analytic_clause)
```

LEAD

```
LEAD
  { ( value_expr [, offset [, default]] ) [ { RESPECT | IGNORE } NULLS ]
    | ( value_expr [ { RESPECT | IGNORE } NULLS ] [, offset [, default]] )
  }
OVER ([ query_partition_clause ] order_by_clause)
```

LEAST

```
LEAST(expr [, expr ]...)
```

LENGTH

```
{ LENGTH
  | LENGTHB
  | LENGTHC
  | LENGTH2
  | LENGTH4
}
(char)
```

LISTAGG

```
LISTAGG(measure_expr [, 'delimiter'])
  WITHIN GROUP (order_by_clause) [OVER query_partition_clause]
```

LN

```
LN(n)
```

LNNVL

```
LNNVL(condition)
```

LOCALTIMESTAMP

```
LOCALTIMESTAMP [ (timestamp_precision) ]
```

LOG

LOG(n2, n1)

LOWER

LOWER(char)

LPAD

LPAD(expr1, n [, expr2])

LTRIM

LTRIM(char [, set])

MAKE_REF

MAKE_REF({ table | view } , key [, key]...)

MAX

MAX([DISTINCT | ALL] expr) [OVER (analytic_clause)]

MEDIAN

MEDIAN(expr) [OVER (query_partition_clause)]

MIN

MIN([DISTINCT | ALL] expr) [OVER (analytic_clause)]

MOD

MOD(n2, n1)

MONTHS_BETWEEN

MONTHS_BETWEEN(date1, date2)

NANVL

NANVL(n2, n1)

NCHR

NCHR(number)

NEW_TIME

NEW_TIME(date, timezone1, timezone2)

NEXT_DAY

NEXT_DAY(date, char)

NLS_CHARSET_DECL_LEN

NLS_CHARSET_DECL_LEN(byte_count, 'char_set_id')

NLS_CHARSET_ID

NLS_CHARSET_ID(string)

NLS_CHARSET_NAME

NLS_CHARSET_NAME(number)

NLS_INITCAP

NLS_INITCAP(char [, 'nlsparam'])

NLS_LOWER

NLS_LOWER(char [, 'nlsparam'])

NLS_UPPER

NLS_UPPER(char [, 'nlsparam'])

NLSSORT

NLSSORT(char [, 'nlsparam'])

NTH_VALUE

NTH_VALUE(measure_expr, n)
[FROM { FIRST | LAST }][{ RESPECT | IGNORE } NULLS]
OVER (analytic_clause)

NTILE

NTILE(expr) OVER ([query_partition_clause] order_by_clause)

NULLIF

NULLIF(expr1, expr2)

NUMTODSINTERVAL

NUMTODSINTERVAL(n, 'interval_unit')

NUMTOYMINTERVAL

NUMTOYMINTERVAL(n, 'interval_unit')

NVL

NVL(expr1, expr2)

NVL2

NVL2(expr1, expr2, expr3)

ORA_DST_AFFECTED

ORA_DST_AFFECTED(datetime_expr)

ORA_DST_CONVERT

ORA_DST_CONVERT(datetime_expr [, integer [, integer]])

ORA_DST_ERROR

ORA_DST_ERROR(datetime_expr)

ORA_HASH

ORA_HASH(expr [, max_bucket [, seed_value]])

PATH

PATH(correlation_integer)

PERCENT_RANK (aggregate)

PERCENT_RANK(expr [, expr]...) WITHIN GROUP
(ORDER BY

```
expr [ DESC | ASC ]
      [NULLS { FIRST | LAST } ]
[, expr [ DESC | ASC ]
      [NULLS { FIRST | LAST } ]
]...
)
```

PERCENT_RANK (analytic)

PERCENT_RANK() OVER ([query_partition_clause] order_by_clause)

PERCENTILE_CONT

PERCENTILE_CONT(expr) WITHIN GROUP
(ORDER BY expr [DESC | ASC])
[OVER (query_partition_clause)]

PERCENTILE_DISC

PERCENTILE_DISC(expr) WITHIN GROUP
(ORDER BY expr [DESC | ASC])
[OVER (query_partition_clause)]

POWER

POWER(n2, n1)

POWERMULTISET

POWERMULTISET(expr)

POWERMULTISET_BY_CARDINALITY

POWERMULTISET_BY_CARDINALITY(expr, cardinality)

PREDICTION

PREDICTION ([schema .] model [cost_matrix_clause] mining_attribute_clause)

PREDICTION_BOUNDS

PREDICTION_BOUNDS
([schema.] model
[, confidence_level [, class_value]]
mining_attribute_clause
)

PREDICTION_COST

PREDICTION_COST ([schema .] model [, class] cost_matrix_clause
mining_attribute_clause)

PREDICTION_DETAILS

PREDICTION_DETAILS ([schema .] model mining_attribute_clause)

PREDICTION_PROBABILITY

PREDICTION_PROBABILITY ([schema .] model [, class]
mining_attribute_clause)

PREDICTION_SET

PREDICTION_SET ([schema .] model [, bestN [, cutoff]]
[cost_matrix_clause] mining_attribute_clause)

PRESENTNNV

PRESENTNNV(cell_reference, expr1, expr2)

PRESENTV

```
PRESENTV(cell_reference, expr1, expr2)
```

PREVIOUS

```
PREVIOUS(cell_reference)
```

RANK (aggregate)

```
RANK(expr [, expr ]...) WITHIN GROUP
  (ORDER BY
    expr [ DESC | ASC ]
        [ NULLS { FIRST | LAST } ]
    [, expr [ DESC | ASC ]
        [ NULLS { FIRST | LAST } ]
    ]...
  )
```

RANK (analytic)

```
RANK( )
  OVER ([ query_partition_clause ] order_by_clause)
```

RATIO_TO_REPORT

```
RATIO_TO_REPORT(expr)
  OVER ([ query_partition_clause ])
```

RAWTOHEX

```
RAWTOHEX(raw)
```

RAWTONHEX

```
RAWTONHEX(raw)
```

REF

```
REF (correlation_variable)
```

REFTOHEX

```
REFTOHEX (expr)
```

REGEXP_COUNT

```
REGEXP_COUNT (source_char, pattern [, position [, match_param]])
```

REGEXP_INSTR

```
REGEXP_INSTR (source_char, pattern
              [, position
                [, occurrence
                  [, return_opt
                    [, match_param
                      [, subexpr]
                ]
              ]
            ]
          ]
```

REGEXP_REPLACE

```
REGEXP_REPLACE(source_char, pattern
               [, replace_string
                 [, position
                   [, occurrence
                     [, match_param ]
```

```
    ]  
  ]  
]  
)
```

REGEXP_SUBSTR

```
REGEXP_SUBSTR(source_char, pattern  
              [, position  
              [, occurrence  
              [, match_param  
              [, subexpr  
              ]  
            ]  
          ]  
        ]  
      ]  
    )
```

**REGR_AVGX, REGR_AVGY, REGR_COUNT, REGR_INTERCEPT, REGR_R2,
REGR_SLOPE, REGR_SXX, REGR_SXY, REGR_SYY**

```
{ REGR_SLOPE  
| REGR_INTERCEPT  
| REGR_COUNT  
| REGR_R2  
| REGR_AVGX  
| REGR_AVGY  
| REGR_SXX  
| REGR_SYY  
| REGR_SXY  
}  
(expr1 , expr2)  
[ OVER (analytic_clause) ]
```

REMAINDER

```
REMAINDER(n2, n1)
```

REPLACE

```
REPLACE(char, search_string  
        [, replacement_string ]  
      )
```

ROUND (date)

```
ROUND(date [, fmt ])
```

ROUND (number)

```
ROUND(n [, integer ])
```

ROW_NUMBER

```
ROW_NUMBER( )  
  OVER ([ query_partition_clause ] order_by_clause)
```

ROWIDTOCHAR

```
ROWIDTOCHAR(rowid)
```

ROWIDTONCHAR

```
ROWIDTONCHAR(rowid)
```

RPAD

```
RPAD(expr1 , n [, expr2 ])
```

RTRIM

RTRIM(char [, set])

SCN_TO_TIMESTAMP

SCN_TO_TIMESTAMP(number)

SESSIONTIMEZONE

SESSIONTIMEZONE

SET

SET (nested_table)

SIGN

SIGN(n)

SIN

SIN(n)

SINH

SINH(n)

SOUNDEX

SOUNDEX(char)

SQRT

SQRT(n)

STATS_BINOMIAL_TEST

```
STATS_BINOMIAL_TEST(expr1, expr2, p
                    [, { TWO_SIDED_PROB
                        | EXACT_PROB
                        | ONE_SIDED_PROB_OR_MORE
                        | ONE_SIDED_PROB_OR_LESS
                    }
                    ]
                    )
```

STATS_CROSSTAB

```
STATS_CROSSTAB(expr1, expr2
               [, { CHISQ_OBS
                   | CHISQ_SIG
                   | CHISQ_DF
                   | PHI_COEFFICIENT
                   | CRAMERS_V
                   | CONT_COEFFICIENT
                   | COHENS_K
               }
               ]
               )
```

STATS_F_TEST

```
STATS_F_TEST(expr1, expr2
             [, { STATISTIC
                 | DF_NUM
                 | DF_DEN
                 | ONE_SIDED_SIG
             }
             , expr3
```

```
        | TWO_SIDED_SIG
      }
    ]
  )
```

STATS_KS_TEST

```
STATS_KS_TEST(expr1, expr2
              [, { STATISTIC | SIG } ]
            )
```

STATS_MODE

```
STATS_MODE(expr)
```

STATS_MW_TEST

```
STATS_MW_TEST(expr1, expr2
              [, { STATISTIC
                  | U_STATISTIC
                  | ONE_SIDED_SIG , expr3
                  | TWO_SIDED_SIG
                }
              ]
            )
```

STATS_ONE_WAY_ANOVA

```
STATS_ONE_WAY_ANOVA(expr1, expr2
                    [, { SUM_SQUARES_BETWEEN
                        | SUM_SQUARES_WITHIN
                        | DF_BETWEEN
                        | DF_WITHIN
                        | MEAN_SQUARES_BETWEEN
                        | MEAN_SQUARES_WITHIN
                        | F_RATIO
                        | SIG
                      }
                    ]
                  )
```

STATS_T_TEST_INDEP, STATS_T_TEST_INDEPU, STATS_T_TEST_ONE, STATS_T_TEST_PAIED

```
{ STATS_T_TEST_INDEP
| STATS_T_TEST_INDEPU
| STATS_T_TEST_ONE
| STATS_T_TEST_PAIED
}
(expr1, expr2
  [, { { STATISTIC
        | ONE_SIDED_SIG
      } , expr3
    | TWO_SIDED_SIG
    | DF
    }
  ]
)
```

STATS_WSR_TEST

```
STATS_WSR_TEST(expr1, expr2
              [, { STATISTIC
                  | ONE_SIDED_SIG
                  | TWO_SIDED_SIG
                }
              ]
            )
```

)

STDDEV

```
STDDEV([ DISTINCT | ALL ] expr)
      [ OVER (analytic_clause) ]
```

STDDEV_POP

```
STDDEV_POP(expr)
      [ OVER (analytic_clause) ]
```

STDDEV_SAMP

```
STDDEV_SAMP(expr)
      [ OVER (analytic_clause) ]
```

SUBSTR

```
{ SUBSTR
| SUBSTRB
| SUBSTRC
| SUBSTR2
| SUBSTR4
}
(char, position [, substring_length ])
```

SUM

```
SUM([ DISTINCT | ALL ] expr)
      [ OVER (analytic_clause) ]
```

SYS_CONNECT_BY_PATH

```
SYS_CONNECT_BY_PATH(column, char)
```

SYS_CONTEXT

```
SYS_CONTEXT('namespace', 'parameter' [, length ])
```

SYS_DBURIGEN

```
SYS_DBURIGEN({ column | attribute }
             [ rowid ]
             [, { column | attribute }
               [ rowid ]
             ]...
             [, 'text ( )' ]
             )
```

SYS_EXTRACT_UTC

```
SYS_EXTRACT_UTC(datetime_with_timezone)
```

SYS_GUID

```
SYS_GUID( )
```

SYS_TYPEID

```
SYS_TYPEID(object_type_value)
```

SYS_XMLAGG

```
SYS_XMLAGG(expr [, fmt ])
```

SYS_XMLGEN

```
SYS_XMLGEN(expr [, fmt ])
```

SYSDATE

`SYSDATE`

SYSTIMESTAMP

`SYSTIMESTAMP`

TAN

`TAN(n)`

TANH

`TANH(n)`

TIMESTAMP_TO_SCN

`TIMESTAMP_TO_SCN(timestamp)`

TO_BINARY_DOUBLE

`TO_BINARY_DOUBLE(expr [, fmt [, 'nlsparam']])`

TO_BINARY_FLOAT

`TO_BINARY_FLOAT(expr [, fmt [, 'nlsparam']])`

TO_BLOB

`TO_BLOB (raw_value)`

TO_CHAR (character)

`TO_CHAR(nchar | clob | nclob)`

TO_CHAR (datetime)

`TO_CHAR({ datetime | interval } [, fmt [, 'nlsparam']])`

TO_CHAR (number)

`TO_CHAR(n [, fmt [, 'nlsparam']])`

TO_CLOB

`TO_CLOB(lob_column | char)`

TO_DATE

`TO_DATE(char [, fmt [, 'nlsparam']])`

TO_DSINTERVAL

`TO_DSINTERVAL (' { sql_format | ds_iso_format } ')`

TO_LOB

`TO_LOB(long_column)`

TO_MULTI_BYTE

`TO_MULTI_BYTE(char)`

TO_NCHAR (character)

`TO_NCHAR({char | clob | nclob})`

TO_NCHAR (datetime)

```
TO_NCHAR({ datetime | interval }
        [, fmt [, 'nlsparam' ] ]
        )
```

TO_NCHAR (number)

```
TO_NCHAR(n [, fmt [, 'nlsparam' ] ])
```

TO_NCLOB

```
TO_NCLOB(lob_column | char)
```

TO_NUMBER

```
TO_NUMBER(expr [, fmt [, 'nlsparam' ] ])
```

TO_SINGLE_BYTE

```
TO_SINGLE_BYTE(char)
```

TO_TIMESTAMP

```
TO_TIMESTAMP(char [, fmt [, 'nlsparam' ] ])
```

TO_TIMESTAMP_TZ

```
TO_TIMESTAMP_TZ(char [, fmt [, 'nlsparam' ] ])
```

TO_YMINTERVAL

```
TO_YMINTERVAL
( ' { [+|-] years - months
  | ym_iso_format
} ' )
```

TRANSLATE

```
TRANSLATE(expr, from_string, to_string)
```

TRANSLATE ... USING

```
TRANSLATE ( char USING
           { CHAR_CS | NCHAR_CS }
           )
```

TREAT

```
TREAT(expr AS [ REF ] [ schema. ]type)
```

TRIM

```
TRIM([ { { LEADING | TRAILING | BOTH }
        [ trim_character ]
        | trim_character
      }
      FROM
    ]
    trim_source
    )
```

TRUNC (date)

```
TRUNC(date [, fmt ])
```

TRUNC (number)

```
TRUNC(n1 [, n2 ])
```

TZ_OFFSET

```
TZ_OFFSET({ 'time_zone_name'
           | '{ + | - } hh : mi'
           | SESSIONTIMEZONE
           | DBTIMEZONE
           })
```

UID

```
UID
```

UNISTR

```
UNISTR( string )
```

UPDATEXML

```
UPDATEXML
    (XMLType_instance,
     XPath_string, value_expr
     [, XPath_string, value_expr ]...
     [, namespace_string ]
    )
```

UPPER

```
UPPER(char)
```

USER

```
USER
```

user-defined function

```
[ schema. ]
{ [ package. ]function | user_defined_operator }
[ @ dblink. ]
[ ( [ [ DISTINCT | ALL ] expr [, expr ]... ] ) ]
```

USERENV

```
USERENV('parameter')
```

VALUE

```
VALUE(correlation_variable)
```

VAR_POP

```
VAR_POP(expr) [ OVER (analytic_clause) ]
```

VAR_SAMP

```
VAR_SAMP(expr) [ OVER (analytic_clause) ]
```

VARIANCE

```
VARIANCE([ DISTINCT | ALL ] expr)
        [ OVER (analytic_clause) ]
```

VSIZE

```
VSIZE(expr)
```

WIDTH_BUCKET

```
WIDTH_BUCKET
    (expr, min_value, max_value, num_buckets)
```

XMLAGG

```
XMLAGG(XMLType_instance [ order_by_clause ])
```

XMLCAST

```
XMLCAST ( value_expression AS datatype )
```

XMLCDATA

```
XMLCDATA ( value_expr )
```

XMLCOLATTVAL

```
XMLCOLATTVAL
  (value_expr [ AS { c_alias | EVALNAME value_expr } ]
   [, value_expr [ AS { c_alias | EVALNAME value_expr } ]
   ]...
  )
```

XMLCOMMENT

```
XMLCOMMENT ( value_expr )
```

XMLCONCAT

```
XMLCONCAT(XMLType_instance [, XMLType_instance ]...)
```

XMLDIFF

```
XMLDIFF ( XMLType_document, XMLType_document [ , integer, string ] )
```

XMLELEMENT

```
XMLELEMENT
  ( [ ENTITYESCAPING | NOENTITYESCAPING ]
    [ NAME ]
    { identifier
      | EVALNAME value_expr
    }
    [, XML_attributes_clause ]
    [, value_expr [ [AS] c_alias ]]...
  )
```

XMLEXISTS

```
XMLEXISTS ( XQuery_string [ XML_passing_clause ] )
```

XMLFOREST

```
XMLFOREST
  ( value_expr [ AS { c_alias | EVALNAME value_expr } ]
    [, value_expr [ AS { c_alias | EVALNAME value_expr } ]
    ]...
  )
```

XMLISVALID

```
XMLISVALID ( XMLType_instance [, XMLSchema_URL [, element ]] )
```

XMLPARSE

```
XMLPARSE
  ( { DOCUMENT | CONTENT } value_expr [ WELLFORMED ]
  )
```

XMLPATCH

```
XMLPATCH ( XMLType_document, XMLType_document )
```

XMLPI

```
XMLPI
( { [ NAME ] identifier
  | EVALNAME value_expr
  } [, value_expr ]
)
```

XMLQUERY

```
XMLQUERY
( XQuery_string
  [ XML_passing_clause ]
  RETURNING CONTENT [NULL ON EMPTY]
)
```

XMLROOT

```
XMLROOT
( value_expr, VERSION
  { value_expr | NO VALUE }
  [, STANDALONE { YES | NO | NO VALUE } ]
)
```

XMLSEQUENCE

```
XMLSEQUENCE( XMLType_instance
              | sys_refcursor_instance [, fmt ]
            )
```

XMLSERIALIZE

```
XMLSERIALIZE
( { DOCUMENT | CONTENT } value_expr [ AS datatype ]
  [ ENCODING xml_encoding_spec ]
  [ VERSION string_literal ]
  [ NO INDENT | { INDENT [SIZE = number] } ]
  [ { HIDE | SHOW } DEFAULTS ]
)
```

XMLTABLE

```
XMLTABLE
(
  [ XMLnamespaces_clause , ] XQuery_string XMLTABLE_options
)
```

XMLTRANSFORM

```
XMLTRANSFORM(XMLType_instance, { XMLType_instance
                                   | string
                                   }
              )
```

SQL Expressions

This chapter presents the syntax for combining values, operators, and functions into expressions.

This chapter includes the following section:

- [Syntax for SQL Expression Types](#)

Syntax for SQL Expression Types

An expression is a combination of one or more values, operators, and SQL functions that evaluate to a value. An expression generally assumes the data type of its components.

Expressions have several forms. The sections that follow show the syntax for each form of expression. Refer to [Chapter 5, "Subclauses"](#) for the syntax of the subclauses.

See Also: Expressions in *Oracle Database SQL Language Reference* for detailed information about SQL expressions

CASE expressions

```
CASE { simple_case_expression
      | searched_case_expression
      }
    [ else_clause ]
END
```

Column expressions

A column expression can be a simple expression, compound expression, function expression, or expression list, containing only columns of the subject table, constants, and deterministic functions.

Compound expressions

```
{ (expr)
| { + | - | PRIOR } expr
| expr { * | / | + | - | || } expr
}
```

Note: The double vertical bars are part of the syntax (indicating concatenation) rather than BNF notation.

CURSOR expressions

```
CURSOR (subquery)
```

Datetime expressions

```
expr AT
{ LOCAL
| TIME_ZONE { ' [ + | - ] hh:mm'
| DBTIMEZONE
| 'time_zone_name'
| expr
}
}
```

Function expressions

You can use any built-in SQL function or user-defined function as an expression.

Interval expressions

```
( expr1 - expr2 )
{ DAY [ (leading_field_precision) ] TO
SECOND [ (fractional_second_precision) ]
| YEAR [ (leading_field_precision) ] TO
MONTH
}
```

Model expressions

```
{ measure_column [ { condition | expr } [ , { condition | expr } ... ] ]
| aggregate_function
{ [ { condition | expr } [ , { condition | expr } ... ] ]
| [ single_column_for_loop [ , single_column_for_loop ] ... ]
| [ multi_column_for_loop ]
}
| analytic_function
}
```

Note: The outside square brackets shown in boldface type are part of the syntax. In this case, they do not represent optionality.

Object access expressions

```
{ table_alias.column.
| object_table_alias.
| (expr).
}
{ attribute [.attribute] ...
[.method ([ argument [, argument ] ... ]) ]
| method ([ argument [, argument ] ... ])
}
```

Placeholder expressions

```
:host_variable
[ [ INDICATOR ]
:indicator_variable
]
```

Scalar subquery expressions

A scalar subquery expression is a subquery that returns exactly one column value from one row.

Simple expressions

```
{ [ query_name.
| [schema.]
{ table. | view. | materialized view. }
```

```
] { column | ROWID }  
| ROWNUM  
| string  
| number  
| sequence. { CURRVAL | NEXTVAL }  
| NULL  
}
```

Type constructor expressions

```
[ NEW ] [ schema. ]type_name  
    ([ expr [, expr ]... ])
```

SQL Conditions

This chapter presents the syntax for combining one or more expressions and logical (Boolean) operators to specify a condition.

This chapter includes the following section:

- [Syntax for SQL Condition Types](#)

Syntax for SQL Condition Types

A condition specifies a combination of one or more expressions and logical (Boolean) operators and returns a value of TRUE, FALSE, or unknown.

Conditions have several forms. The sections that follow show the syntax for each form of condition. Refer to [Chapter 5, "Subclauses"](#) for the syntax of the subclauses.

See Also: Conditions in *Oracle Database SQL Language Reference* for detailed information about SQL conditions

BETWEEN condition

```
expr1 [ NOT ] BETWEEN expr2 AND expr3
```

Compound conditions

```
{ (condition)
| NOT condition
| condition { AND | OR } condition
}
```

EQUALS_PATH condition

```
EQUALS_PATH
(column, path_string [, correlation_integer ])
```

EXISTS condition

```
EXISTS (subquery)
```

Floating-point conditions

```
expr IS [ NOT ] { NAN | INFINITE }
```

Group comparison conditions

```
{ expr
  { = | != | ^= | <> | > | < | >= | <= }
  { ANY | SOME | ALL }
  ({ expression_list | subquery })
| ( expr [, expr ]... )
```

```
{ = | != | ^= | <> }
{ ANY | SOME | ALL }
({ expression_list
  [, expression_list ]...
  | subquery
  }
)
```

where !=, ^=, and <> test for inequality

IN condition

```
{ expr [ NOT ] IN ({ expression_list | subquery })
| ( expr [, expr ]... )
  [ NOT ] IN ({ expression_list [, expression_list ]...
              | subquery
              }
            )
}
```

IS A SET condition

```
nested_table IS [ NOT ] A SET
```

IS ANY condition

```
[ dimension_column IS ] ANY
```

IS EMPTY condition

```
nested_table IS [ NOT ] EMPTY
```

IS OF *type* condition

```
expr IS [ NOT ] OF [ TYPE ]
  ([ ONLY ] [ schema. ] type
  [, [ ONLY ] [ schema. ] type ]...
  )
```

IS PRESENT condition

```
cell_reference IS PRESENT
```

LIKE condition

```
char1 [ NOT ] { LIKE | LIKEC | LIKE2 | LIKE4 }
char2 [ ESCAPE esc_char ]
```

Logical conditions

```
{ NOT | AND | OR }
```

MEMBER condition

```
expr [ NOT ] MEMBER [ OF ] nested_table
```

Null conditions

```
expr IS [ NOT ] NULL
```

REGEXP_LIKE condition

```
REGEXP_LIKE(source_char, pattern
             [, match_param ]
             )
```

Simple comparison conditions

```
{ expr
  { = | != | ^= | <> | > | < | >= | <= }
  expr
| (expr [, expr ]...)
  { = | != | ^= | <> }
  (subquery)
}
```

where !=, ^=, and <> test for inequality

SUBMULTISET condition

```
nested_table1
[ NOT ] SUBMULTISET [ OF ]
nested_table2
```

UNDER_PATH condition

```
UNDER_PATH (column [, levels ], path_string
            [, correlation_integer ]
            )
```


Subclauses

This chapter presents the syntax for the subclauses found in the syntax for SQL statements, functions, expressions and conditions.

This chapter includes the following section:

- [Syntax for Subclauses](#)

Syntax for Subclauses

The sections that follow show the syntax for each subclause found in:

- [Chapter 1, "SQL Statements"](#)
- [Chapter 2, "SQL Functions"](#)
- [Chapter 3, "SQL Expressions"](#)
- [Chapter 4, "SQL Conditions"](#)

See Also: *Oracle Database SQL Language Reference* for detailed information about Oracle SQL

activate_standby_db_clause

```
ACTIVATE
  [ PHYSICAL | LOGICAL ]
  STANDBY DATABASE
  [ FINISH APPLY ]
```

add_binding_clause

```
ADD BINDING
  (parameter_type [, parameter_type ]...)
  RETURN (return_type)
  [ implementation_clause ]
  using_function_clause
```

add_column_clause

```
ADD
  {column_definition | virtual_column_definition
    [, column_definition | virtual_column_definition] ...
  }
  [ column_properties ]
  [ out_of_line_part_storage [, out_of_line_part_storage]...]
```

add_disk_clause

```
ADD
  { [ QUORUM | REGULAR ] [ FAILGROUP failgroup_name ]
```

```
DISK qualified_disk_clause [, qualified_disk_clause ]...
}...
```

add_hash_index_partition

```
ADD PARTITION
[ partition_name ]
[ TABLESPACE tablespace_name ]
[ key_compression ]
[ parallel_clause ]
```

add_hash_partition_clause

```
ADD PARTITION [ partition ]
partitioning_storage_clause
[ update_index_clauses ]
[ parallel_clause ]
```

add_hash_subpartition

```
ADD hash_subpartition_desc
[ dependent_tables_clause ]
[ update_index_clauses ]
[ parallel_clause ]
```

add_list_partition_clause

```
ADD PARTITION [ partition ]
list_values_clause
[ table_partition_description ]
[ { range_subpartition_desc
  | list_subpartition_desc
  | hash_subpartition_desc
  }
]
[ update_index_clauses ]
```

add_list_subpartition

```
ADD list_subpartition_desc [ dependent_tables_clause ] [ update_index_clauses ]
```

add_logfile_clauses

```
ADD [ STANDBY ] LOGFILE
{
  { [ INSTANCE 'instance_name' ] | [ THREAD 'integer' ] }
  [ GROUP integer ] redo_log_file_spec
  [, [ GROUP integer ] redo_log_file_spec ]...
  | MEMBER 'filename' [ REUSE ] [, 'filename' [ REUSE ] ]...
  TO logfile_descriptor [, logfile_descriptor ]...
}
```

add_mv_log_column_clause

```
ADD (column)
```

add_overflow_clause

```
ADD OVERFLOW [ segment_attributes_clause ]
[ ( PARTITION [ segment_attributes_clause ]
  [, PARTITION [ segment_attributes_clause ] ]...
  )
]
```

add_range_partition_clause

```
ADD PARTITION [ partition ]
range_values_clause
```

```

[ table_partition_description ]
[ ( { range_subpartition_desc
    | list_subpartition_desc
    | hash_subpartition_desc
    }
)
]
[ update_index_clauses ]

```

add_range_subpartition

```
ADD range_subpartition_desc [ dependent_tables_clause ] [ update_index_clauses ]
```

add_system_partition_clause

```

[BEFORE { partition_name | partition_number }]
[table_partition_description]
[update_index_clauses]

```

add_table_partition

```

{ add_range_partition_clause
| add_hash_partition_clause
| add_list_partition_clause
} [ dependent_tables_clause ]

```

add_volume_clause

```

ADD VOLUME asm_volume SIZE size_clause [redundancy_clause]
[ STRIPE_WIDTH integer {K | M} ]
[ STRIPE_COLUMNS integer ]
[ ATTRIBUTE disk_region_clause ]

```

alias_file_name

```
+diskgroup_name [ (template_name) ] /alias_name
```

allocate_extent_clause

```

ALLOCATE EXTENT
[ ( { SIZE size_clause
    | DATAFILE 'filename'
    | INSTANCE integer
    } ...
)
]

```

alter_datafile_clause

```

DATAFILE
{ 'filename' | filenumber }
[, 'filename' | filenumber ]...
}
{ ONLINE
| OFFLINE [ FOR DROP ]
| RESIZE size_clause
| autoextend_clause
| END BACKUP
}

```

alter_external_table

```

{ add_column_clause
| modify_column_clauses
| drop_column_clause
| parallel_clause
| external_data_properties
| REJECT LIMIT { integer | UNLIMITED }
}

```

```
| PROJECT COLUMN { ALL | REFERENCED }
}
[ add_column_clause
| modify_column_clauses
| drop_column_clause
| parallel_clause
| external_data_properties
| REJECT LIMIT { integer | UNLIMITED }
| PROJECT COLUMN { ALL | REFERENCED }
]...
```

alter_index_partitioning

```
{ modify_index_default_attrs
| add_hash_index_partition
| modify_index_partition
| rename_index_partition
| drop_index_partition
| split_index_partition
| coalesce_index_partition
| modify_index_subpartition
}
```

alter_interval_partitioning

```
{ SET INTERVAL ( [ expr ] )
| SET STORE IN ( tablespace [, tablespace]... )
}
```

alter_iot_clauses

```
{ index_org_table_clause
| alter_overflow_clause
| alter_mapping_table_clauses
| COALESCE
}
```

alter_mapping_table_clauses

```
MAPPING TABLE
{ allocate_extent_clause
| deallocate_unused_clause
}
```

alter_mv_refresh

```
REFRESH
{ { FAST | COMPLETE | FORCE }
| ON { DEMAND | COMMIT }
| { START WITH | NEXT } date
| WITH PRIMARY KEY
| USING
    { DEFAULT MASTER ROLLBACK SEGMENT
    | MASTER ROLLBACK SEGMENT rollback_segment
    }
| USING { ENFORCED | TRUSTED } CONSTRAINTS
}
```

alter_overflow_clause

```
{ add_overflow_clause
| OVERFLOW
    { segment_attributes_clause
    | allocate_extent_clause
    | shrink_clause
    | deallocate_unused_clause
    }...
}
```


alter_session_set_clause

```
SET { { parameter_name = parameter_value }...
    | EDITION = edition_name
  }
```

alter_system_reset_clause

```
parameter_name
[ { SCOPE = SPFILE
  | SID = { 'sid' | '*' }
  }...
]
```

alter_system_set_clause

```
{ set_parameter_clause
| USE_STORED_OUTLINES = (TRUE | FALSE | category_name)
| GLOBAL_TOPIC_ENABLED = (TRUE | FALSE)
}
```

alter_table_partitioning

```
{ modify_table_default_attrs
| alter_interval_partitioning
| set_subpartition_template
| modify_table_partition
| modify_table_subpartition
| move_table_partition
| move_table_subpartition
| add_table_partition
| coalesce_table_partition
| coalesce_table_subpartition
| drop_table_partition
| drop_table_subpartition
| rename_partition_subpart
| truncate_partition_subpart
| split_table_partition
| split_table_subpartition
| merge_table_partitions
| merge_table_subpartitions
| exchange_partition_subpart
}
```

alter_table_properties

```
{ { { physical_attributes_clause
  | logging_clause
  | table_compression
  | supplemental_table_logging
  | allocate_extent_clause
  | deallocate_unused_clause
  | { CACHE | NOCACHE }
  | RESULT_CACHE ( MODE {DEFAULT | FORCE} )
  | upgrade_table_clause
  | records_per_block_clause
  | parallel_clause
  | row_movement_clause
  | flashback_archive_clause
  }...
| RENAME TO new_table_name
} [ alter_iot_clauses ] [ alter_XMLSchema_clause ]
| { shrink_clause
  | READ ONLY
  | READ WRITE
  | REKEY encryption_spec
  }
}
```

alter_tempfile_clause

```
TEMPFILE
{ 'filename' [, 'filename' ]...
| filenumber [, filenumber ]...
}
{ RESIZE size_clause
| autoextend_clause
| DROP [ INCLUDING DATAFILES ]
| ONLINE
| OFFLINE
}
```

alter_varray_col_properties

```
MODIFY VARRAY varray_item
( modify_LOB_parameters )
```

alter_XMLSchema_clause

```
{ ALLOW ANYSCHEMA
| ALLOW NONSCHEMA
| DISALLOW NONSCHEMA
}
```

analytic_clause

```
[ query_partition_clause ]
[ order_by_clause [ windowing_clause ] ]
```

archive_log_clause

```
ARCHIVE LOG
[ INSTANCE 'instance_name' ]
{ { SEQUENCE integer
| CHANGE integer
| CURRENT [ NOSWITCH ]
| GROUP integer
| LOGFILE 'filename'
[ USING BACKUP CONTROLFILE ]
| NEXT
| ALL
}
[ TO 'location' ]
}
```

array_DML_clause

```
[ WITH | WITHOUT ]
ARRAY DML
[ ([ schema. ]type
[, [ schema. ]varray_type ])
[, ([ schema. ]type
[, [ schema. ]varray_type ])...
]
```

ASM_filename

```
{ fully_qualified_file_name
| numeric_file_name
| incomplete_file_name
| alias_file_name
}
```

attribute_clause

```
ATTRIBUTE level DETERMINES
{ dependent_column
```

```

    | ( dependent_column
      [, dependent_column ]... )
  }

```

audit_operation_clause

```

{ { sql_statementShortcut
  | ALL
  | ALL STATEMENTS
} [, { sql_statementShortcut
    | ALL
    }
]
| { system_privilege
  | ALL PRIVILEGES
} [, { system_privilege
    | ALL PRIVILEGES
    }
]
}

```

audit_schema_object_clause

```

{ sql_operation [, object_option]
| ALL
} auditing_on_clause

```

auditing_by_clause

```

BY user [, user ]...

```

auditing_on_clause

```

ON { [ schema. ] object
    | DIRECTORY directory_name
    | MINING MODEL [ schema. ] model
    | DEFAULT
  }

```

autoextend_clause

```

AUTOEXTEND
{ OFF
| ON [ NEXT size_clause ]
    [ maxsize_clause ]
}

```

binding_clause

```

BINDING
(parameter_type [, parameter_type ]...)
RETURN return_type
[ implementation_clause ]
using_function_clause
[, (parameter_type [, parameter_type ]...)
    RETURN return_type
    [ implementation_clause ]
    using_function_clause
]...

```

bitmap_join_index_clause

```

[ schema. ]table
( [ [ schema. ]table. | t_alias. ]column
  [ ASC | DESC ]
  [, [ [ schema. ]table. | t_alias. ]column
    [ ASC | DESC ]
  ]...

```

```
)  
FROM [ schema. ]table [ t_alias ]  
    [, [ schema. ]table [ t_alias ]  
    ]...  
WHERE condition  
    [ local_partitioned_index ] index_attributes
```

build_clause

```
BUILD { IMMEDIATE | DEFERRED }
```

cell_assignment

```
measure_column [ { { condition  
                    | expr  
                    | single_column_for_loop  
                    }  
                [, { condition  
                    | expr  
                    | single_column_for_loop  
                    }  
                ]...  
                | multi_column_for_loop  
                }  
            ]
```

Note: The outer square brackets are part of the syntax.
In this case, they do not indicate optionality.

cell_reference_options

```
[ { IGNORE | KEEP } NAV ]  
[ UNIQUE { DIMENSION | SINGLE REFERENCE } ]
```

character_set_clause

```
CHARACTER SET character_set
```

check_datafiles_clause

```
CHECK DATAFILES [ GLOBAL | LOCAL ]
```

check_diskgroup_clause

```
CHECK [ REPAIR | NOREPAIR ]
```

checkpoint_clause

```
CHECKPOINT [ GLOBAL | LOCAL ]
```

cluster_index_clause

```
CLUSTER [ schema. ] cluster index_attributes
```

coalesce_index_partition

```
COALESCE PARTITION [ parallel_clause ]
```

coalesce_table_partition

```
COALESCE PARTITION [ update_index_clauses ] [ parallel_clause ]
```

coalesce_table_subpartition

```
COALESCE SUBPARTITION subpartition [update_index_clauses] [parallel_clause]
```

column_association

```
COLUMNS [ schema. ]table.column
```

```

        [, [ schema. ]table.column ]...
using_statistics_type

```

column_clauses

```

{ { add_column_clause
  | modify_column_clause
  | drop_column_clause
  }...
| rename_column_clause
| { modify_collection_retrieval }...
| { modify_LOB_storage_clause }...
| { alter_varray_col_properties }...
}

```

column_definition

```

column datatype [ SORT ]
[ DEFAULT expr ]
[ ENCRYPT encryption_spec ]
[ ( { inline_constraint }... )
| inline_ref_constraint
]

```

column_properties

```

{ object_type_col_properties
| nested_table_col_properties
| { varray_col_properties | LOB_storage_clause
  [ (LOB_partition_storage [, LOB_partition_storage ]...) ]
| XMLType_column_properties
}...

```

commit_switchover_clause

```

{ PREPARE | COMMIT } TO SWITCHOVER
[ TO { { [ PHYSICAL | LOGICAL ] PRIMARY
  | [ PHYSICAL ] STANDBY
  } [ { WITH | WITHOUT } SESSION SHUTDOWN
    { WAIT | NOWAIT }
  ]
  | LOGICAL STANDBY
  }
| CANCEL
]

```

composite_hash_partitions

```

PARTITION BY HASH (column [, column ] ...)
{ subpartition_by_range
  | subpartition_by_hash
  | subpartition_by_list
  }
{ individual_hash_partitions
  | hash_partitions_by_quantity
  }

```

composite_list_partitions

```

PARTITION BY LIST ( column )
{ subpartition_by_range
  | subpartition_by_hash
  | subpartition_by_list
  }
( { PARTITION [partition] list_partition_desc }... )

```

composite_range_partitions

```
PARTITION BY RANGE ( column [, column]... )
  [ INTERVAL ( expr ) [ STORE IN ( tablespace [, tablespace]... ) ]]
  { subpartition_by_range
    | subpartition_by_list
    | subpartition_by_hash
  }
( { PARTITION [partition] range_partition_desc }... )
```

conditional_insert_clause

```
[ ALL | FIRST ]
WHEN condition
THEN insert_into_clause
  [ values_clause ]
  [ error_logging_clause ]
  [ insert_into_clause [ values_clause ] [ error_logging_clause ] ]...
[ WHEN condition
  THEN insert_into_clause
    [ values_clause ]
    [ error_logging_clause ]
    [ insert_into_clause [ values_clause ] [ error_logging_clause ] ]...
]...
[ ELSE insert_into_clause
  [ values_clause ]
  [ error_logging_clause ]
  [ insert_into_clause [ values_clause ] [ error_logging_clause ] ]...
]
```

constraint

```
{ inline_constraint
| out_of_line_constraint
| inline_ref_constraint
| out_of_line_ref_constraint
}
```

constraint_clauses

```
{ ADD { { out_of_line_constraint }...
        | out_of_line_REF_constraint
      }
| MODIFY { CONSTRAINT constraint
          | PRIMARY KEY
          | UNIQUE (column [, column ]...)
        } constraint_state
| RENAME CONSTRAINT old_name TO new_name
| drop_constraint_clause
}
```

constraint_state

```
[ [ [ NOT ] DEFERRABLE ]
  [ INITIALLY { IMMEDIATE | DEFERRED } ]
| [ INITIALLY { IMMEDIATE | DEFERRED } ]
  [ [ NOT ] DEFERRABLE ]
]
[ RELY | NORELY ]
[ using_index_clause ]
[ ENABLE | DISABLE ]
[ VALIDATE | NOVALIDATE ]
[ exceptions_clause ]
```

context_clause

```
[ WITH INDEX CONTEXT,
  SCAN CONTEXT implementation_type
```

```

    [ COMPUTE ANCILLARY DATA ]
]
[ WITH COLUMN CONTEXT ]

```

controlfile_clauses

```

{ CREATE [ LOGICAL | PHYSICAL ]
  STANDBY CONTROLFILE AS
    'filename' [ REUSE ]
| BACKUP CONTROLFILE TO
  { 'filename' [ REUSE ]
    | trace_file_clause
  }
}

```

convert_database_clause

```

CONVERT TO ( PHYSICAL | SNAPSHOT ) STANDBY

```

cost_matrix_clause

```

COST
{ MODEL [AUTO]
  | ( class_value [, class_value]... )
    VALUES ( ( cost_value [, cost_value]... )
              [ , (cost_value [, cost_value]... ) ]...
            )
}

```

create_datafile_clause

```

CREATE DATAFILE
  { 'filename' | filenumber }
  [, 'filename' | filenumber ]...
}
[ AS { file_specification
      [, file_specification ]...
      | NEW
    }
]

```

create_mv_refresh

```

{ REFRESH
  { { FAST | COMPLETE | FORCE }
    | { ON DEMAND
      | ON COMMIT
    }
  | { START WITH date |
      NEXT date
    }...
  | WITH { PRIMARY KEY | ROWID }
  | USING
    { DEFAULT [ MASTER | LOCAL ] ROLLBACK SEGMENT
      | [ MASTER | LOCAL ] ROLLBACK SEGMENT rollback_segment
    }...
  | USING
    { ENFORCED | TRUSTED } CONSTRAINTS
  }...
| NEVER REFRESH
}

```

cycle_clause

```

{CYCLE c_alias [, c_alias]...
  SET cycle_mark_c_alias TO cycle_value
  DEFAULT no_cycle_value
}

```

```
}
```

database_file_clauses

```
{ RENAME FILE 'filename' [, 'filename' ]...  
  TO 'filename'  
| create_datafile_clause  
| alter_datafile_clause  
| alter_tempfile_clause  
}
```

database_logging_clauses

```
{ LOGFILE  
  [ GROUP integer ] file_specification  
  [, [ GROUP integer ] file_specification ]...  
| MAXLOGFILES integer  
| MAXLOGMEMBERS integer  
| MAXLOGHISTORY integer  
| { ARCHIVELOG | NOARCHIVELOG }  
| FORCE LOGGING  
}
```

datafile_tempfile_clauses

```
{ ADD { DATAFILE | TEMPFILE }  
  [ file_specification [, file_specification ]... ]  
| DROP {DATAFILE | TEMPFILE } { 'filename' | file_number }  
| SHRINK TEMPFILE { 'filename' | file_number } [KEEP size_clause]  
| RENAME DATAFILE 'filename' [, 'filename' ]...  
  TO 'filename' [, 'filename' ]...  
| { DATAFILE | TEMPFILE } { ONLINE | OFFLINE }  
}
```

datafile_tempfile_spec

```
[ 'filename' | 'ASM_filename' ]  
[ SIZE size_clause ]  
[ REUSE ]  
[ autoextend_clause ]
```

db_user_proxy_clauses

```
[ WITH  
  { ROLE { role_name [, role_name]...  
    | ALL EXCEPT role_name [, role_name]...  
  }  
| NO ROLES  
}  
]  
[ AUTHENTICATION REQUIRED ]
```

dblink

```
database[.domain [.domain ]... ] [ @ connection_qualifier ]
```

dblink_authentication

```
AUTHENTICATED BY user IDENTIFIED BY password
```

deallocate_unused_clause

```
DEALLOCATE UNUSED [ KEEP size_clause ]
```

default_cost_clause

```
DEFAULT COST (cpu_cost, io_cost, network_cost)
```


default_selectivity_clause

```
DEFAULT SELECTIVITY default_selectivity
```

default_settings_clauses

```
{ DEFAULT EDITION = edition_name
| SET DEFAULT
    { BIGFILE | SMALLFILE } TABLESPACE
| DEFAULT TABLESPACE tablespace
| DEFAULT TEMPORARY TABLESPACE
    { tablespace | tablespace_group_name }
| RENAME GLOBAL_NAME TO
    database.domain [.domain ]...
| { ENABLE BLOCK CHANGE TRACKING
    [ USING FILE 'filename' [ REUSE ] ]
  | DISABLE BLOCK CHANGE TRACKING
  }
| flashback_mode_clause
| set_time_zone_clause
}
```

default_tablespace

```
DEFAULT TABLESPACE tablespace
[ DATAFILE datafile_tempfile_spec ]
extent_management_clause
```

default_temp_tablespace

```
    [ BIGFILE | SMALLFILE ]
DEFAULT TEMPORARY TABLESPACE tablespace
    [ TEMPFILE file_specification [, file_specification ]...]
extent_management_clause
```

deferred_segment_creation

```
SEGMENT CREATION { IMMEDIATE | DEFERRED }
```

dependent_tables_clause

```
DEPENDENT TABLES
( table ( partition_spec [, partition_spec]...
        [, table ( partition_spec [, partition_spec]... ]
        )
)
```

dimension_join_clause

```
{ JOIN KEY
  { child_key_column
    | (child_key_column [, child_key_column ]...)
  }
  REFERENCES parent_level
}...
```

disk_offline_clause

```
OFFLINE
  { [QUORUM | REGULAR] DISK disk_name [, disk_name ] ...
  | DISKS IN [QUORUM | REGULAR] FAILGROUP failgroup_name [, failgroup_name ]...
  } ... [timeout_clause]
```

disk_online_clause

```
ONLINE
  { { [QUORUM | REGULAR] DISK disk_name [, disk_name]...
    | DISKS IN [QUORUM | REGULAR] FAILGROUP failgroup_name [, failgroup_name]...
  } ...
```

```
| ALL  
} [ WAIT | NOWAIT ]
```

disk_region_clause

```
[ HOT | COLD ] [ MIRRORHOT | MIRRORCOLD ]
```

diskgroup_alias_clauses

```
{ ADD ALIAS  
    'alias_name' FOR 'filename'  
    [, 'alias_name' FOR 'filename' ]...  
| DROP ALIAS 'alias_name' [, 'alias_name' ]...  
| RENAME ALIAS  
    'old_alias_name' TO 'new_alias_name'  
    [, 'old_alias_name' TO 'new_alias_name' ]...  
}
```

diskgroup_attributes

```
SET ATTRIBUTE 'attribute_name' = 'attribute_value'
```

diskgroup_availability

```
{ MOUNT [ RESTRICTED | NORMAL ]  
    [ FORCE | NOFORCE ]  
| DISMOUNT [ FORCE | NOFORCE ]  
}
```

diskgroup_directory_clauses

```
{ ADD DIRECTORY 'filename' [, 'filename' ]...  
| DROP DIRECTORY  
    'filename' [ FORCE | NOFORCE ]  
    [, 'filename' [ FORCE | NOFORCE ] ]...  
| RENAME DIRECTORY  
    'old_dir_name' TO 'new_dir_name'  
    [, 'old_dir_name' TO 'new_dir_name' ]...  
}
```

diskgroup_template_clauses

```
{ { ADD | MODIFY } TEMPLATE template_name qualified_template_clause  
    [, template_name qualified_template_clause ]...  
| DROP TEMPLATE template_name [, template_name ]...  
}
```

diskgroup_volume_clauses

```
{ add_volume_clause  
| modify_volume_clause  
| RESIZE VOLUME asm_volume SIZE size_clause  
| DROP VOLUME asm_volume  
}
```

distributed_recov_clauses

```
{ ENABLE | DISABLE } DISTRIBUTED RECOVERY
```

dml_table_expression_clause

```
{ [ schema. ]  
    { table  
        [ partition_extension_clause  
        | @ dblink  
        ]  
    | { view | materialized view } [ @ dblink ]  
}
```

```
| ( subquery [ subquery_restriction_clause ] )
| table_collection_expression
}
```

domain_index_clause

```
indextype
[ local_domain_index_clause ]
[ parallel_clause ]
[ PARAMETERS ('ODCI_parameters') ]
```

drop_binding_clause

```
DROP BINDING (parameter_type [, parameter_type ]...)
[ FORCE ]
```

drop_column_clause

```
{ SET UNUSED { COLUMN column
                | (column [, column ]...)
              }
  [ { CASCADE CONSTRAINTS | INVALIDATE }... ]
| DROP { COLUMN column
        | (column [, column ]...)
      }
  [ { CASCADE CONSTRAINTS | INVALIDATE }... ]
  [ CHECKPOINT integer ]
| DROP { UNUSED COLUMNS
        | COLUMNS CONTINUE
      }
  [ CHECKPOINT integer ]
}
```

drop_constraint_clause

```
DROP
{ { PRIMARY KEY
  | UNIQUE (column [, column ]...)
  }
  [ CASCADE ]
  [ { KEEP | DROP } INDEX ]
| CONSTRAINT constraint
  [ CASCADE ]
}
```

drop_disk_clauses

```
DROP
{ [QUORUM | REGULAR] DISK
  disk_name [ FORCE | NOFORCE ]
  [, disk_name [ FORCE | NOFORCE ] ]...
| DISKS IN [QUORUM | REGULAR] FAILGROUP
  failgroup_name [ FORCE | NOFORCE ]
  [, failgroup_name [ FORCE | NOFORCE ] ]...
}
```

drop_diskgroup_file_clause

```
DROP FILE 'filename' [, 'filename' ]...
```

drop_index_partition

```
DROP PARTITION partition_name
```

drop_logfile_clauses

```
DROP [ STANDBY ] LOGFILE
{ logfile_descriptor
```

```
    [, logfile_descriptor ]...  
  | MEMBER 'filename'  
    [, 'filename' ]...  
}
```

drop_table_partition

```
DROP partition_extended_name  
  [ update_index_clauses [ parallel_clause ] ]
```

drop_table_subpartition

```
DROP subpartition_extended_name  
  [ update_index_clauses [ parallel_clause ] ]
```

ds_iso_format

```
[ - ] P [days D]  
  [T [hours H] [minutes M] [seconds [. frac_secs] S ] ]
```

else_clause

```
ELSE else_expr
```

enable_disable_clause

```
{ ENABLE | DISABLE }  
[ VALIDATE | NOVALIDATE ]  
{ UNIQUE (column [, column ]...) |  
  PRIMARY KEY |  
  CONSTRAINT constraint  
}  
[ using_index_clause ]  
[ exceptions_clause ]  
[ CASCADE ]  
[ { KEEP | DROP } INDEX ]
```

enable_disable_volumes

```
{ ENABLE | DISABLE } VOLUME  
  { asm_volume [, asm_volume]...  
  | ALL  
  }
```

encryption_spec

```
[ USING 'encrypt_algorithm' ]  
[ IDENTIFIED BY password ]  
[ 'integrity_algorithm' ]  
[ [ NO ] SALT ]
```

end_session_clauses

```
{ DISCONNECT SESSION 'integer1, integer2'  
  [ POST_TRANSACTION ]  
| KILL SESSION 'integer1, integer2 [, @integer3]'  
}  
[ IMMEDIATE ]
```

error_logging_clause

```
LOG ERRORS  
  [ INTO [schema.] table ]  
  [ (simple_expression) ]  
  [ REJECT LIMIT { integer | UNLIMITED } ]
```

exceptions_clause

```
EXCEPTIONS INTO [ schema. ] table
```

exchange_partition_subpart

```
EXCHANGE { partition_extended_name
          | subpartition_extended_name
          }
WITH TABLE [ schema. ] table
[ { INCLUDING | EXCLUDING } INDEXES ]
[ { WITH | WITHOUT } VALIDATION ]
[ exceptions_clause ]
[ update_index_clauses [ parallel_clause ] ]
```

expr

```
{ simple_expression
| compound_expression
| case_expression
| cursor_expression
| datetime_expression
| function_expression
| interval_expression
| object_access_expression
| scalar_subquery_expression
| model_expression
| type_constructor_expression
| variable_expression
}
```

expression_list

```
{ expr [, expr ]...
| ( [expr [, expr ]] ...)
}
```

extended_attribute_clause

```
ATTRIBUTE attribute
{ LEVEL level
  DETERMINES { dependent_column
              | (dependent_column [, dependent_column ]... )
  }
}...
```

extent_management_clause

```
EXTENT MANAGEMENT LOCAL
[ AUTOALLOCATE
| UNIFORM [ SIZE size_clause ]
]
```

external_data_properties

```
DEFAULT DIRECTORY directory
[ ACCESS PARAMETERS
  { (opaque_format_spec)
  | USING CLOB subquery
  }
]
LOCATION
([ directory: ] 'location_specifier'
[, [ directory: ] 'location_specifier' ]...
)
```

external_table_clause

```
([ TYPE access_driver_type ]
  external_data_properties
)
[ REJECT LIMIT { integer | UNLIMITED } ]
```

file_owner_clause

```
SET OWNERSHIP { OWNER = user | GROUP = usergroup
               [, OWNER = user | GROUP = usergroup ]...
               } FOR FILE 'filename' [, 'filename']...
```

file_permissions_clause

```
SET PERMISSION { OWNER | GROUP | OTHER }
= { NONE | READ ONLY | READ WRITE }
[, { OWNER | GROUP | OTHER | ALL }
  = { NONE | READ ONLY | READ WRITE } ]...
FOR FILE 'filename' [, 'filename']...
```

file_specification

```
{ datafile_tempfile_spec
| redo_log_file_spec
}
```

flashback_archive_clause

```
FLASHBACK ARCHIVE [flashback_archive] | NO FLASHBACK ARCHIVE
```

flashback_archive_quota

```
QUOTA integer { M | G | T | P | E }
```

flashback_archive_retention

```
RETENTION integer {YEAR | MONTH | DAY}
```

flashback_mode_clause

```
FLASHBACK { ON | OFF }
```

flashback_query_clause

```
{ VERSIONS BETWEEN
  { SCN | TIMESTAMP }
  { expr | MINVALUE } AND { expr | MAXVALUE }
| AS OF { SCN | TIMESTAMP } expr
}
```

for_update_clause

```
FOR UPDATE
[ OF [ [ schema. ] { table | view } . ] column
    [, [ [ schema. ] { table | view } . ] column
    ]...
]
[ { NOWAIT | WAIT integer
  | SKIP LOCKED
  }
]
```

full_database_recovery

```
[ STANDBY ] DATABASE
[ { UNTIL { CANCEL
        | TIME date
        | CHANGE integer
```

```

        | CONSISTENT
      }
    | USING BACKUP CONTROLFILE
  }...
]

```

fully_qualified_file_name

```

+diskgroup_name/db_name/file_type/
  file_type_tag.filenumber.incarnation_number

```

function_association

```

{ FUNCTIONS
  [ schema. ]function [, [ schema. ]function ]...
| PACKAGES
  [ schema. ]package [, [ schema. ]package ]...
| TYPES
  [ schema. ]type [, [ schema. ]type ]...
| INDEXES
  [ schema. ]index [, [ schema. ]index ]...
| INDEXTYPES
  [ schema. ]indextype [, [ schema. ]indextype ]...
}
{ using_statistics_type
| { default_cost_clause [, default_selectivity_clause ]
  | default_selectivity_clause [, default_cost_clause ]
  }
}

```

general_recovery

```

RECOVER
[ AUTOMATIC ]
[ FROM 'location' ]
{ { full_database_recovery
  | partial_database_recovery
  | LOGFILE 'filename'
  }
| { TEST
  | ALLOW integer CORRUPTION
  | parallel_clause
  }...
}
| CONTINUE [ DEFAULT ]
| CANCEL
}

```

global_partitioned_index

```

GLOBAL PARTITION BY
{ RANGE (column_list)
  (index_partitioning_clause)
| HASH (column_list)
  { individual_hash_partitions
  | hash_partitions_by_quantity
  }
}

```

grant_object_privileges

```

{ object_privilege | ALL [ PRIVILEGES ] }
[ (column [, column ]...) ]
[ , { object_privilege | ALL [ PRIVILEGES ] }
  [ (column [, column ]...) ]
  ]...
on_object_clause

```

```
TO grantee_clause
  [ WITH HIERARCHY OPTION ]
  [ WITH GRANT OPTION ]
```

grant_system_privileges

```
{ system_privilege
| role
| ALL PRIVILEGES
}

[, { system_privilege
  | role
  | ALL PRIVILEGES
  }
]...

TO grantee_clause
  [ WITH ADMIN OPTION ]
```

grantee_clause

```
{ user [ IDENTIFIED BY password ]
| role
| PUBLIC
}

[, { user [ IDENTIFIED BY password ]
  | role
  | PUBLIC
  }
]...
```

group_by_clause

```
GROUP BY
  { expr
  | rollup_cube_clause
  | grouping_sets_clause
  }

  [, { expr
    | rollup_cube_clause
    | grouping_sets_clause
    }
  ]...

  [ HAVING condition ]
```

grouping_expression_list

```
expression_list [, expression_list ]...
```

grouping_sets_clause

```
GROUPING SETS
({ rollup_cube_clause | grouping_expression_list })
```

hash_partitions

```
PARTITION BY HASH (column [, column ] ...)
{ individual_hash_partitions
| hash_partitions_by_quantity
}
```

hash_partitions_by_quantity

```
PARTITIONS hash_partition_quantity
[ STORE IN (tablespace [, tablespace ]...) ]
[ key_compression | table_compression ]
[ OVERFLOW STORE IN (tablespace [, tablespace ]...) ]
```


hash_subparts_by_quantity

```
SUBPARTITIONS integer [STORE IN ( tablespace [, tablespace]... )]
```

hierarchical_query_clause

```
{ CONNECT BY [ NOCYCLE ] condition [AND condition]... [ START WITH condition ]
| START WITH condition CONNECT BY [ NOCYCLE ] condition [AND condition]...
}
```

hierarchy_clause

```
HIERARCHY hierarchy
(child_level { CHILDOF parent_level }...
 [ dimension_join_clause ]
)
```

implementation_clause

```
{ ANCILLARY TO primary_operator
  ( parameter_type [, parameter_type ]... )
  [, primary_operator
    ( parameter_type [, parameter_type ]... )
  ]...
| context_clause
}
```

incomplete_file_name

```
+diskgroup_name [ (template_name) ]
```

index_attributes

```
[ { physical_attributes_clause
  | logging_clause
  | ONLINE
  | TABLESPACE { tablespace | DEFAULT }
  | key_compression
  | { SORT | NOSORT }
  | REVERSE
  | VISIBLE | INVISIBLE
  | parallel_clause
  }...
]
```

index_expr

```
{ column | column_expression }
```

index_org_overflow_clause

```
[ INCLUDING column_name ]
OVERFLOW [ segment_attributes_clause ]
```

index_org_table_clause

```
[ { mapping_table_clause
  | PCTTHRESHOLD integer
  | key_compression
  }...
]
[ index_org_overflow_clause ]
```

index_partition_description

```
PARTITION
[ partition
  [ { segment_attributes_clause
    | key_compression
  }
]
```

```
    }...  
    | ( PARAMETERS 'ODCI_parameters' )  
    ] [ UNUSABLE ]  
]
```

index_partitioning_clause

```
PARTITION [ partition ]  
    VALUES LESS THAN (literal[, literal]... )  
    [ segment_attributes_clause ]
```

index_properties

```
[ { { global_partitioned_index  
    | local_partitioned_index  
    }  
    | index_attributes  
    }...  
| INDEXTYPE IS { domain_index_clause  
                | XMLTable_index_clause  
                | XMLIndex_clause  
                }  
]
```

index_subpartition_clause

```
{ STORE IN (tablespace[, tablespace ]...)  
| (SUBPARTITION  
    [ subpartition ][ TABLESPACE tablespace ] [ key_compression ] [ UNUSABLE ]  
    [, SUBPARTITION  
        [ subpartition ][ TABLESPACE tablespace ] [ key_compression ] [ UNUSABLE ]  
    ]...  
    )  
}
```

individual_hash_partitions

```
( PARTITION  
    [partition] [partitioning_storage_clause ]]  
    [, [partition] [partitioning_storage_clause ]]]...  
)
```

individual_hash_subparts

```
SUBPARTITION [subpartition] [partitioning_storage_clause]
```

inline_constraint

```
[ CONSTRAINT constraint_name ]  
{ [ NOT ] NULL  
| UNIQUE  
| PRIMARY KEY  
| references_clause  
| CHECK (condition)  
}  
[ constraint_state ]
```

inline_ref_constraint

```
{ SCOPE IS [ schema. ] scope_table  
| WITH ROWID  
| [ CONSTRAINT constraint_name ]  
    references_clause  
    [ constraint_state ]  
}
```

inner_cross_join_clause

```
{ [ INNER ] JOIN table_reference
  { ON condition
    | USING (column [, column ]...)
  }
| { CROSS
  | NATURAL [ INNER ]
  }
  JOIN table_reference
}
```

insert_into_clause

```
INTO dml_table_expression_clause [ t_alias ]
[ (column [, column ]...) ]
```

instance_clauses

```
{ ENABLE | DISABLE } INSTANCE 'instance_name'
```

integer

```
[ + | - ] digit [ digit ]...
```

interval_day_to_second

```
INTERVAL '{ integer | integer time_expr | time_expr }'
{ { DAY | HOUR | MINUTE } [ (leading_precision) ]
| SECOND [ (leading_precision [, fractional_seconds_precision) ] ]
}
[ TO { DAY | HOUR | MINUTE | SECOND [ (fractional_seconds_precision) ] } ]
```

interval_year_to_month

```
INTERVAL 'integer [- integer ]'
{ YEAR | MONTH } [ (precision) ] [ TO { YEAR | MONTH } ]
```

into_clause

```
INTO [ schema. ] table
```

invoker_rights_clause

```
AUTHID { CURRENT_USER | DEFINER }
```

join_clause

```
table_reference
{ inner_cross_join_clause | outer_join_clause }...
```

key_compression

```
{ COMPRESS [ integer ]
| NOCOMPRESS
}
```

level_clause

```
LEVEL level IS
{ level_table.level_column
| (level_table.level_column
  [, level_table.level_column ]...
)
}
```

list_partition_desc

```
list_values_clause
```

```
table_partition_description
[ ( "(" ( "range_subpartition_desc"/"," )
    | ("list_subpartition_desc"/"," )
    | ("individual_hash_subparts"/"," )
    )
  ")"
) | "hash_subparts_by_quantity"
]
```

list_partitions

```
PARTITION BY LIST (column)
(PARTITION [ partition ]
  list_values_clause table_partition_description
[, PARTITION [ partition ]
  list_values_clause table_partition_description
]...
)
```

list_subpartition_desc

```
SUBPARTITION [subpartition]
  list_values_clause
  [partitioning_storage_clause]
```

list_values_clause

```
VALUES ({ literal | NULL }
        [, { literal | NULL } ]...
        | DEFAULT
)
```

LOB_compression_clause

```
{ COMPRESS [HIGH | MEDIUM | LOW ]
| NOCOMPRESS
}
```

LOB_deduplicate_clause

```
{ DEDUPLICATE
| KEEP_DUPLICATES
}
```

LOB_parameters

```
{ { ENABLE | DISABLE } STORAGE IN ROW
  | CHUNK integer
  | PCTVERSION integer
  | FREEPOOLS integer
  | LOB_retention_clause
  | LOB_deduplicate_clause
  | LOB_compression_clause
  | { ENCRYPT encryption_spec | DECRYPT }
  | { CACHE | NOCACHE | CACHE READS } [ logging_clause ]
}...
```

LOB_partition_storage

```
PARTITION partition
{ LOB_storage_clause | varray_col_properties }...
[ (SUBPARTITION subpartition
  { LOB_partitioning_storage | varray_col_properties }...
)
]
```

LOB_partitioning_storage

```
LOB (LOB_item) STORE AS [BASICFILE | SECUREFILE]
  [ LOB_segname [ (TABLESPACE tablespace) ]
    | (TABLESPACE tablespace)
  ]
```

LOB_retention_storage

```
RETENTION [ MAX | MIN integer | AUTO | NONE ]
```

LOB_storage_clause

```
LOB
{ (LOB_item [, LOB_item ]...)
  STORE AS { {SECUREFILE | BASICFILE}
             | (LOB_storage_parameters)
           }...
| (LOB_item)
  STORE AS { {SECUREFILE | BASICFILE}
             | LOB_segname
             | (LOB_storage_parameters)
           }...
}
```

LOB_storage_parameters

```
{ { TABLESPACE tablespace
  | LOB_parameters [storage_clause]
}...
| storage_clause
}
```

local_domain_index_clause

```
LOCAL
[ ( PARTITION partition [ PARAMETERS ( 'ODCI_parameters' ) ]
  [, PARTITION partition [ PARAMETERS ( 'ODCI_parameters' ) ] ]...
)
]
```

local_partitioned_index

```
LOCAL
[ on_range_partitioned_table
| on_list_partitioned_table
| on_hash_partitioned_table
| on_comp_partitioned_table
]
```

local_XMLIndex_clause

```
LOCAL
[ ( PARTITION partition [ XMLIndex_parameters_clause ]
  [, PARTITION partition [ XMLIndex_parameters_clause ] ]...
)
]
```

logfile_clause

```
LOGFILE
[ GROUP integer ] file_specification
[, [ GROUP integer ] file_specification ]...
```

logfile_clauses

```
{ { ARCHIVELOG [ MANUAL ]
  | NOARCHIVELOG
```

```
    }
  | [ NO ] FORCE LOGGING
  | RENAME FILE 'filename' [, 'filename' ]...
    TO 'filename'
  | CLEAR [ UNARCHIVED ]
    LOGFILE logfile_descriptor [, logfile_descriptor ]...
    [ UNRECOVERABLE DATAFILE ]
  | add_logfile_clauses
  | drop_logfile_clauses
  | switch_logfile_clause
  | supplemental_db_logging
}
```

logfile_descriptor

```
{ GROUP integer
| ('filename' [, 'filename' ]...)
| 'filename'
}
```

logging_clause

```
{ LOGGING | NOLOGGING | FILESYSTEM_LIKE_LOGGING }
```

main_model

```
[ MAIN main_model_name ]
model_column_clauses
[ cell_reference_options ]
model_rules_clause
```

managed_standby_recovery

```
RECOVER
{ MANAGED STANDBY DATABASE
  [ { USING CURRENT LOGFILE
    | DISCONNECT [FROM SESSION]
    | NODELAY
    | UNTIL CHANGE integer
    | UNTIL CONSISTENT
    | parallel_clause
    }...
  | FINISH
  | CANCEL
  ]
| TO LOGICAL STANDBY { db_name | KEEP IDENTITY }
}
```

mapping_table_clauses

```
{ MAPPING TABLE | NOMAPPING }
```

materialized_view_props

```
[ column_properties ]
[ table_partitioning_clauses ]
[ CACHE | NOCACHE ]
[ parallel_clause ]
[ build_clause ]
```

maximize_standby_db_clause

```
SET STANDBY DATABASE TO MAXIMIZE
{ PROTECTION | AVAILABILITY | PERFORMANCE }
```

maxsize_clause

```
MAXSIZE { UNLIMITED | size_clause }
```

merge_insert_clause

```

WHEN NOT MATCHED THEN
INSERT [ (column [, column ]...) ]
VALUES ({ expr | DEFAULT }
        [, { expr | DEFAULT } ]...
        )
[ where_clause ]

```

merge_table_partitions

```

MERGE PARTITIONS partition_extended_name, partition_extended_name
[ INTO partition_spec ]
[ dependent_tables_clause ]
[ update_index_clauses ]
[ parallel_clause ]

```

merge_table_subpartitions

```

MERGE SUBPARTITIONS partition_extended_name, partition_extended_name
[ INTO { range_subpartition_desc
        | list_subpartition_desc
        }
        ]
[ dependent_tables_clause ]
[ update_index_clauses ]
[ parallel_clause ]

```

merge_update_clause

```

WHEN MATCHED THEN
UPDATE SET column = { expr | DEFAULT }
        [, column = { expr | DEFAULT } ]...
[ where_clause ]
[ DELETE where_clause ]

```

mining_attribute_clause

```

USING
{ *
| { [ schema . ] table . *
  | expr [ AS alias ]
  }
  [, { [ schema . ] table . *
    | expr [ AS alias ]
    }
  ]...
}

```

model_clause

```

MODEL
[ cell_reference_options ]
[ return_rows_clause ]
[ reference_model ]...
main_model

```

model_column

```

expr [ [ AS ] c_alias ]

```

model_column_clauses

```

[ PARTITION BY expr [ c_alias ] [, expr [c_alias] ]...
DIMENSION BY (expr [c_alias] [, expr [c_alias] ]...)
MEASURES (expr [c_alias] [, expr [c_alias] ]...)

```

model_iterate_clause

```
ITERATE ( number ) [ UNTIL ( condition ) ]
```

model_rules_clause

```
[ RULES
  [ { UPDATE | UPSERT [ ALL ] } ]
  [ { AUTOMATIC | SEQUENTIAL } ORDER ]
  [ model_iterate_clause ]
]
( [ { UPDATE | UPSERT [ ALL ] } ]
cell_assignment [ order_by_clause ] = expr
[, [ { UPDATE | UPSERT [ ALL ] } ]
  cell_assignment [ order_by_clause ] = expr
]...
)
```

modify_col_properties

```
column [ datatype ]
  [ DEFAULT expr ]
  [ { ENCRYPT encryption_spec | DECRYPT }
  [ inline_constraint ...
  [ LOB_storage_clause ]
  [ alter_XMLSchema_clause ]
```

modify_col_substitutable

```
COLUMN column
[ NOT ] SUBSTITUTABLE AT ALL LEVELS
[ FORCE ]
```

modify_collection_retrieval

```
MODIFY NESTED TABLE collection_item
RETURN AS { LOCATOR | VALUE }
```

modify_column_clauses

```
MODIFY { (modify_col_properties [, modify_col_properties] ...)
        | modify_col_substitutable
        }
```

modify_diskgroup_file

```
MODIFY FILE 'filename' ATTRIBUTE ( disk_region_clause )
[, 'filename' ATTRIBUTE ( disk_region_clause ) ]...
```

modify_hash_partition

```
MODIFY partition_extended_name
  { partition_attributes
  | alter_mapping_table_clause
  | [ REBUILD ] UNUSABLE LOCAL INDEXES
  }
```

modify_index_default_attrs

```
MODIFY DEFAULT ATTRIBUTES
  [ FOR PARTITION partition ]
  { physical_attributes_clause
  | TABLESPACE { tablespace | DEFAULT }
  | logging_clause
  }...
```

modify_index_partition

```
MODIFY PARTITION partition
```



```

{ { deallocate_unused_clause
  | allocate_extent_clause
  | physical_attributes_clause
  | logging_clause
  | key_compression
  } ...
| PARAMETERS ('ODCI_parameters')
| COALESCE
| UPDATE BLOCK REFERENCES
| UNUSABLE
}

```

modify_index_subpartition

```

MODIFY SUBPARTITION subpartition
{ UNUSABLE
| allocate_extent_clause
| deallocate_unused_clause
}

```

modify_list_partition

```

MODIFY partition_extended_name
{ partition_attributes
| { ADD | DROP } VALUES (literal[ , literal ]...)
| { add_range_subpartition
  | add_list_subpartition
  | add_hash_subpartition
  }
| COALESCE SUBPARTITION [ update_index_clauses ][ parallel_clause ]
| [ REBUILD ] UNUSABLE LOCAL INDEXES
}

```

modify_LOB_parameters

```

{ storage_clause
| PCTVERSION integer
| FREEPOOLS integer
| REBUILD FREEPOOLS
| LOB_retention_clause
| LOB_deduplicate_clause
| LOB_compression_clause
| { ENCRYPT encryption_spec | DECRYPT }
| { CACHE
  | { NOCACHE | CACHE READS } [ logging_clause ]
  }
| allocate_extent_clause
| shrink_clause
| deallocate_unused_clause
} ...

```

modify_LOB_storage_clause

```

MODIFY LOB (LOB_item)
(modify_LOB_parameters)

```

modify_mv_column_clause

```

MODIFY ( column [ ENCRYPT encryption_spec
| DECRYPT ]
)

```

modify_range_partition

```

MODIFY partition_extended_name
{ partition_attributes
| { add_range_subpartition

```

```
| add_hash_subpartition
| add_list_subpartition
}
| COALESCE SUBPARTITION
  [ update_index_clauses ]
  [ parallel_clause ]
| alter_mapping_table_clause
| [ REBUILD ] UNUSABLE LOCAL INDEXES
}
```

modify_table_default_attrs

```
MODIFY DEFAULT ATTRIBUTES
  [ FOR partition_extended_name ]
  [ deferred_segment_creation ]
  [ segment_attributes_clause ]
  [ table_compression ]
  [ PCTTHRESHOLD integer ]
  [ key_compression ]
  [ alter_overflow_clause ]
  [ { LOB (LOB_item) | VARRAY varray } (LOB_parameters) ]...
```

Note: You can specify `deferred_segment_creation` in this clause starting with Oracle Database 11g Release 2 (11.2.0.2).

modify_table_partition

```
{ modify_range_partition
| modify_hash_partition
| modify_list_partition
}
```

modify_table_subpartition

```
MODIFY subpartition_extended_name
{ allocate_extent_clause
| deallocate_unused_clause
| shrink_clause
| { { LOB LOB_item | VARRAY varray } (modify_LOB_parameters) }...
| [ REBUILD ] UNUSABLE LOCAL INDEXES
| { ADD | DROP } VALUES ( literal [, literal]... )
}
```

modify_volume_clause

```
MODIFY VOLUME asm_volume
  [ ATTRIBUTE disk_region_clause ]
  [ MOUNTPATH 'mountpath_name' ]
  [ USAGE 'usage_name' ]
```

move_mv_log_clause

```
MOVE segment_attributes_clause [parallel_clause]
```

move_table_clause

```
MOVE [ ONLINE ]
  [ segment_attributes_clause ]
  [ table_compression ]
  [ index_org_table_clause ]
  [ { LOB_storage_clause | varray_col_properties }... ]
  [ parallel_clause ]
```

move_table_partition

```

MOVE partition_extended_name
  [ MAPPING TABLE ]
  [ table_partition_description ]
  [ update_index_clauses ]
  [ parallel_clause ]

```

move_table_subpartition

```

MOVE SUBPARTITION
  { range_subpartition_desc
  | list_subpartition_desc
  | hash_subpartition_desc
  } [ update_index_clauses ] [ parallel_clause ]

```

multi_column_for_loop

```

FOR (dimension_column
     [, dimension_column ]...)
IN ( ( (literal [, literal ]...)
      [ (literal [, literal ]...) ]...
      | subquery
      )
    )

```

multi_table_insert

```

{ ALL
  { insert_into_clause [ values_clause ] [error_logging_clause] }...
  | conditional_insert_clause
} subquery

```

multiset_except

```

nested_table1
MULTISET EXCEPT [ ALL | DISTINCT ]
nested_table2

```

multiset_intersect

```

nested_table1
MULTISET INTERSECT [ ALL | DISTINCT ]
nested_table2

```

multiset_union

```

nested_table1
MULTISET UNION [ ALL | DISTINCT ]
nested_table2

```

mv_log_augmentation

```

ADD { { OBJECT ID
      | PRIMARY KEY
      | ROWID
      | SEQUENCE
      } [ (column [, column ]...) ]
    | (column [, column ]... )
    } [, { { OBJECT ID
          | PRIMARY KEY
          | ROWID
          | SEQUENCE
          }
        [ (column [, column ]...) ]
        | (column [, column ]...)
        }

```

```

]...
[ new_values_clause ]

```

mv_log_purge_clause

```

PURGE { IMMEDIATE [ SYNCHRONOUS | ASYNCHRONOUS ] }
      | START WITH datetime_expr
        [ NEXT datetime_expr
          | REPEAT INTERVAL interval_expr
        ]
      | [ START WITH datetime_expr ] { NEXT datetime_expr
                                       | REPEAT INTERVAL interval_expr
                                     }
    }

```

nested_table_col_properties

```

NESTED TABLE
{ nested_item | COLUMN_VALUE }
[ substitutable_column_clause ]
[ LOCAL | GLOBAL ]
STORE AS storage_table
[ ( { (object_properties)
    | [ physical_properties ]
    | [ column_properties ]
  }...
)
]
[ RETURN [ AS ] { LOCATOR | VALUE } ]

```

nested_table_partition_spec

```

PARTITION partition [segment_attributes_clause]

```

new_values_clause

```

{ INCLUDING | EXCLUDING } NEW VALUES

```

number

```

[ + | - ]
{ digit [ digit ]... [ . ] [ digit [ digit ]... ]
| . digit [ digit ]...
}
[ [ e | E ] [ + | - ] digit [ digit ]... ] [ f | F | d | D ]

```

numeric_file_name

```

+diskgroup_name.filenumber.incarnation_number

```

object_properties

```

{ { column | attribute }
  [ DEFAULT expr ]
  [ { inline_constraint }... | inline_ref_constraint ]
| { out_of_line_constraint
  | out_of_line_ref_constraint
  | supplemental_logging_props
  }
}

```

object_table

```

OF
[ schema. ] object_type
[ object_table_substitution ]
[ (object_properties) ]
[ ON COMMIT { DELETE | PRESERVE } ROWS ]

```

```

[ OID_clause ]
[ OID_index_clause ]
[ physical_properties ]
[ table_properties ]
;

```

object_table_substitution

```
[ NOT ] SUBSTITUTABLE AT ALL LEVELS
```

object_type_col_properties

```
COLUMN column substitutable_column_clause
```

object_view_clause

```

OF [ schema. ] type_name
{ WITH OBJECT IDENTIFIER
  { DEFAULT | ( attribute [, attribute ]... ) }
| UNDER [ schema. ] superview
}
[ ( { out_of_line_constraint
  | attribute { inline_constraint }...
  } [, { out_of_line_constraint
  | attribute { inline_constraint }...
  }
  ]...
)
]

```

OID_clause

```

OBJECT IDENTIFIER IS
{ SYSTEM GENERATED | PRIMARY KEY }

```

OID_index_clause

```

OIDINDEX [ index ]
({ physical_attributes_clause
| TABLESPACE tablespace
}...
)

```

on_comp_partitioned_table

```

[ STORE IN ( tablespace [, tablespace ]... ) ]
( PARTITION
  [ partition ]
  [ { segment_attributes_clause
  | key_compression
  }...
  ] [ UNUSABLE ] [ index_subpartition_clause ]
  [, PARTITION
  [ partition ]
  [ { segment_attributes_clause
  | key_compression
  }...
  ] [ UNUSABLE ] [ index_subpartition_clause ]
  ]...
)

```

on_hash_partitioned_table

```

{ STORE IN (tablespace[, tablespace ]...)
| (PARTITION [ partition ] [ TABLESPACE tablespace ] [key_compression]
  [, PARTITION [ partition ] [ TABLESPACE tablespace ] [key_compression]] ...
)
}

```

on_list_partitioned_table

```
( PARTITION
  [ partition ]
  [ { segment_attributes_clause
    | key_compression
    }...
  ] [ UNUSABLE ]
  [, PARTITION
    [ partition ]
    [ { segment_attributes_clause
      | key_compression
      }...
    ] [ UNUSABLE ]
  ]...
)
```

on_object_clause

```
ON { [ schema. ] object
  | DIRECTORY directory_name
  | EDITION edition_name
  | MINING MODEL [schema.] mining_model_name
  | JAVA { SOURCE | RESOURCE } [ schema. ] object
}
```

on_range_partitioned_table

```
( PARTITION
  [ partition ]
  [ { segment_attributes_clause
    | key_compression
    }...
  ] [ UNUSABLE ]
  [, PARTITION
    [ partition ]
    [ { segment_attributes_clause
      | key_compression
      }...
    ] [ UNUSABLE ]
  ]...
)
```

order_by_clause

```
ORDER [ SIBLINGS ] BY
{ expr | position | c_alias }
[ ASC | DESC ]
[ NULLS FIRST | NULLS LAST ]
[, { expr | position | c_alias }
  [ ASC | DESC ]
  [ NULLS FIRST | NULLS LAST ]
]...
```

out_of_line_constraint

```
[ CONSTRAINT constraint_name ]
{ UNIQUE (column [, column ]...)
| PRIMARY KEY (column [, column ]...)
| FOREIGN KEY (column [, column ]...) references_clause
| CHECK (condition)
} [ constraint_state ]
```

out_of_line_part_storage

```
PARTITION partition
  { nested_table_col_properties | LOB_storage_clause | varray_col_properties }
  [ nested_table_col_properties | LOB_storage_clause | varray_col_properties ]
```

```

]...
[ (SUBPARTITION subpartition
  { nested_table_col_properties | LOB_storage_clause | varray_col_properties }
  [ nested_table_col_properties | LOB_storage_clause | varray_col_properties
  ]...
)
]

```

out_of_line_ref_constraint

```

{ SCOPE FOR ({ ref_col | ref_attr })
  IS [ schema. ] scope_table
| REF ({ ref_col | ref_attr }) WITH ROWID
| [ CONSTRAINT constraint_name ] FOREIGN KEY
  ( { ref_col | ref_attr } ) references_clause
  [ constraint_state ]
}

```

outer_join_clause

```

[ query_partition_clause ]
{ outer_join_type JOIN
| NATURAL [ outer_join_type ] JOIN
}
table_reference [ query_partition_clause ]
[ ON condition
| USING ( column [, column ]...)
]

```

outer_join_type

```

{ FULL | LEFT | RIGHT } [ OUTER ]

```

parallel_clause

```

{ NOPARALLEL | PARALLEL [ integer ] }

```

partial_database_recovery

```

{ TABLESPACE tablespace [, tablespace ]...
| DATAFILE { 'filename' | filenumber }
  [, 'filename' | filenumber ]...
}

```

partition_attributes

```

[ { physical_attributes_clause
  | logging_clause
  | allocate_extent_clause
  | deallocate_unused_clause
  | shrink_clause
  }...
]
[ OVERFLOW
  { physical_attributes_clause
  | logging_clause
  | allocate_extent_clause
  | deallocate_unused_clause
  }...
]
[ table_compression ]
[ { { LOB LOB_item | VARRAY varray } (modify_LOB_parameters) }... ]

```

partition_extended_name

```

PARTITION partition
|

```

```
PARTITION FOR ( partition_key_value [, partition_key_value]... )
```

partition_extension_clause

```
{ PARTITION (partition)
| PARTITION FOR (partition_key_value [, partition_key_value]...)
| SUBPARTITION (subpartition)
| SUBPARTITION FOR (subpartition_key_value [, subpartition_key_value]...)
}
```

partition_spec

```
PARTITION [ partition ] [ table_partition_description ]
```

partitioning_storage_clause

```
[ { TABLESPACE tablespace
| OVERFLOW [TABLESPACE tablespace]
| table_compression
| key_compression
| LOB_partitioning_storage
| VARRAY varray_item STORE AS [SECUREFILE | BASICFILE] LOB LOB_segname
}...
]
```

password_parameters

```
{ { FAILED_LOGIN_ATTEMPTS
| PASSWORD_LIFE_TIME
| PASSWORD_REUSE_TIME
| PASSWORD_REUSE_MAX
| PASSWORD_LOCK_TIME
| PASSWORD_GRACE_TIME
}
{ expr | UNLIMITED | DEFAULT }
| PASSWORD_VERIFY_FUNCTION
{ function | NULL | DEFAULT }
}
```

permanent_tablespace_clause

```
TABLESPACE tablespace
[ DATAFILE file_specification [, file_specification]... ]
{ MINIMUM EXTENT size_clause
| BLOCKSIZE integer [ K ]
| logging_clause
| FORCE LOGGING
| ENCRYPTION encryption_spec
| DEFAULT [ table_compression ]
storage_clause
| { ONLINE | OFFLINE }
| extent_management_clause
| segment_management_clause
| flashback_mode_clause
}...
;
```

physical_attributes_clause

```
[ { PCTFREE integer
| PCTUSED integer
| INITRANS integer
| storage_clause
}...
]
```


physical_properties

```

{ [deferred_segment_creation] segment_attributes_clause [ table_compression ]
| [deferred_segment_creation] ORGANIZATION
  { HEAP [ segment_attributes_clause ] [ table_compression ]
  | INDEX [ segment_attributes_clause ] index_org_table_clause
  | EXTERNAL external_table_clause
  }
| CLUSTER cluster (column [, column ]...)
}

```

pivot_clause

```

table_reference PIVOT [ XML ]
( aggregate_function ( expr ) [[AS] alias ]
  [, aggregate_function ( expr ) [[AS] alias ] ]...
  pivot_for_clause
  pivot_in_clause
)

```

pivot_for_clause

```

FOR { column
    | ( column [, column]... )
}

```

pivot_in_clause

```

IN ( ( { { expr
    | ( expr [, expr]... )
    } [ [ AS] alias]
    }...
    | subquery
    | ANY [, ANY]...
    }
)

```

proxy_clause

```

{ GRANT CONNECT THROUGH { ENTERPRISE USERS | db_user_proxy db_user_proxy_clauses }
| REVOKE CONNECT THROUGH { ENTERPRISE USERS | db_user_proxy }}

```

qualified_disk_clause

```

search_string
[ NAME disk_name ]
[ SIZE size_clause ]
[ FORCE | NOFORCE ]

```

qualified_template_clause

```

ATTRIBUTE
( redundancy_clause
  striping_clause
  disk_region_clause
)

```

query_block

```

SELECT
[ hint ]
[ { { DISTINCT | UNIQUE } | ALL } ]
select_list
FROM { table_reference | join_clause | ( join_clause ) }
    [ , { table_reference | join_clause | (join_clause) } ] ...
[ where_clause ]
[ hierarchical_query_clause ]

```

```
[ group_by_clause ]
[ model_clause ]
```

query_partition_clause

```
PARTITION BY
  { value_expr[, value_expr ]...
  | ( value_expr[, value_expr ]... )
}
```

query_table_expression

```
{ query_name
| [ schema. ]
  { table [ partition_extension_clause
          | @ dblink
        ]
  | { view | materialized view } [ @ dblink ]
  } ["sample_clause"]
| (subquery [ subquery_restriction_clause ])
| table_collection_expression
}
```

quiesce_clauses

```
QUIESCE RESTRICTED | UNQUIESCE
```

range_partition_desc

```
range_values_clause
table_partition_description
[ ( { range_subpartition_desc [, range_subpartition_desc] ...
    | list_subpartition_desc [, list_subpartition_desc] ...
    | individual_hash_subparts [, individual_hash_subparts] ...
    }
) | hash_subparts_by_quantity ]
```

range_partitions

```
PARTITION BY RANGE (column[, column ]...)
  [ INTERVAL expr [ STORE IN ( tablespace [, tablespace]...) ]]
( PARTITION [ partition ]
  range_values_clause table_partition_description
  [, PARTITION [ partition ]
    range_values_clause table_partition_description
  ]...
)
```

range_subpartition_desc

```
SUBPARTITION [subpartition] range_values_clause
[partitioning_storage_clause]
```

range_values_clause

```
VALUES LESS THAN
  ({ literal | MAXVALUE }
  [, { literal | MAXVALUE } ]...
)
```

rebalance_diskgroup_clause

```
REBALANCE [POWER integer] [WAIT | NOWAIT]
```

rebuild_clause

```
REBUILD
  [ { PARTITION partition
```

```

    | SUBPARTITION subpartition
  }
  | { REVERSE | NOREVERSE }
]
[ parallel_clause
| TABLESPACE tablespace
| PARAMETERS ( 'ODCI_parameters' )
| XMLIndex_parameters_clause
| ONLINE
| physical_attributes_clause
| key_compression
| logging_clause
]...

```

records_per_block_clause

```
{ MINIMIZE | NOMINIMIZE } RECORDS_PER_BLOCK
```

recovery_clauses

```

{ general_recovery
| managed_standby_recovery
| BEGIN BACKUP
| END BACKUP
}

```

redo_log_file_spec

```

[ 'filename' | ASM_filename'
| ('filename' | ASM_filename'
  [, 'filename' | ASM_filename' ]...)
]
[ SIZE size_clause ]
[ BLOCKSIZE size_clause
[ REUSE ]

```

redundancy_clause

```
[ MIRROR | HIGH | UNPROTECTED ]
```

reference_model

```

REFERENCE reference_spreadsheet_name
ON (subquery)
spreadsheet_column_clauses
  [ cell_reference_options ]

```

reference_partition_desc

```
PARTITION [partition] [table_partition_description] )
```

reference_partitioning

```

PARTITION BY REFERENCE ( constraint )
  [ (reference_partition_desc...) ]

```

references_clause

```

REFERENCES [ schema. ] { object_table | view }
  [ (column [, column ]...) ]
  [ON DELETE { CASCADE | SET NULL } ]
  [ constraint_state ]

```

register_logfile_clause

```

REGISTER [ OR REPLACE ]
  [ PHYSICAL | LOGICAL ]
LOGFILE [ file_specification [, file_specification ]...

```

```
[ FOR logminer_session_name ]
```

relational_properties

```
{ column_definition
| virtual_column_definition
| { out_of_line_constraint
  | out_of_line_ref_constraint
  | supplemental_logging_props
}
}
[, { column_definition
  | virtual_column_definition
  | { out_of_line_constraint
    | out_of_line_ref_constraint
    | supplemental_logging_props
  }
}
]...
```

relational_table

```
[ (relational_properties) ]
[ ON COMMIT { DELETE | PRESERVE } ROWS ]
[ physical_properties ]
[ table_properties ]
;
```

rename_column_clause

```
RENAME COLUMN old_name TO new_name
```

rename_index_partition

```
RENAME
{ PARTITION partition | SUBPARTITION subpartition }
TO new_name
```

rename_partition_subpart

```
RENAME { partition_extended_name
       | subpartition_extended_name
       } TO new_name
```

resize_disk_clauses

```
RESIZE
{ ALL [ SIZE size_clause ]
| [QUORUM | REGULAR] DISK
  disk_name [ SIZE size_clause ]
  [, disk_name [ SIZE size_clause ] ]...
| DISKS IN [QUORUM | REGULAR] FAILGROUP
  failgroup_name [ SIZE size_clause ]
  [, failgroup_name [ SIZE size_clause ] ]...
}
```

resource_parameters

```
{ { SESSIONS_PER_USER
  | CPU_PER_SESSION
  | CPU_PER_CALL
  | CONNECT_TIME
  | IDLE_TIME
  | LOGICAL_READS_PER_SESSION
  | LOGICAL_READS_PER_CALL
  | COMPOSITE_LIMIT
}
{ integer | UNLIMITED | DEFAULT }
```

```
| PRIVATE_SGA
  { size_clause | UNLIMITED | DEFAULT }
}
```

return_rows_clause

```
RETURN { UPDATED | ALL } ROWS
```

returning_clause

```
{ RETURN | RETURNING } expr [, expr ]...
INTO data_item [, data_item ]...
```

revoke_object_privileges

```
{ object_privilege | ALL [ PRIVILEGES ] }
  [, { object_privilege | ALL [ PRIVILEGES ] } ]...
on_object_clause
FROM grantee_clause
[ CASCADE CONSTRAINTS | FORCE ]
```

revoke_system_privileges

```
{ system_privilege
| role
| ALL PRIVILEGES
}
  [, { system_privilege
      | role
      | ALL PRIVILEGES
    }
  ]...
FROM grantee_clause
```

rolling_migration_clause

```
{ START ROLLING MIGRATION TO 'ASM_version'
| STOP ROLLING MIGRATION
}
```

rollup_cube_clause

```
{ ROLLUP | CUBE } (grouping_expression_list)
```

routine_clause

```
[ schema. ] [ type. | package. ]
{ function | procedure | method }
[ @dblink_name ]
( [ argument [, argument ]... ] )
```

row_movement_clause

```
{ ENABLE | DISABLE } ROW MOVEMENT
```

sample_clause

```
SAMPLE [ BLOCK ]
      (sample_percent)
      [ SEED (seed_value) ]
```

scoped_table_ref_constraint

```
{ SCOPE FOR
  ({ ref_column | ref_attribute })
  IS [ schema. ] { scope_table_name | c_alias }
}
  [, SCOPE FOR
```

```
    ({ ref_column | ref_attribute })
    IS [ schema. ] { scope_table_name | c_alias }
]...
```

search_clause

```
{ SEARCH
    { DEPTH FIRST BY c_alias [, c_alias]...
      [ ASC | DESC ]
      [ NULLS FIRST | NULLS LAST ]
    | BREADTH FIRST BY c_alias [, c_alias]...
      [ ASC | DESC ]
      [ NULLS FIRST | NULLS LAST ]
    }
    SET ordering_column
}
```

searched_case_expression

```
{ WHEN condition THEN return_expr }...
```

security_clause

```
GUARD { ALL | STANDBY | NONE }
```

security_clauses

```
{ { ENABLE | DISABLE } RESTRICTED SESSION
  | SET ENCRYPTION WALLET OPEN
    IDENTIFIED BY { "wallet_password" | "HSM_auth_string" }
  | SET ENCRYPTION WALLET CLOSE
    [ IDENTIFIED BY { "wallet_password" | "HSM_auth_string" } ]
  | set_encryption_key
}
```

segment_attributes_clause

```
{ physical_attributes_clause
  | TABLESPACE tablespace
  | logging_clause
}...
```

segment_management_clause

```
SEGMENT SPACE MANAGEMENT { AUTO | MANUAL }
```

select_list

```
{ [t_alias.] *
  | { query_name.*
    | [ schema. ]
      { table | view | materialized view } .*
    | expr [ [ AS ] c_alias ]
  }
  [, { query_name.*
    | [ schema. ]
      { table | view | materialized view } .*
    | expr [ [ AS ] c_alias ]
  }
  ]...
}
```

set_encryption_key

```
{ SET ENCRYPTION KEY
  {
```

```

    [ "certificate_id" ] IDENTIFIED BY "wallet_password"
    |
    IDENTIFIED BY "HSM_auth_string" [ MIGRATE USING "wallet_password" ]
  }
}

```

set_parameter_clause

```

parameter_name =
  parameter_value [, parameter_value ]...
  [ COMMENT = string ]
  [ DEFERRED ]
  [ { SCOPE = { MEMORY | SPFILE | BOTH }
    | SID = { 'sid' | '*' }
  }...
  ]

```

set_subpartition_template

```

SET SUBPARTITION TEMPLATE
  { ( range_subpartition_desc [, range_subpartition_desc]... )
    | ( list_subpartition_desc [, list_subpartition_desc]... )
    | hash_subpartition_quantity
  }

```

set_time_zone_clause

```

SET TIME_ZONE =
  '{ { + | - } hh : mi | time_zone_region }'

```

shrink_clause

```

SHRINK SPACE [ COMPACT ] [ CASCADE ]

```

shutdown_dispatcher_clause

```

SHUTDOWN [ IMMEDIATE ] dispatcher_name

```

simple_case_expression

```

expr
  { WHEN comparison_expr THEN return_expr }...

```

single_column_for_loop

```

FOR dimension_column
  { IN ( { literal [, literal ]...
        | subquery
      }
    )
  | [ LIKE pattern ] FROM literal TO literal
    { INCREMENT | DECREMENT } literal
  }

```

single_table_insert

```

insert_into_clause
{ values_clause [ returning_clause ]
  | subquery
} [ error_logging_clause ]

```

size_clause

```

integer [ K | M | G | T | P | E ]

```

split_index_partition

```
SPLIT PARTITION partition_name_old
  AT (literal [, literal ]...)
  [ INTO (index_partition_description,
          index_partition_description
        )
  ]
  [ parallel_clause ]
```

split_nested_table_part

```
NESTED TABLE column INTO
  ( PARTITION partition [segment_attributes_clause],
    PARTITION partition [segment_attributes_clause] [split_nested_table_part]
  ) [ split_nested_table_part ]
```

split_table_partition

```
SPLIT partition_extended_name
  { AT (literal [, literal]... )
    [ INTO ( range_partition_desc, range_partition_desc ) ]
  | VALUES (literal [, literal] ... )
    [ INTO (list_partition_desc, list_partition_desc ) ]
  } [ split_nested_table_part ]
  [ dependent_tables_clause ]
  [ update_index_clauses ]
  [ parallel_clause ]
```

split_table_subpartition

```
SPLIT subpartition_extended_name
  { AT ( literal [, literal]... )
    [ INTO (range_subpartition_desc, range_subpartition_desc) ]
  | VALUES ({ literal | NULL [, literal | NULL ]...})
    [ INTO (list_subpartition_desc, list_subpartition_desc) ]
  } [ dependent_tables_clause ]
  [ update_index_clauses ]
  [ parallel_clause ]
```

sql_format

```
[+ | -] days hours : minutes : seconds [. frac_secs ]
```

standby_database_clauses

```
{ activate_standby_db_clause
| maximize_standby_db_clause
| register_logfile_clause
| commit_switchover_clause
| start_standby_clause
| stop_standby_clause
| convert_database_clause
} [ parallel_clause ]
```

start_standby_clause

```
START LOGICAL STANDBY APPLY
[ IMMEDIATE ]
[ NODELAY ]
[ NEW PRIMARY dblink
| INITIAL [ scn_value ]
| { SKIP FAILED TRANSACTION | FINISH }
]
```


startup_clauses

```
{ MOUNT [ { STANDBY | CLONE } DATABASE ]
| OPEN
  { [ READ WRITE ]
    [ RESETLOGS | NORESETLOGS ]
    [ UPGRADE | DOWNGRADE ]
  | READ ONLY
  }
}
```

still_image_object_types

```
{ SI_StillImage
| SI_AverageColor
| SI_PositionalColor
| SI_ColorHistogram
| SI_Texture
| SI_FeatureList
| SI_Color
}
```

stop_standby_clause

```
{ STOP | ABORT } LOGICAL STANDBY APPLY
```

storage_clause

```
STORAGE
({ INITIAL size_clause
| NEXT size_clause
| MINEXTENTS integer
| MAXEXTENTS { integer | UNLIMITED }
| maxsize_clause
| PCTINCREASE integer
| FREELISTS integer
| FREELIST GROUPS integer
| OPTIMAL [ size_clause | NULL ]
| BUFFER_POOL { KEEP | RECYCLE | DEFAULT }
| FLASH_CACHE { KEEP | NONE | DEFAULT }
| ENCRYPT
} ...
)
```

storage_table_clause

```
WITH {SYSTEM | USER} MANAGED STORAGE TABLES
```

string

```
[ {N | n} ]
{ '[ c ]...'
| { Q | q } 'quote_delimiter c [ c ]... quote_delimiter'
}
```

striping_clause

```
[ FINE | COARSE ]
```

subpartition_by_hash

```
SUBPARTITION BY HASH (column [, column ]...)
  [ SUBPARTITIONS integer
    [ STORE IN (tablespace [, tablespace ]...) ]
  | subpartition_template
  ]
```

subpartition_by_list

```
SUBPARTITION BY LIST (column) [ subpartition_template ]
```

subpartition_by_range

```
SUBPARTITION BY RANGE ( column [, column]... ) [subpartition_template]
```

subpartition_extended_name

```
SUBPARTITION subpartition  
|  
SUBPARTITION FOR ( subpartition_key_value [, subpartition_key_value]... )
```

subpartition_template

```
SUBPARTITION TEMPLATE  
  ( { range_subpartition_desc [, range_subpartition_desc] ...  
    | list_subpartition_desc [, list_subpartition_desc] ...  
    | individual_hash_subparts [, individual_hash_subparts] ...  
    }  
  ) | hash_subpartition_quantity
```

subquery

```
{ query_block  
| subquery { UNION [ALL] | INTERSECT | MINUS } subquery  
  [ { UNION [ALL] | INTERSECT | MINUS } subquery ]...  
| ( subquery )  
} [ order_by_clause ]
```

subquery_factoring_clause

```
WITH  
  query_name ([c_alias [, c_alias]...]) AS (subquery) [search_clause] [cycle_clause]  
  [, query_name ([c_alias [, c_alias]...]) AS (subquery) [search_clause] [cycle_clause]]...
```

subquery_restriction_clause

```
WITH { READ ONLY  
      | CHECK OPTION  
      } [ CONSTRAINT constraint ]
```

substitutable_column_clause

```
{ [ ELEMENT ] IS OF [ TYPE ] ( [ONLY] type)  
| [ NOT ] SUBSTITUTABLE AT ALL LEVELS  
}
```

supplemental_db_logging

```
{ ADD | DROP } SUPPLEMENTAL LOG  
{ DATA  
| supplemental_id_key_clause  
| supplemental_plsql_clause  
}
```

supplemental_id_key_clause

```
DATA  
( { ALL | PRIMARY KEY | UNIQUE | FOREIGN KEY }  
  [, { ALL | PRIMARY KEY | UNIQUE | FOREIGN KEY } ]...  
)  
COLUMNS
```

supplemental_log_grp_clause

```
GROUP log_group  
(column [ NO LOG ]
```

```
[, column [ NO LOG ] ]...)
[ ALWAYS ]
```

supplemental_logging_props

```
SUPPLEMENTAL LOG { supplemental_log_grp_clause
                  | supplemental_id_key_clause
                  }
```

supplemental_plsql_clause

```
DATA FOR PROCEDURAL REPLICATION
```

supplemental_table_logging

```
{ ADD SUPPLEMENTAL LOG
  { supplemental_log_grp_clause | supplemental_id_key_clause }
  [, SUPPLEMENTAL LOG
    { supplemental_log_grp_clause | supplemental_id_key_clause }
  ]...
| DROP SUPPLEMENTAL LOG
  { supplemental_id_key_clause | GROUP log_group }
  [, SUPPLEMENTAL LOG
    { supplemental_id_key_clause | GROUP log_group }
  ]...
}
```

switch_logfile_clause

```
SWITCH ALL LOGFILES TO BLOCKSIZE integer
```

system_partitioning

```
PARTITION BY SYSTEM [ PARTITIONS integer
                    | reference_partition_desc
                    [, reference_partition_desc ...]
                    ]
```

table_collection_expression

```
TABLE (collection_expression) [ (+) ]
```

table_compression

```
{ COMPRESS [ BASIC
            | FOR { OLTP
                  | { QUERY | ARCHIVE } [ LOW | HIGH ]
                  }
            ]
| NOCOMPRESS
}
```

table_index_clause

```
[ schema. ] table [ t_alias ]
(index_expr [ ASC | DESC ]
[, index_expr [ ASC | DESC ] ]...)
[ index_properties ]
```

table_partition_description

```
[ deferred_segment_creation ]
[ segment_attributes_clause ]
[ table_compression | key_compression ]
[ OVERFLOW [ segment_attributes_clause ] ]
[ { LOB_storage_clause
  | varray_col_properties
  | nested_table_col_properties
```

```
}...  
]
```

Note: You can specify `deferred_segment_creation` in this clause starting with Oracle Database 11g Release 2 (11.2.0.2).

table_partitioning_clauses

```
{ range_partitions  
| hash_partitions  
| list_partitions  
| reference_partitioning  
| composite_range_partitions  
| composite_hash_partitions  
| composite_list_partitions  
| system_partitioning  
}
```

table_properties

```
[ column_properties ]  
[ table_partitioning_clauses ]  
[ CACHE | NOCACHE ]  
[ RESULT_CACHE ( MODE {DEFAULT | FORCE } ) ]  
[ parallel_clause ]  
[ ROWDEPENDENCIES | NOROWDEPENDENCIES ]  
[ enable_disable_clause ]...  
[ row_movement_clause ]  
[ flashback_archive_clause ]  
[ AS subquery ]
```

table_reference

```
{ ONLY (query_table_expression)  
| query_table_expression [ pivot_clause | unpivot_clause ]  
} [ flashback_query_clause ]  
[ t_alias ]
```

tablespace_clauses

```
{ EXTENT MANAGEMENT LOCAL  
| DATAFILE file_specification [, file_specification ]...  
| SYSAUX DATAFILE file_specification [, file_specification ]...  
| default_tablespace  
| default_temp_tablespace  
| undo_tablespace  
}
```

tablespace_group_clause

```
TABLESPACE GROUP { tablespace_group_name | '' }
```

tablespace_logging_clauses

```
{ logging_clause  
| [ NO ] FORCE LOGGING  
}
```

tablespace_retention_clause

```
RETENTION { GUARANTEE | NOGUARANTEE }
```

tablespace_state_clauses

```
{ { ONLINE
```

```

    | OFFLINE [ NORMAL | TEMPORARY | IMMEDIATE ]
  }
  | READ { ONLY | WRITE }
  | { PERMANENT | TEMPORARY }
}

```

temporary_tablespace_clause

```

TEMPORARY TABLESPACE tablespace
  [ TEMPFILE file_specification [, file_specification ]... ]
  [ tablespace_group_clause ]
  [ extent_management_clause ]

```

timeout_clause

```

DROP AFTER integer { M | H }

```

trace_file_clause

```

TRACE
  [ AS 'filename' [ REUSE ] ]
  [ RESETLOGS | NORESETLOGS ]

```

truncate_partition_subpart

```

TRUNCATE { partition_extended_name
          | subpartition_extended_name
        }
  [ { DROP [ ALL ] | REUSE } STORAGE ]
  [ update_index_clauses [ parallel_clause ] ]

```

Note: You can specify the ALL keyword in this clause starting with Oracle Database 11g Release 2 (11.2.0.2).

undo_tablespace

```

  [ BIGFILE | SMALLFILE ]
UNDO TABLESPACE tablespace
  [ TABLESPACE file_specification [, file_specification ]...]

```

undo_tablespace_clause

```

UNDO TABLESPACE tablespace
  [ DATAFILE file_specification [, file_specification ]... ]
  [ extent_management_clause ]
  [ tablespace_retention_clause ]

```

undrop_disk_clause

```

UNDROP DISKS

```

unpivot_clause

```

table_reference UNPIVOT [ { INCLUDE | EXCLUDE } NULLS ]
( { column | ( column [, column]... ) }
  pivot_for_clause
  unpivot_in_clause
)

```

unpivot_in_clause

```

IN
( { column | ( column [, column]... ) }
  [ AS { literal | ( literal [, literal]... ) } ]
  [, { column | ( column [, column]... ) } ]
)

```

```
        [ AS {literal | ( literal [, literal]... ) } ]
    ]...
)
```

update_all_indexes_clause

```
UPDATE INDEXES
    [ (index ( update_index_partition
                | update_index_subpartition
            )
      [, (index ( update_index_partition
                | update_index_subpartition
            )
      ]...
    )
```

update_global_index_clause

```
{ UPDATE | INVALIDATE } GLOBAL INDEXES
```

update_index_clauses

```
{ update_global_index_clause
| update_all_indexes_clause
}
```

update_index_partition

```
index_partition_description
    [ index_subpartition_clause ]
[, index_partition_description
    [ index_subpartition_clause ] ...
```

update_index_subpartition

```
SUBPARTITION [ subpartition ]
    [ TABLESPACE tablespace ]
[, SUBPARTITION [ subpartition ]
    [ TABLESPACE tablespace ]
]...
```

update_set_clause

```
SET
{ { (column [, column ]...) = (subquery)
  | column = { expr | (subquery) | DEFAULT }
}
[, { (column [, column]...) = (subquery)
  | column = { expr | (subquery) | DEFAULT }
}
]...
| VALUE (t_alias) = { expr | (subquery) }
}
```

upgrade_table_clause

```
UPGRADE [ [NOT ] INCLUDING DATA ]
    [ column_properties ]
```

user_clauses

```
{ ADD USER user [, user]...
| DROP USER user [, user]... [CASCADE]
}
```

usergroup_clauses

```
{ ADD USERGROUP usergroup WITH MEMBER user [, user]...
| MODIFY USERGROUP usergroup { ADD | DROP } MEMBER user [, user]...
| DROP USERGROUP usergroup
}
```

using_function_clause

```
USING [ schema. ] [ package. | type. ] function_name
```

using_index_clause

```
USING INDEX
{ [ schema. ] index
| (create_index_statement)
| index_properties
}
```

using_statistics_type

```
USING { [ schema. ] statistics_type | NULL }
```

using_type_clause

```
USING [ schema. ] implementation_type [ array_DML_clause ]
```

validation_clauses

```
{ VALIDATE REF UPDATE [ SET Dangling TO NULL ]
| VALIDATE STRUCTURE
  [ CASCADE { FAST | COMPLETE [ into_clause ] { OFFLINE | ONLINE } } ]
}
```

values_clause

```
VALUES ({ expr | DEFAULT }
        [, { expr | DEFAULT } ]...
)
```

varray_col_properties

```
VARRAY varray_item
{ [ substitutable_column_clause ] varray_storage_clause
| substitutable_column_clause
}
```

varray_storage_clause

```
STORE AS [SECUREFILE | BASICFILE] LOB
{ [LOB_segname] ( LOB_storage_parameters )
| LOB_segname
}
```

virtual_column_definition

```
column [datatype] [GENERATED ALWAYS] AS (column_expression)
[VIRTUAL]
[ inline_constraint [inline_constraint]... ]
```

where_clause

```
WHERE condition
```

windowing_clause

```
{ ROWS | RANGE }
{ BETWEEN
  { UNBOUNDED PRECEDING
```

```
| CURRENT ROW
| value_expr { PRECEDING | FOLLOWING }
}
AND
{ UNBOUNDED FOLLOWING
| CURRENT ROW
| value_expr { PRECEDING | FOLLOWING }
}
| { UNBOUNDED PRECEDING
| CURRENT ROW
| value_expr PRECEDING
}
}
```

XML_attributes_clause

```
XMLATTRIBUTES
[ ENTITYESCAPING | NOENTITYESCAPING ]
[ SCHEMACHECK | NOSCHEMACHECK ]
value_expr [ { [AS] c_alias } | { AS EVALNAME value_expr } ]
[, value_expr [ { [AS] c_alias } | { AS EVALNAME value_expr } ]
]...
```

XML_namespaces_clause

```
XMLNAMESPACES
( [ string AS identifier ]
  [ [, string AS identifier ]
  ]...
  [ DEFAULT string ]
)
```

XML_passing_clause

```
PASSING [ BY VALUE ]
  expr [ AS identifier ]
  [, expr [ AS identifier ]
  ]...
```

XML_table_column

```
column
{ FOR ORDINALITY
| datatype [ PATH string ] [ DEFAULT expr ]
}
```

XMLIndex_clause

```
[XDB.] XMLINDEX [ local_XMLIndex_clause ]
                [ parallel_clause ]
[ XMLIndex_parameters_clause ]
```

XMLSchema_spec

```
[ XMLSCHEMA XMLSchema_URL ]
ELEMENT { element | XMLSchema_URL # element }
[ ALLOW ANYSCHEMA
| ALLOW NONSCHEMA
| DISALLOW NONSCHEMA
]
```

XMLTABLE_options

```
[ XML_passing_clause ]
[ COLUMNS XML_table_column [, XML_table_column]...]
```


XMLType_column_properties

```
XMLTYPE [ COLUMN ] column
  [ XMLType_storage ]
  [ XMLSchema_spec ]
```

XMLType_storage

```
STORE
{ AS
{ OBJECT RELATIONAL
| [SECUREFILE | BASICFILE]
  { CLOB | BINARY XML }
    [ { LOB_segname [ (LOB_parameters) ]
      | (LOB_parameters)
    }
  ]
}
| { ALL VARRAYS AS { LOBS | TABLES } }
}
```

XMLType_table

```
OF XMLTYPE
  [ (object_properties) ]
  [ XMLTYPE XMLType_storage ]
  [ XMLSchema_spec ]
  [ XMLType_virtual_columns ]
  [ ON COMMIT { DELETE | PRESERVE } ROWS ]
  [ OID_clause ]
  [ OID_index_clause ]
  [ physical_properties ]
  [ table_properties ]
```

XMLType_view_clause

```
OF XMLTYPE [ XMLSchema_spec ]
WITH OBJECT IDENTIFIER
  { DEFAULT | ( expr [, expr ]... ) }
```

XMLType_virtual_columns

```
VIRTUAL COLUMNS ( column AS (expr) [, column AS (expr) ]... )
```

ym_iso_format

```
[ - ] P [ years Y ] [ months M ] [ days D ]
      [ T [ hours H ] [ minutes M ] [ seconds [ . frac_secs ] S ] ]
```


Data Types

This chapter presents data types that are recognized by Oracle and available for use within SQL.

This chapter includes the following sections:

- [Overview of Data Types](#)
- [Oracle Built-In Data Types](#)
- [Oracle-Supplied Data Types](#)
- [Converting to Oracle Data Types](#)

Overview of Data Types

A **data type** is a classification of a particular type of information or data. Each value manipulated by Oracle has a data type. The data type of a value associates a fixed set of properties with the value. These properties cause Oracle to treat values of one data type differently from values of another.

The data types recognized by Oracle are:

ANSI-supported data types

```
{ CHARACTER [VARYING] (size)
| { CHAR | NCHAR } VARYING (size)
| VARCHAR (size)
| NATIONAL { CHARACTER | CHAR }
  [VARYING] (size)
| { NUMERIC | DECIMAL | DEC }
  [ (precision [, scale ]) ]
| { INTEGER | INT | SMALLINT }
| FLOAT [ (size) ]
| DOUBLE PRECISION
| REAL
}
```

Oracle built-in data types

```
{ character_datatypes
| number_datatypes
| long_and_raw_datatypes
| datetime_datatypes
| large_object_datatypes
| rowid_datatypes
}
```

Oracle-supplied data types

```
{ any_types
```

```
| XML_types  
| spatial_types  
| media_types  
| expression_filter_type  
}
```

User-defined data types

User-defined data types use Oracle built-in data types and other user-defined data types to model the structure and behavior of data in applications.

See Also: Data types in *Oracle Database SQL Language Reference*

Oracle Built-In Data Types

This section describes the kinds of Oracle built-in data types.

character_datatypes

```
{ CHAR [ (size [ BYTE | CHAR ]) ]  
| VARCHAR2 (size [ BYTE | CHAR ])  
| NCHAR [ (size) ]  
| NVARCHAR2 (size)  
}
```

datetime_datatypes

```
{ DATE  
| TIMESTAMP [ (fractional_seconds_precision) ]  
  [ WITH [ LOCAL ] TIME ZONE ]  
| INTERVAL YEAR [ (year_precision) ] TO MONTH  
| INTERVAL DAY [ (day_precision) ] TO SECOND  
  [ (fractional_seconds_precision) ]  
}
```

large_object_datatypes

```
{ BLOB | CLOB | NCLOB | BFILE }
```

long_and_raw_datatypes

```
{ LONG | LONG RAW | RAW (size) }
```

number_datatypes

```
{ NUMBER [ (precision [, scale ]) ]  
| FLOAT [ (precision) ]  
| BINARY_FLOAT  
| BINARY_DOUBLE  
}
```

rowid_datatypes

```
{ ROWID | UROWID [ (size) ] }
```

The codes listed for the data types are used internally by Oracle Database. The data type code of a column or object attribute is returned by the DUMP function.

Table 6–1 Built-in Data Type Summary

Code	Data Type	Description
1	VARCHAR2(<i>size</i> [BYTE CHAR])	Variable-length character string having maximum length <i>size</i> bytes or characters. Maximum <i>size</i> is 4000 bytes or characters, and minimum is 1 byte or 1 character. You must specify <i>size</i> for VARCHAR2. BYTE indicates that the column will have byte length semantics. CHAR indicates that the column will have character semantics.
1	NVARCHAR2(<i>size</i>)	Variable-length Unicode character string having maximum length <i>size</i> characters. The number of bytes can be up to two times <i>size</i> for AL16UTF16 encoding and three times <i>size</i> for UTF8 encoding. Maximum <i>size</i> is determined by the national character set definition, with an upper limit of 4000 bytes. You must specify <i>size</i> for NVARCHAR2.
2	NUMBER [(<i>p</i> , <i>s</i>)]	Number having precision <i>p</i> and scale <i>s</i> . The precision <i>p</i> can range from 1 to 38. The scale <i>s</i> can range from -84 to 127. Both precision and scale are in decimal digits. A NUMBER value requires from 1 to 22 bytes.
2	FLOAT [(<i>p</i>)]	A subtype of the NUMBER data type having precision <i>p</i> . A FLOAT value is represented internally as NUMBER. The precision <i>p</i> can range from 1 to 126 binary digits. A FLOAT value requires from 1 to 22 bytes.
8	LONG	Character data of variable length up to 2 gigabytes, or 2 ³¹ -1 bytes. Provided for backward compatibility.
12	DATE	Valid date range from January 1, 4712 BC, to December 31, 9999 AD. The default format is determined explicitly by the NLS_DATE_FORMAT parameter or implicitly by the NLS_TERRITORY parameter. The size is fixed at 7 bytes. This data type contains the datetime fields YEAR, MONTH, DAY, HOUR, MINUTE, and SECOND. It does not have fractional seconds or a time zone.
21	BINARY_FLOAT	32-bit floating point number. This data type requires 4 bytes.
22	BINARY_DOUBLE	64-bit floating point number. This data type requires 8 bytes.
180	TIMESTAMP [(<i>fractional_seconds_precision</i>)]	Year, month, and day values of date, as well as hour, minute, and second values of time, where <i>fractional_seconds_precision</i> is the number of digits in the fractional part of the SECOND datetime field. Accepted values of <i>fractional_seconds_precision</i> are 0 to 9. The default is 6. The default format is determined explicitly by the NLS_DATE_FORMAT parameter or implicitly by the NLS_TERRITORY parameter. The sizes varies from 7 or 11 bytes, depending on the precision. This data type contains the datetime fields YEAR, MONTH, DAY, HOUR, MINUTE, and SECOND. It contains fractional seconds but does not have a time zone.
181	TIMESTAMP [(<i>fractional_seconds</i>)] WITH TIME ZONE	All values of TIMESTAMP as well as time zone displacement value, where <i>fractional_seconds_precision</i> is the number of digits in the fractional part of the SECOND datetime field. Accepted values are 0 to 9. The default is 6. The default format is determined explicitly by the NLS_DATE_FORMAT parameter or implicitly by the NLS_TERRITORY parameter. The size is fixed at 13 bytes. This data type contains the datetime fields YEAR, MONTH, DAY, HOUR, MINUTE, SECOND, TIMEZONE_HOUR, and TIMEZONE_MINUTE. It has fractional seconds and an explicit time zone.

Table 6–1 (Cont.) Built-in Data Type Summary

Code	Data Type	Description
231	TIMESTAMP [(<i>fractional_seconds</i>)] WITH LOCAL TIME ZONE	<p>All values of TIMESTAMP WITH TIME ZONE, with the following exceptions:</p> <ul style="list-style-type: none"> ■ Data is normalized to the database time zone when it is stored in the database. ■ When the data is retrieved, users see the data in the session time zone. <p>The default format is determined explicitly by the NLS_DATE_FORMAT parameter or implicitly by the NLS_TERRITORY parameter. The sizes varies from 7 or 11 bytes, depending on the precision.</p>
182	INTERVAL YEAR [(<i>year_precision</i>)] TO MONTH	<p>Stores a period of time in years and months, where <i>year_precision</i> is the number of digits in the YEAR datetime field. Accepted values are 0 to 9. The default is 2. The size is fixed at 5 bytes.</p>
183	INTERVAL DAY [(<i>day_precision</i>)] TO SECOND [(<i>fractional_seconds</i>)]	<p>Stores a period of time in days, hours, minutes, and seconds, where</p> <ul style="list-style-type: none"> ■ <i>day_precision</i> is the maximum number of digits in the DAY datetime field. Accepted values are 0 to 9. The default is 2. ■ <i>fractional_seconds_precision</i> is the number of digits in the fractional part of the SECOND field. Accepted values are 0 to 9. The default is 6. <p>The size is fixed at 11 bytes.</p>
23	RAW(<i>size</i>)	Raw binary data of length <i>size</i> bytes. Maximum <i>size</i> is 2000 bytes. You must specify <i>size</i> for a RAW value.
24	LONG RAW	Raw binary data of variable length up to 2 gigabytes.
69	ROWID	Base 64 string representing the unique address of a row in its table. This data type is primarily for values returned by the ROWID pseudocolumn.
208	UROWID [(<i>size</i>)]	Base 64 string representing the logical address of a row of an index-organized table. The optional <i>size</i> is the size of a column of type UROWID. The maximum size and default is 4000 bytes.
96	CHAR [(<i>size</i> [BYTE CHAR])]	<p>Fixed-length character data of length <i>size</i> bytes or characters. Maximum <i>size</i> is 2000 bytes or characters. Default and minimum <i>size</i> is 1 byte.</p> <p>BYTE and CHAR have the same semantics as for VARCHAR2.</p>
96	NCHAR[(<i>size</i>)]	Fixed-length character data of length <i>size</i> characters. The number of bytes can be up to two times <i>size</i> for AL16UTF16 encoding and three times <i>size</i> for UTF8 encoding. Maximum <i>size</i> is determined by the national character set definition, with an upper limit of 2000 bytes. Default and minimum <i>size</i> is 1 character.
112	CLOB	A character large object containing single-byte or multibyte characters. Both fixed-width and variable-width character sets are supported, both using the database character set. Maximum size is (4 gigabytes - 1) * (database block size).

Table 6–1 (Cont.) Built-in Data Type Summary

Code	Data Type	Description
112	NCLOB	A character large object containing Unicode characters. Both fixed-width and variable-width character sets are supported, both using the database national character set. Maximum size is (4 gigabytes - 1) * (database block size). Stores national character set data.
113	BLOB	A binary large object. Maximum size is (4 gigabytes - 1) * (database block size).
114	BFILE	Contains a locator to a large binary file stored outside the database. Enables byte stream I/O access to external LOBs residing on the database server. Maximum size is 4 gigabytes.

See Also: Data types in *Oracle Database SQL Language Reference*

Oracle-Supplied Data Types

This section shows the syntax for the Oracle-supplied data types.

any_types

```
{ SYS.AnyData | SYS.AnyType | SYS.AnyDataSet }
```

XML_types

```
{ XMLType | URIType }
```

spatial_types

```
{ SDO_Geometry | SDO_Topo_Geometry | SDO_GeoRaster }
```

media_types

```
{ ORDAudio
| ORDImage
| ORDVideo
| ORDDoc
| ORDDicom
| still_image_object_types
}
```

expression_filter_type

```
Expression
```

Converting to Oracle Data Types

SQL statements that create tables and clusters can also use ANSI data types and data types from the IBM products SQL/DS and DB2. Oracle recognizes the ANSI or IBM data type name that differs from the Oracle data type name, records it as the name of the data type of the column, and then stores the column data in an Oracle data type based on the conversions shown in the following table.

Table 6–2 ANSI Data Types Converted to Oracle Data Types

ANSI SQL Data Type	Oracle Data Type
CHARACTER (n)	CHAR (n)
CHAR (n)	

Table 6–2 (Cont.) ANSI Data Types Converted to Oracle Data Types

ANSI SQL Data Type	Oracle Data Type
CHARACTER VARYING (n)	VARCHAR2 (n)
CHAR VARYING (n)	
NATIONAL CHARACTER (n)	NCHAR (n)
NATIONAL CHAR (n)	
NCHAR (n)	
NATIONAL CHARACTER VARYING (n)	NVARCHAR2 (n)
NATIONAL CHAR VARYING (n)	
NCHAR VARYING (n)	
NUMERIC [(p, s)]	NUMBER (p, s)
DECIMAL [(p, s)] (Note 1)	
INTEGER	NUMBER (38)
INT	
SMALLINT	
FLOAT (Note 2)	FLOAT (126)
DOUBLE PRECISION (Note 3)	FLOAT (126)
REAL (Note 4)	FLOAT (63)

Notes:

1. The NUMERIC and DECIMAL data types can specify only fixed-point numbers. For those data types, the scale (s) defaults to 0.
2. The FLOAT data type is a floating-point number with a binary precision b. The default precision for this data type is 126 binary, or 38 decimal.
3. The DOUBLE PRECISION data type is a floating-point number with binary precision 126.
4. The REAL data type is a floating-point number with a binary precision of 63, or 18 decimal.

Do not define columns with the following SQL/DS and DB2 data types, because they have no corresponding Oracle data type:

- GRAPHIC
- LONG VARGRAPHIC
- VARGRAPHIC
- TIME

Note that data of type TIME can also be expressed as Oracle datetime data.

See Also: Data types in *Oracle Database SQL Language Reference*

Format Models

This chapter presents the format models for datetime and number data stored in character strings.

This chapter includes the following sections:

- [Overview of Format Models](#)
- [Number Format Models](#)
- [Datetime Format Models](#)

Overview of Format Models

A format model is a character literal that describes the format of `DATETIME` or `NUMBER` data stored in a character string. When you convert a character string into a datetime or number, a format model tells Oracle how to interpret the string.

See Also: Format Models in *Oracle Database SQL Language Reference*

Number Format Models

You can use number format models:

- In the `TO_CHAR` function to translate a value of `NUMBER` data type to `VARCHAR2` data type
- In the `TO_NUMBER` function to translate a value of `CHAR` or `VARCHAR2` data type to `NUMBER` data type

Number Format Elements

A number format model is composed of one or more number format elements. The following table lists the elements of a number format model.

Table 7–1 Number Format Elements

Element	Example	Description
, (comma)	9,999	Returns a comma in the specified position. You can specify multiple commas in a number format model. Restrictions: <ul style="list-style-type: none"> ■ A comma element cannot begin a number format model. ■ A comma cannot appear to the right of a decimal character or period in a number format model.
. (period)	99.99	Returns a decimal point, which is a period (.) in the specified position. Restriction: You can specify only one period in a number format model.
\$	\$9999	Returns value with a leading dollar sign.
0	0999 9990	Returns leading zeros. Returns trailing zeros.
9	9999	Returns value with the specified number of digits with a leading space if positive or with a leading minus if negative. Leading zeros are blank, except for a zero value, which returns a zero for the integer part of the fixed-point number.
B	B9999	Returns blanks for the integer part of a fixed-point number when the integer part is zero (regardless of zeros in the format model).
C	C999	Returns in the specified position the ISO currency symbol (the current value of the NLS_ISO_CURRENCY parameter).
D	99D99	Returns in the specified position the decimal character, which is the current value of the NLS_NUMERIC_CHARACTER parameter. The default is a period (.). Restriction: You can specify only one decimal character in a number format model.
EEEE	9.9EEEE	Returns a value using in scientific notation.
G	9G999	Returns in the specified position the group separator (the current value of the NLS_NUMERIC_CHARACTER parameter). You can specify multiple group separators in a number format model. Restriction: A group separator cannot appear to the right of a decimal character or period in a number format model.
L	L999	Returns in the specified position the local currency symbol (the current value of the NLS_CURRENCY parameter).
MI	9999MI	Returns negative value with a trailing minus sign (-). Returns positive value with a trailing blank. Restriction: The MI format element can appear only in the last position of a number format model.
PR	9999PR	Returns negative value in <angle brackets>. Returns positive value with a leading and trailing blank. Restriction: The PR format element can appear only in the last position of a number format model.
RN	RN	Returns a value as Roman numerals in uppercase.
rn	rn	Returns a value as Roman numerals in lowercase. Value can be an integer between 1 and 3999.

Table 7–1 (Cont.) Number Format Elements

Element	Example	Description
S	S9999 9999S	Returns negative value with a leading minus sign (-). Returns positive value with a leading plus sign (+). Returns negative value with a trailing minus sign (-). Returns positive value with a trailing plus sign (+). Restriction: The S format element can appear only in the first or last position of a number format model.
TM	TM	The text minimum number format model returns (in decimal output) the smallest number of characters possible. This element is case insensitive. The default is TM9, which returns the number in fixed notation unless the output exceeds 64 characters. If the output exceeds 64 characters, then Oracle Database automatically returns the number in scientific notation. Restrictions: <ul style="list-style-type: none"> You cannot precede this element with any other element. You can follow this element only with one 9 or one E (or e), but not with any combination of these. The following statement returns an error: <pre>SELECT TO_CHAR(1234, 'TM9e') FROM DUAL;</pre>
U	U9999	Returns in the specified position the Euro (or other) dual currency symbol, determined by the current value of the NLS_DUAL_CURRENCY parameter.
V	999V99	Returns a value multiplied by 10 ⁿ (and if necessary, round it up), where <i>n</i> is the number of 9's after the V.
X	XXXX xxxxx	Returns the hexadecimal value of the specified number of digits. If the specified number is not an integer, then Oracle Database rounds it to an integer. Restrictions: <ul style="list-style-type: none"> This element accepts only positive values or 0. Negative values return an error. You can precede this element only with 0 (which returns leading zeroes) or FM. Any other elements return an error. If you specify neither 0 nor FM with X, then the return always has one leading blank.

See Also: Number Format Models in *Oracle Database SQL Language Reference*

Datetime Format Models

You can use datetime format models:

- In the TO_CHAR, TO_DATE, TO_TIMESTAMP, TO_TIMESTAMP_TZ, TO_YMINTERVAL, and TO_DSINTERVAL datetime functions to translate a character string that is in a format other than the default datetime format into a DATETIME value
- In the TO_CHAR function to translate a DATETIME value that is in a format other than the default datetime format into a character string

Datetime Format Elements

A datetime format model is composed of one or more datetime format elements. The following table lists the elements of a date format model.

Table 7–2 Datetime Format Elements

Element	TO_* datetime functions?	Description
- / , . ; : "text"	Yes	Punctuation and quoted text is reproduced in the result.
AD A.D.	Yes	AD indicator with or without periods.
AM A.M.	Yes	Meridian indicator with or without periods.
BC B.C.	Yes	BC indicator with or without periods.
CC SCC		<p>Century.</p> <ul style="list-style-type: none"> ■ If the last 2 digits of a 4-digit year are between 01 and 99 (inclusive), then the century is one greater than the first 2 digits of that year. ■ If the last 2 digits of a 4-digit year are 00, then the century is the same as the first 2 digits of that year. <p>For example, 2002 returns 21; 2000 returns 20.</p>
D	Yes	Day of week (1-7). This element depends on the NLS territory of the session.
DAY	Yes	Name of day.
DD	Yes	Day of month (1-31).
DDD	Yes	Day of year (1-366).
DL	Yes	<p>Returns a value in the long date format, which is an extension of Oracle Database's DATE format, determined by the current value of the NLS_DATE_FORMAT parameter. Makes the appearance of the date components (day name, month number, and so forth) depend on the NLS_TERRITORY and NLS_LANGUAGE parameters. For example, in the AMERICAN_AMERICA locale, this is equivalent to specifying the format 'fmDay, Month dd, yyyy'. In the GERMAN_GERMANY locale, it is equivalent to specifying the format 'fmDay, dd. Month yyyy'.</p> <p>Restriction: You can specify this format only with the TS element, separated by white space.</p>
DS	Yes	<p>Returns a value in the short date format. Makes the appearance of the date components (day name, month number, and so forth) depend on the NLS_TERRITORY and NLS_LANGUAGE parameters. For example, in the AMERICAN_AMERICA locale, this is equivalent to specifying the format 'MM/DD/RRRR'. In the ENGLISH_UNITED_KINGDOM locale, it is equivalent to specifying the format 'DD/MM/RRRR'.</p> <p>Restriction: You can specify this format only with the TS element, separated by white space.</p>
DY	Yes	Abbreviated name of day.
E	Yes	Abbreviated era name (Japanese Imperial, ROC Official, and Thai Buddha calendars).
EE	Yes	Full era name (Japanese Imperial, ROC Official, and Thai Buddha calendars).

Table 7–2 (Cont.) Datetime Format Elements

Element	TO_* datetime functions?	Description
FF [1..9]	Yes	Fractional seconds; no radix character is printed. Use the X format element to add the radix character. Use the numbers 1 to 9 after FF to specify the number of digits in the fractional second portion of the datetime value returned. If you do not specify a digit, then Oracle Database uses the precision specified for the datetime data type or the data type's default precision. Valid in timestamp and interval formats, but not in DATE formats. Examples: 'HH:MI:SS.FF' SELECT TO_CHAR(SYSTIMESTAMP, 'SS.FF3') from dual;
FM	Yes	Returns a value with no leading or trailing blanks. See Also: Additional discussion on this format model modifier in the <i>Oracle Database SQL Language Reference</i>
FX	Yes	Requires exact matching between the character data and the format model. See Also: Additional discussion on this format model modifier in the <i>Oracle Database SQL Language Reference</i>
HH HH12	Yes	Hour of day (1-12).
HH24	Yes	Hour of day (0-23).
IW		Week of year (1-52 or 1-53) based on the ISO standard.
IYY IY I		Last 3, 2, or 1 digit(s) of ISO year.
YYYY		4-digit year based on the ISO standard.
J	Yes	Julian day; the number of days since January 1, 4712 BC. Number specified with J must be integers.
MI	Yes	Minute (0-59).
MM	Yes	Month (01-12; January = 01).
MON	Yes	Abbreviated name of month.
MONTH	Yes	Name of month.
PM P.M.	Yes	Meridian indicator with or without periods.
Q		Quarter of year (1, 2, 3, 4; January - March = 1).
RM	Yes	Roman numeral month (I-XII; January = I).
RR	Yes	Lets you store 20th century dates in the 21st century using only two digits. See Also: Additional discussion on RR datetime format element in the <i>Oracle Database SQL Language Reference</i>
RRRR	Yes	Round year. Accepts either 4-digit or 2-digit input. If 2-digit, provides the same return as RR. If you do not want this functionality, then enter the 4-digit year.
SS	Yes	Second (0-59).
SSSSS	Yes	Seconds past midnight (0-86399).

Table 7–2 (Cont.) Datetime Format Elements

Element	TO_* datetime functions?	Description
TS	Yes	Returns a value in the short time format. Makes the appearance of the time components (hour, minutes, and so forth) depend on the NLS_TERRITORY and NLS_LANGUAGE initialization parameters. Restriction: You can specify this format only with the DL or DS element, separated by white space.
TZD	Yes	Daylight saving information. The TZD value is an abbreviated time zone string with daylight saving information. It must correspond with the region specified in TZR. Valid in timestamp and interval formats, but not in DATE formats. Example: PST (for US/Pacific standard time); PDT (for US/Pacific daylight time).
TZH	Yes	Time zone hour. (See TZM format element.) Valid in timestamp and interval formats, but not in DATE formats. Example: 'HH:MI:SS.FFTZH:TZM'.
TZM	Yes	Time zone minute. (See TZH format element.) Valid in timestamp and interval formats, but not in DATE formats. Example: 'HH:MI:SS.FFTZH:TZM'.
TZR	Yes	Time zone region information. The value must be one of the time zone regions supported in the database. Valid in timestamp and interval formats, but not in DATE formats. Example: US/Pacific
WW		Week of year (1-53) where week 1 starts on the first day of the year and continues to the seventh day of the year.
W		Week of month (1-5) where week 1 starts on the first day of the month and ends on the seventh.
X	Yes	Local radix character. Example: 'HH:MI:SSXFF'.
Y,YYY	Yes	Year with comma in this position.
YEAR SYEAR		Year, spelled out; S prefixes BC dates with a minus sign (-).
YYYY SYYYY	Yes	4-digit year; S prefixes BC dates with a minus sign.
YYY YY Y	Yes	Last 3, 2, or 1 digit(s) of year.

See Also: Datetime Format Models in *Oracle Database SQL Language Reference*

SQL*Plus Commands

This appendix presents many of the SQL*Plus commands.

This appendix includes the following section:

- [SQL*Plus Commands](#)

SQL*Plus Commands

SQL*Plus is a command-line tool that provides access to the Oracle RDBMS. SQL*Plus enables you to:

- Enter SQL*Plus commands to configure the SQL*Plus environment
- Startup and shutdown an Oracle database
- Connect to an Oracle database
- Enter and execute SQL commands and PL/SQL blocks
- Format and print query results

SQL*Plus is available on several platforms.

The commands shown in [Table A-1](#) are SQL*Plus commands available in the command-line interface. Not all commands or command parameters are shown.

See Also:

- *SQL*Plus Quick Reference*
- *SQL*Plus User's Guide and Reference*

Table A-1 Basic SQL*Plus Commands

Database Operation	SQL*Plus Command
Log in to SQL*Plus	SQLPLUS [[{username[/password][@connect_identifier] / } [AS {SYSOPER SYSDBA SYSASM}][edition=value]] /NOLOG]
List help topics available in SQL*Plus	HELP [INDEX topic]
Execute host commands	HOST [command]
Show SQL*Plus system variables or environment settings	SHOW { ALL ERRORS USER system_variable [, system_variable] ... }

Table A-1 (Cont.) Basic SQL*Plus Commands

Database Operation	SQL*Plus Command
Alter SQL*Plus system variables or environment settings	SET <i>system_variable</i> <i>value</i>
Start up a database	STARTUP [PFILE = <i>filename</i>] [MOUNT [<i>dbname</i>] NOMOUNT]
Connect to a database	CONNECT [{ <i>username</i> [/ <i>password</i>] [<i>@connect_identifier</i>] / <i>proxy_user</i> [<i>username</i>] [/ <i>password</i>] [<i>@connect_</i> <i>identifier</i>]}] [AS {SYSOPER SYSDBA SYSASM}] [<i>edition=value</i>]]
	Note: Brackets in boldface are part of the syntax and do not imply optionality.
List column definitions for a table, view, or synonym, or specifications for a function or procedure	DESCRIBE [<i>schema.</i>] <i>object</i>
Edit contents of the SQL buffer or a file	EDIT [<i>filename</i> [<i>.ext</i>]]
Get a file and load its contents into the SQL buffer	GET <i>filename</i> [<i>.ext</i>] [LIST NOLLIST]
Save contents of the SQL buffer to a file	SAVE <i>filename</i> [<i>.ext</i>] [CREATE REPLACE APPEND]
List contents of the SQL buffer	LIST [<i>n</i> <i>n m</i> <i>n</i> LAST]
Delete contents of the SQL buffer	DEL [<i>n</i> <i>n m</i> <i>n</i> LAST]
Add new lines following current line in the SQL buffer	INPUT [<i>text</i>]
Append text to end of current line in the SQL buffer	APPEND <i>text</i>
Find and replace first occurrence of a text string in current line of the SQL buffer	CHANGE <i>sepchar</i> <i>old</i> [<i>sepchar</i> [<i>new</i> [<i>sepchar</i>]]] <i>sepchar</i> can be any nonalphanumeric ASCII character such as "/" or "!"
Capture query results in a file and, optionally, send contents of file to default printer	SPOOL [<i>filename</i> [<i>.ext</i>] [CREATE REPLACE APPEND OFF OUT]
Run SQL*Plus statements stored in a file	@ { <i>url</i> <i>filename</i> [<i>.ext</i>] } [<i>arg</i> ...] START { <i>url</i> <i>filename</i> [<i>.ext</i>] } [<i>arg</i> ...] <i>ext</i> can be omitted if the filename extension is .sql
Execute commands stored in the SQL buffer	/
List and execute commands stored in the SQL buffer	RUN

Table A–1 (Cont.) Basic SQL*Plus Commands

Database Operation	SQL*Plus Command
Execute a single PL/SQL statement or run a stored procedure	<code>EXECUTE statement</code>
Disconnect from a database	<code>DISCONNECT</code>
Shut down a database	<code>SHUTDOWN [ABORT IMMEDIATE NORMAL]</code>
Log out of SQL*Plus	<code>{ EXIT QUIT }</code> <code>[SUCCESS FAILURE WARNING]</code> <code>[COMMIT ROLLBACK]</code>

Symbols

@ (at sign) SQL*Plus command, A-2

/ (slash) SQL*Plus command, A-2

A

ABS function, 2-1

ACOS function, 2-1

activate_standby_db_clause, 5-1

add_binding_clause, 5-1

add_column_clause, 5-1

add_disk_clause, 5-1

add_hash_index_partition, 5-2

add_hash_partition_clause, 5-2

add_hash_subpartition, 5-2

add_list_partition_clause, 5-2

add_list_subpartition, 5-2

add_logfile_clauses, 5-2

ADD_MONTHS function, 2-1

add_mv_log_column_clause, 5-2

add_overflow_clause, 5-2

add_range_partition_clause, 5-2

add_range_subpartition, 5-3

add_system_partition_clause, 5-3

add_table_partition, 5-3

add_volume_clause, 5-3

aggregate functions, 2-1

alias_file_name, 5-3

allocate_extent_clause, 5-3

ALTER CLUSTER statement, 1-1

ALTER DATABASE LINK statement, 1-1

ALTER DATABASE statement, 1-1

ALTER DIMENSION statement, 1-2

ALTER DISKGROUP statement, 1-2

ALTER FLASHBACK ARCHIVE statement, 1-2

ALTER FUNCTION statement, 1-2

ALTER INDEX statement, 1-3

ALTER INDEXTYPE statement, 1-3

ALTER JAVA statement, 1-3

ALTER LIBRARY statement, 1-3

ALTER MATERIALIZED VIEW LOG statement, 1-4

ALTER MATERIALIZED VIEW statement, 1-3

ALTER OPERATOR statement, 1-4

ALTER OUTLINE statement, 1-4

ALTER PACKAGE statement, 1-4

ALTER PROCEDURE statement, 1-4

ALTER PROFILE statement, 1-4

ALTER RESOURCE COST statement, 1-4

ALTER ROLE statement, 1-5

ALTER ROLLBACK SEGMENT statement, 1-5

ALTER SEQUENCE statement, 1-5

ALTER SESSION statement, 1-5

ALTER SYSTEM statement, 1-5

ALTER TABLE statement, 1-6

ALTER TABLESPACE statement, 1-6

ALTER TRIGGER statement, 1-6

ALTER TYPE statement, 1-6

ALTER USER statement, 1-6

ALTER VIEW statement, 1-7

alter_datafile_clause, 5-3

alter_external_table, 5-3

alter_index_partitioning, 5-4

alter_interval_partitioning, 5-4

alter_iot_clauses, 5-4

alter_mapping_table_clauses, 5-4

alter_mv_refresh, 5-4

alter_overflow_clause, 5-4

alter_session_set_clause, 5-5

alter_system_reset_clause, 5-5

alter_system_set_clause, 5-5

alter_table_partitioning, 5-5

alter_table_properties, 5-5

alter_tempfile_clause, 5-6

alter_varray_col_properties, 5-6

alter_XMLSchema_clause, 5-6

American National Standards Institute (ANSI)

converting to Oracle data types, 6-5

analytic functions, 2-1

analytic_clause, 5-6

ANALYZE statement, 1-7

ANSI-supported data types, 6-1

any_types, 6-5

APPEND SQL*Plus command, A-2

APPENDCHILDXML function, 2-1

archive_log_clause, 5-6

array_DML_clause, 5-6

ASCII function, 2-1

ASCIISTR function, 2-1

ASIN function, 2-2

ASM_filename, 5-6

ASSOCIATE STATISTICS statement, 1-7

- ATAN function, 2-2
- ATAN2 function, 2-2
- attribute_clause, 5-6
- AUDIT statement, 1-7
- audit_operation_clause, 5-7
- audit_schema_object_clause, 5-7
- auditing_by_clause, 5-7
- auditing_on_clause, 5-7
- autoextend_clause, 5-7
- AVG function, 2-2

B

- BETWEEN condition, 4-1
- BFILENAME function, 2-2
- BIN_TO_NUM function, 2-2
- binding_clause, 5-7
- BITAND function, 2-2
- bitmap_join_index_clause, 5-7
- build_clause, 5-8
- built-in data types, 6-1, 6-2

C

- CALL statement, 1-7
- CARDINALITY function, 2-2
- CASE expressions, 3-1
- CAST function, 2-2
- CEIL function, 2-2
- cell_assignment, 5-8
- cell_reference_options, 5-8
- CHANGE SQL*Plus command, A-2
- character_datatypes, 6-2
- character_set_clause, 5-8
- CHARTOROWID function, 2-2
- check_datafiles_clause, 5-8
- check_diskgroup_clause, 5-8
- checkpoint_clause, 5-8
- CHR function, 2-2
- CLUSTER_ID function, 2-2
- cluster_index_clause, 5-8
- CLUSTER_PROBABILITY function, 2-2
- CLUSTER_SET function, 2-2
- COALESCE function, 2-2
- coalesce_index_partition, 5-8
- coalesce_table_partition, 5-8
- coalesce_table_subpartition, 5-8
- COLLECT function, 2-2
- column expressions, 3-1
- column_association, 5-8
- column_clauses, 5-9
- column_definition, 5-9
- column_properties, 5-9
- COMMENT statement, 1-7
- COMMIT statement, 1-8
- commit_switchover_clause, 5-9
- COMPOSE function, 2-3
- composite_hash_partitions, 5-9
- composite_list_partitions, 5-9
- composite_range_partitions, 5-10

- compound conditions, 4-1
- compound expressions, 3-1
- CONCAT function, 2-3
- conditional_insert_clause, 5-10
- conditions, 4-1
 - see also* SQL conditions
- CONNECT SQL*Plus command, A-2
- constraint, 5-10
- constraint_clauses, 5-10
- constraint_state, 5-10
- context_clause, 5-10
- controlfile_clauses, 5-11
- CONVERT function, 2-3
- convert_database_clause, 5-11
- converting to Oracle data types, 6-5
- CORR function, 2-3
- CORR_K function, 2-3
- CORR_S function, 2-3
- COS function, 2-3
- COSH function, 2-3
- cost_matrix_clause, 5-11
- COUNT function, 2-3
- COVAR_POP function, 2-3
- COVAR_SAMP function, 2-3
- CREATE CLUSTER statement, 1-8
- CREATE CONTEXT statement, 1-8
- CREATE CONTROLFILE statement, 1-8
- CREATE DATABASE LINK statement, 1-9
- CREATE DATABASE statement, 1-9
- CREATE DIMENSION statement, 1-9
- CREATE DIRECTORY statement, 1-9
- CREATE DISKGROUP statement, 1-9
- CREATE EDITION statement, 1-9
- CREATE FLASHBACK ARCHIVE statement, 1-9
- CREATE FUNCTION statement, 1-9
- CREATE INDEX statement, 1-10
- CREATE INDEXTYPE statement, 1-10
- CREATE JAVA statement, 1-10
- CREATE LIBRARY statement, 1-10
- CREATE MATERIALIZED VIEW LOG statement, 1-10
- CREATE MATERIALIZED VIEW statement, 1-10
- CREATE OPERATOR statement, 1-11
- CREATE OUTLINE statement, 1-11
- CREATE PACKAGE BODY statement, 1-11
- CREATE PACKAGE statement, 1-11
- CREATE PFILE statement, 1-11
- CREATE PROCEDURE statement, 1-11
- CREATE PROFILE statement, 1-11
- CREATE RESTORE POINT statement, 1-11
- CREATE ROLE statement, 1-12
- CREATE ROLLBACK SEGMENT statement, 1-12
- CREATE SCHEMA statement, 1-12
- CREATE SEQUENCE statement, 1-12
- CREATE SPFILE statement, 1-12
- CREATE SYNONYM statement, 1-12
- CREATE TABLE statement, 1-12
- CREATE TABLESPACE statement, 1-12
- CREATE TRIGGER statement, 1-13
- CREATE TYPE BODY statement, 1-13

- CREATE TYPE statement, 1-13
- CREATE USER statement, 1-13
- CREATE VIEW statement, 1-13
- create_datafile_clause, 5-11
- create_mv_refresh, 5-11
- CUBE_TABLE function, 2-3
- CUME_DIST (aggregate) function, 2-3
- CUME_DIST (analytic) function, 2-4
- currency
 - group separators, 7-2
- currency symbol
 - ISO, 7-2
 - local, 7-2
 - union, 7-3
- CURRENT_DATE function, 2-4
- CURRENT_TIMESTAMP function, 2-4
- CURSOR expressions, 3-1
- CV function, 2-4
- cycle_clause, 5-11

D

data types

- ANSI-supported, 6-1
- converting to Oracle, 6-5
- Oracle built-in, 6-1, 6-2
- Oracle-supplied, 6-1, 6-5
- overview, 6-1
- user-defined, 6-2
- database_file_clauses, 5-12
- database_logging_clauses, 5-12
- datafile_tempfile_clauses, 5-12
- datafile_tempfile_spec, 5-12
- DATAOBJ_TO_PARTITION function, 2-4
- date format models, 7-3, 7-4
 - long, 7-4
 - short, 7-4
- datetime expressions, 3-2
- datetime_datatypes, 6-2
- db_user_proxy_clauses, 5-12
- DB2 data types
 - restrictions on, 6-6
- dblink, 5-12
- dblink_authentication, 5-12
- DBTIMEZONE function, 2-4
- deallocate_unused_clause, 5-12
- decimal characters
 - specifying, 7-2
- DECODE function, 2-4
- DECOMPOSE function, 2-4
- default_cost_clause, 5-12
- default_selectivity_clause, 5-13
- default_settings_clauses, 5-13
- default_tablespace, 5-13
- default_temp_tablespace, 5-13
- deferred_segment_creation, 5-13
- DEL SQL*Plus command, A-2
- DELETE statement, 1-13
- DELETXML function, 2-4
- DENSE_RANK (aggregate) function, 2-4

- DENSE_RANK (analytic) function, 2-4
- dependent_tables_clause, 5-13
- DEPTH function, 2-4
- DEREF function, 2-4
- DESCRIBE SQL*Plus command, A-2
- dimension_join_clause, 5-13
- DISASSOCIATE STATISTICS statement, 1-13
- DISCONNECT SQL*Plus command, A-3
- disk_offline_clause, 5-13
- disk_online_clause, 5-13
- disk_region_clause, 5-14
- diskgroup_alias_clauses, 5-14
- diskgroup_attributes, 5-14
- diskgroup_availability, 5-14
- diskgroup_directory_clauses, 5-14
- diskgroup_template_clauses, 5-14
- diskgroup_volume_clauses, 5-14
- distributed_recov_clauses, 5-14
- dml_table_expression_clause, 5-14
- domain_index_clause, 5-15
- DROP CLUSTER statement, 1-14
- DROP CONTEXT statement, 1-14
- DROP DATABASE LINK statement, 1-14
- DROP DATABASE statement, 1-14
- DROP DIMENSION statement, 1-14
- DROP DIRECTORY statement, 1-14
- DROP DISKGROUP statement, 1-14
- DROP EDITION statement, 1-14
- DROP FLASHBACK ARCHIVE statement, 1-14
- DROP FUNCTION statement, 1-14
- DROP INDEX statement, 1-14
- DROP INDEXTYPE statement, 1-14
- DROP JAVA statement, 1-15
- DROP LIBRARY statement, 1-15
- DROP MATERIALIZED VIEW LOG statement, 1-15
- DROP MATERIALIZED VIEW statement, 1-15
- DROP OPERATOR statement, 1-15
- DROP OUTLINE statement, 1-15
- DROP PACKAGE statement, 1-15
- DROP PROCEDURE statement, 1-15
- DROP PROFILE statement, 1-15
- DROP RESTORE POINT statement, 1-15
- DROP ROLE statement, 1-15
- DROP ROLLBACK SEGMENT statement, 1-15
- DROP SEQUENCE statement, 1-15
- DROP SYNONYM statement, 1-15
- DROP TABLE statement, 1-15
- DROP TABLESPACE statement, 1-15
- DROP TRIGGER statement, 1-16
- DROP TYPE BODY statement, 1-16
- DROP TYPE statement, 1-16
- DROP USER statement, 1-16
- DROP VIEW statement, 1-16
- drop_binding_clause, 5-15
- drop_column_clause, 5-15
- drop_constraint_clause, 5-15
- drop_disk_clauses, 5-15
- drop_diskgroup_file_clause, 5-15
- drop_index_partition, 5-15
- drop_logfile_clauses, 5-15

- drop_table_partition, 5-16
- drop_table_subpartition, 5-16
- ds_iso_format of TO_DSINTERVAL function, 5-16
- DUMP function, 2-4

E

- EDIT SQL*Plus command, A-2
- else_clause, 5-16
- EMPTY_BLOB function, 2-4
- EMPTY_CLOB function, 2-4
- enable_disable_clause, 5-16
- enable_disable_volumes, 5-16
- encryption_spec, 5-16
- end_session_clauses, 5-16
- EQUALS_PATH condition, 4-1
- error_logging_clause, 5-16
- exceptions_clause, 5-17
- exchange_partition_subpart, 5-17
- EXECUTE SQL*Plus command, A-3
- EXISTS condition, 4-1
- EXISTSNODE function, 2-4
- EXIT SQL*Plus command, A-3
- EXP function, 2-5
- EXPLAIN PLAN statement, 1-16
- expr, 5-17
- expression_filter_type, 6-5
- expression_list, 5-17
- expressions, 3-1
 - see also* SQL expressions
- extended_attribute_clause, 5-17
- extent_management_clause, 5-17
- external_data_properties, 5-17
- external_table_clause, 5-18
- EXTRACT (datetime) function, 2-5
- EXTRACT (XML) function, 2-5
- EXTRACTVALUE function, 2-5

F

- FEATURE_ID function, 2-5
- FEATURE_SET function, 2-5
- FEATURE_VALUE function, 2-5
- file_owner_clause, 5-18
- file_permissions_clause, 5-18
- file_specification, 5-18
- FIRST function, 2-5
- FIRST_VALUE function, 2-5
- FLASHBACK DATABASE statement, 1-16
- FLASHBACK TABLE statement, 1-16
- flashback_archive_clause, 5-18
- flashback_archive_quota, 5-18
- flashback_archive_retention, 5-18
- flashback_mode_clause, 5-18
- flashback_query_clause, 5-18
- floating-point conditions, 4-1
- FLOOR function, 2-5
- for_update_clause, 5-18
- format models, 7-1
 - date format models, 7-3

- number format models, 7-1
- FROM_TZ function, 2-6
- full_database_recovery, 5-18
- fully_qualified_file_name, 5-19
- function expressions, 3-2
- function_association, 5-19
- functions, 2-1
 - see also* SQL functions

G

- general_recovery, 5-19
- GET SQL*Plus command, A-2
- global_partitioned_index, 5-19
- GRANT statement, 1-16
- grant_object_privileges, 5-19
- grant_system_privileges, 5-20
- grantee_clause, 5-20
- GRAPHIC data type
 - DB2, 6-6
 - SQL/DS, 6-6
- GREATEST function, 2-6
- group comparison conditions, 4-1
- group separator
 - specifying, 7-2
- group_by_clause, 5-20
- GROUP_ID function, 2-6
- GROUPING function, 2-6
- grouping_expression_list, 5-20
- GROUPING_ID function, 2-6
- grouping_sets_clause, 5-20

H

- hash_partitions, 5-20
- hash_partitions_by_quantity, 5-20
- hash_subparts_by_quantity, 5-21
- HELP SQL*Plus command, A-1
- hexadecimal value
 - returning, 7-3
- HEXTORAW function, 2-6
- hierarchical_query_clause, 5-21
- hierarchy_clause, 5-21
- HOST SQL*Plus command, A-1

I

- implementation_clause, 5-21
- IN condition, 4-2
- incomplete_file_name, 5-21
- index_attributes, 5-21
- index_expr, 5-21
- index_org_overflow_clause, 5-21
- index_org_table_clause, 5-21
- index_partition_description, 5-21
- index_partitioning_clause, 5-22
- index_properties, 5-22
- index_subpartition_clause, 5-22
- individual_hash_partitions, 5-22
- individual_hash_subparts, 5-22
- INITCAP function, 2-6

- inline_constraint, 5-22
- inline_ref_constraint, 5-22
- inner_cross_join_clause, 5-23
- INPUT SQL*Plus command, A-2
- INSERT statement, 1-16
- insert_into_clause, 5-23
- INSERTCHILDXML function, 2-6
- INSERTCHILDXMLAFTER function, 2-6
- INSERTCHILDXMLBEFORE function, 2-6
- INSERTXMLAFTER function, 2-6
- INSERTXMLBEFORE function, 2-6
- instance_clauses, 5-23
- INSTR function, 2-6
- integer, 5-23
- INTERVAL expressions, 3-2
- interval_day_to_second, 5-23
- interval_year_to_month, 5-23
- into_clause, 5-23
- invoker_rights_clause, 5-23
- IS A SET condition, 4-2
- IS ANY condition, 4-2
- IS EMPTY condition, 4-2
- IS OF *type* condition, 4-2
- IS PRESENT condition, 4-2
- ITERATION_NUMBER function, 2-6

J

- join_clause, 5-23

K

- key_compression, 5-23

L

- LAG function, 2-7
- large_object_datatypes, 6-2
- LAST function, 2-7
- LAST_DAY function, 2-7
- LAST_VALUE function, 2-7
- LEAD function, 2-7
- LEAST function, 2-7
- LENGTH function, 2-7
- level_clause, 5-23
- LIKE condition, 4-2
- LIST SQL*Plus command, A-2
- list_partition_desc, 5-23
- list_partitions, 5-24
- list_subpartition_desc, 5-24
- list_values_clause, 5-24
- LISTAGG function, 2-7
- LN function, 2-7
- LNNVL function, 2-7
- LOB_compression_clause, 5-24
- LOB_deduplicate_clause, 5-24
- LOB_parameters, 5-24
- LOB_partition_storage, 5-24
- LOB_partitioning_storage, 5-25
- LOB_retention_storage, 5-25
- LOB_storage_clause, 5-25

- LOB_storage_parameters, 5-25
- local_domain_index_clause, 5-25
- local_partitioned_index, 5-25
- local_XMLIndex_clause, 5-25
- locale independent, 7-4
- LOCALTIMESTAMP function, 2-7
- LOCK TABLE statement, 1-16
- LOG function, 2-8
- logfile_clause, 5-25
- logfile_clauses, 5-25
- logfile_descriptor, 5-26
- logging_clause, 5-26
- logical conditions, 4-2
- LONG VARGRAPHIC data type
 - DB2, 6-6
 - SQL/DS, 6-6
- long_and_raw_datatypes, 6-2
- LOWER function, 2-8
- LPAD function, 2-8
- LTRIM function, 2-8

M

- main_model, 5-26
- MAKE_REF function, 2-8
- managed_standby_recovery, 5-26
- mapping_table_clauses, 5-26
- materialized_view_props, 5-26
- MAX function, 2-8
- maximize_standby_db_clause, 5-26
- maxsize_clause, 5-26
- media_types, 6-5
- MEDIAN function, 2-8
- MEMBER condition, 4-2
- MERGE statement, 1-17
- merge_insert_clause, 5-27
- merge_table_partitions, 5-27
- merge_table_subpartitions, 5-27
- merge_update_clause, 5-27
- MIN function, 2-8
- mining_attribute_clause, 5-27
- MOD function, 2-8
- model expressions, 3-2
- model_clause, 5-27
- model_column, 5-27
- model_column_clauses, 5-27
- model_iterate_clause, 5-28
- model_rules_clause, 5-28
- modify_col_properties, 5-28
- modify_col_substitutable, 5-28
- modify_collection_retrieval, 5-28
- modify_column_clauses, 5-28
- modify_diskgroup_files, 5-28
- modify_hash_partition, 5-28
- modify_index_default_attrs, 5-28
- modify_index_partition, 5-28
- modify_index_subpartition, 5-29
- modify_list_partition, 5-29
- modify_LOB_parameters, 5-29
- modify_LOB_storage_clause, 5-29

- modify_mv_column_clause, 5-29
- modify_mv_log_clause, 5-30
- modify_range_partition, 5-29
- modify_table_default_attrs, 5-30
- modify_table_partition, 5-30
- modify_table_subpartition, 5-30
- modify_volume_clause, 5-30
- MONTHS_BETWEEN function, 2-8
- move_table_clause, 5-30
- move_table_partition, 5-31
- move_table_subpartition, 5-31
- multi_column_for_loop, 5-31
- multi_table_insert, 5-31
- multiset_except, 5-31
- multiset_intersect, 5-31
- multiset_union, 5-31
- mv_log_augmentation, 5-31
- mv_log_purge_clause, 5-32

N

- NANVL function, 2-8
- NCHR function, 2-8
- nested_table_col_properties, 5-32
- nested_table_partition_spec, 5-32
- NEW_TIME function, 2-8
- new_values_clause, 5-32
- NEXT_DAY function, 2-8
- NLS_CHARSET_DECL_LEN function, 2-8
- NLS_CHARSET_ID function, 2-8
- NLS_CHARSET_NAME function, 2-8
- NLS_INITCAP function, 2-9
- NLS_LOWER function, 2-9
- NLS_UPPER function, 2-9
- NLSSORT function, 2-9
- NOAUDIT statement, 1-17
- NTH_VALUE function, 2-9
- NTILE function, 2-9
- null conditions, 4-2
- NULLIF function, 2-9
- number, 5-32
- number format elements, 7-1
- number format models, 7-1
- number_datatypes, 6-2
- numeric_file_name, 5-32
- NUMTODSINTERVAL function, 2-9
- NUMTOYMINTERVAL function, 2-9
- NVL function, 2-9
- NVL2 function, 2-9

O

- object access expressions, 3-2
- object_properties, 5-32
- object_table, 5-32
- object_table_substitution, 5-33
- object_type_col_properties, 5-33
- object_view_clause, 5-33
- OID_clause, 5-33
- OID_index_clause, 5-33

- on_comp_partitioned_table, 5-33
- on_hash_partitioned_table, 5-33
- on_list_partitioned_table, 5-34
- on_object_clause, 5-34
- on_range_partitioned_table, 5-34
- ORA_DST_AFFECTED function, 2-9
- ORA_DST_CONVERT function, 2-9
- ORA_DST_ERROR function, 2-9
- ORA_HASH function, 2-9
- Oracle built-in data types, 6-1, 6-2
- Oracle-supplied data types, 6-1, 6-5
- order_by_clause, 5-34
- out_of_line_constraint, 5-34
- out_of_line_part_storage, 5-34
- out_of_line_ref_constraint, 5-35
- outer_join_clause, 5-35
- outer_join_type, 5-35

P

- parallel_clause, 5-35
- partial_database_recovery, 5-35
- partition_attributes, 5-35
- partition_extended_name, 5-35
- partition_extension_clause, 5-36
- partition_spec, 5-36
- partitioning_storage_clause, 5-36
- password_parameters, 5-36
- PATH function, 2-9
- PERCENT_RANK (aggregate) function, 2-9
- PERCENT_RANK (analytic) function, 2-10
- PERCENTILE_CONT function, 2-10
- PERCENTILE_DISC function, 2-10
- permanent_tablespace_clause, 5-36
- physical_attributes_clause, 5-36
- physical_properties, 5-37
- pivot_clause, 5-37
- pivot_for_clause, 5-37
- pivot_in_clause, 5-37
- placeholder expressions, 3-2
- POWER function, 2-10
- POWERMULTISET function, 2-10
- POWERMULTISET_BY_CARDINALITY function, 2-10
- PREDICTION function, 2-10
- PREDICTION_BOUNDS function, 2-10
- PREDICTION_COST function, 2-10
- PREDICTION_DETAILS function, 2-10
- PREDICTION_PROBABILITY function, 2-10
- PREDICTION_SET function, 2-10
- PRESENTNNV function, 2-10
- PRESENTV function, 2-11
- PREVIOUS function, 2-11
- proxy_clause, 5-37
- PURGE statement, 1-17

Q

- qualified_disk_clause, 5-37
- qualified_template_clause, 5-37

- query_block, 5-37
- query_partition_clause, 5-38
- query_table_expression, 5-38
- quiesce_clauses, 5-38
- QUIT SQL*Plus command, A-3

R

- range_partition_desc, 5-38
- range_partitions, 5-38
- range_subpartition_desc, 5-38
- range_values_clause, 5-38
- RANK (aggregate) function, 2-11
- RANK (analytic) function, 2-11
- RATIO_TO_REPORT function, 2-11
- RAWTOHEX function, 2-11
- RAWTONHEX function, 2-11
- rebalance_diskgroup_clause, 5-38
- rebuild_clause, 5-38
- records_per_block_clause, 5-39
- recovery_clauses, 5-39
- redo_log_file_spec, 5-39
- redo_thread_clauses
 - see instance_clauses
- redundancy_clause, 5-39
- REF function, 2-11
- reference_model, 5-39
- reference_partition_desc, 5-39
- reference_partitioning, 5-39
- references_clause, 5-39
- REFTOHEX function, 2-11
- REGEXP_COUNT function, 2-11
- REGEXP_INSTR function, 2-11
- REGEXP_LIKE condition, 4-2
- REGEXP_REPLACE function, 2-11
- REGEXP_SUBSTR function, 2-12
- register_logfile_clause, 5-39
- REGR_AVGX function, 2-12
- REGR_AVGY function, 2-12
- REGR_COUNT function, 2-12
- REGR_INTERCEPT function, 2-12
- REGR_R2 function, 2-12
- REGR_SLOPE function, 2-12
- REGR_SXX function, 2-12
- REGR_SXY function, 2-12
- REGR_SYY function, 2-12
- relational_properties, 5-40
- relational_table, 5-40
- REMAINDER function, 2-12
- RENAME statement, 1-17
- rename_column_clause, 5-40
- rename_index_partition, 5-40
- rename_partition_subpart, 5-40
- REPLACE function, 2-12
- resize_disk_clauses, 5-40
- resource_parameters, 5-40
- return_rows_clause, 5-41
- returning_clause, 5-41
- REVOKE statement, 1-17
- revoke_object_privileges, 5-41

- revoke_system_privileges, 5-41
- ROLLBACK statement, 1-17
- rolling_migration_clause, 5-41
- rollup_cube_clause, 5-41
- ROUND (date) function, 2-12
- ROUND (number) function, 2-12
- routine_clause, 5-41
- row_movement_clause, 5-41
- ROW_NUMBER function, 2-12
- rowid_datatypes, 6-2
- ROWIDTOCHAR function, 2-12
- ROWTONCHAR function, 2-12
- RPAD function, 2-12
- RTRIM function, 2-13
- RUN SQL*Plus command, A-2

S

- sample_clause, 5-41
- SAVE SQL*Plus command, A-2
- SAVEPOINT statement, 1-17
- scalar subquery expressions, 3-2
- scientific notation, 7-2
- SCN_TO_TIMESTAMP function, 2-13
- scoped_table_ref_constraint, 5-41
- search_clause, 5-42
- searched_case_expression, 5-42
- security_clause, 5-42
- security_clauses, 5-42
- segment_attributes_clause, 5-42
- segment_management_clause, 5-42
- SELECT statement, 1-17
- select_list, 5-42
- SESSIONTIMEZONE function, 2-13
- SET CONSTRAINT[S] statement, 1-17
- SET function, 2-13
- SET ROLE statement, 1-18
- SET SQL*Plus command, A-2
- SET TRANSACTION statement, 1-18
- set_encryption_key, 5-42
- set_parameter_clause, 5-43
- set_subpartition_template, 5-43
- set_time_zone_clause, 5-43
- SHOW SQL*Plus command, A-1
- shrink_clause, 5-43
- SHUTDOWN SQL*Plus command, A-3
- shutdown_dispatcher_clause, 5-43
- SIGN function, 2-13
- simple comparison conditions, 4-3
- simple expressions, 3-2
- simple_case_expression, 5-43
- SIN function, 2-13
- single_column_for_loop, 5-43
- single_table_insert, 5-43
- SINH function, 2-13
- size_clause, 5-43
- SOUNDEX function, 2-13
- spatial_types, 6-5
- split_index_partition, 5-44
- split_nested_table_part, 5-44

- split_table_partition, 5-44
- split_table_subpartition, 5-44
- SPOOL SQL*Plus command, A-2
- SQL conditions, 4-1
 - BETWEEN condition, 4-1
 - compound conditions, 4-1
 - EQUALS_PATH condition, 4-1
 - EXISTS condition, 4-1
 - floating-point conditions, 4-1
 - group comparison conditions, 4-1
 - IN condition, 4-2
 - IS A SET condition, 4-2
 - IS ANY condition, 4-2
 - IS EMPTY condition, 4-2
 - IS OF *type* condition, 4-2
 - IS PRESENT condition, 4-2
 - LIKE condition, 4-2
 - logical conditions, 4-2
 - MEMBER condition, 4-2
 - null conditions, 4-2
 - REGEXP_LIKE condition, 4-2
 - simple comparison conditions, 4-3
 - SUBMULTISET condition, 4-3
 - UNDER_PATH condition, 4-3
- SQL expressions, 3-1
 - CASE expressions, 3-1
 - column expressions, 3-1
 - compound expressions, 3-1
 - CURSOR expressions, 3-1
 - datetime expressions, 3-2
 - function expressions, 3-2
 - INTERVAL expressions, 3-2
 - model expressions, 3-2
 - object access expressions, 3-2
 - placeholder expressions, 3-2
 - scalar subquery expressions, 3-2
 - simple expressions, 3-2
 - type constructor expressions, 3-3
- SQL functions, 2-1
 - ABS, 2-1
 - ACOS, 2-1
 - ADD_MONTHS, 2-1
 - aggregate functions, 2-1
 - analytic functions, 2-1
 - APPENDCHILDXML, 2-1
 - ASCII, 2-1
 - ASCIISTR, 2-1
 - ASIN, 2-2
 - ATAN, 2-2
 - ATAN2, 2-2
 - AVG, 2-2
 - BFILENAME, 2-2
 - BIN_TO_NUM, 2-2
 - BITAND, 2-2
 - CARDINALITY, 2-2
 - CAST, 2-2
 - CEIL, 2-2
 - CHARTOROWID, 2-2
 - CHR, 2-2
 - CLUSTER_ID, 2-2
 - CLUSTER_PROBABILITY, 2-2
 - CLUSTER_SET, 2-2
 - COALESCE, 2-2
 - COLLECT, 2-2
 - COMPOSE, 2-3
 - CONCAT, 2-3
 - CONVERT, 2-3
 - CORR, 2-3
 - CORR_K, 2-3
 - CORR_S, 2-3
 - COS, 2-3
 - COSH, 2-3
 - COUNT, 2-3
 - COVAR_POP, 2-3
 - COVAR_SAMP, 2-3
 - CUBE_TABLE, 2-3
 - CUME_DIST (aggregate), 2-3
 - CUME_DIST (analytic), 2-4
 - CURRENT_DATE, 2-4
 - CURRENT_TIMESTAMP, 2-4
 - CV, 2-4
 - DATAOBJ_TO_PARTITION, 2-4
 - DBTIMEZONE, 2-4
 - DECODE, 2-4
 - DECOMPOSE, 2-4
 - DELETXML, 2-4
 - DENSE_RANK (aggregate), 2-4
 - DENSE_RANK (analytic), 2-4
 - DEPTH, 2-4
 - DEREF, 2-4
 - DUMP, 2-4
 - EMPTY_BLOB, 2-4
 - EMPTY_CLOB, 2-4
 - EXISTSNODE, 2-4
 - EXP, 2-5
 - EXTRACT (datetime), 2-5
 - EXTRACT (XML), 2-5
 - EXTRACTVALUE, 2-5
 - FEATURE_ID, 2-5
 - FEATURE_SET, 2-5
 - FEATURE_VALUE, 2-5
 - FIRST, 2-5
 - FIRST_VALUE, 2-5
 - FLOOR, 2-5
 - FROM_TZ, 2-6
 - GREATEST, 2-6
 - GROUP_ID, 2-6
 - GROUPING, 2-6
 - GROUPING_ID, 2-6
 - HEXTORAW, 2-6
 - INITCAP, 2-6
 - INSERTCHILDXML, 2-6
 - INSERTCHILDXMLAFTER, 2-6
 - INSERTCHILDXMLBEFORE, 2-6
 - INSERTXMLAFTER, 2-6
 - INSERTXMLBEFORE, 2-6
 - INSTR, 2-6
 - ITERATION_NUMBER, 2-6
 - LAG, 2-7
 - LAST, 2-7

LAST_DAY, 2-7
 LAST_VALUE, 2-7
 LEAD, 2-7
 LEAST, 2-7
 LENGTH, 2-7
 LISTAGG, 2-7
 LN, 2-7
 LNNVL, 2-7
 LOCALTIMESTAMP, 2-7
 LOG, 2-8
 LOWER, 2-8
 LPAD, 2-8
 LTRIM, 2-8
 MAKE_REF, 2-8
 MAX, 2-8
 MEDIAN, 2-8
 MIN, 2-8
 MOD, 2-8
 MONTHS_BETWEEN, 2-8
 NANVL, 2-8
 NCGR, 2-8
 NEW_TIME, 2-8
 NEXT_DAY, 2-8
 NLS_CHARSET_DECL_LEN, 2-8
 NLS_CHARSET_ID, 2-8
 NLS_CHARSET_NAME, 2-8
 NLS_INITCAP, 2-9
 NLS_LOWER, 2-9
 NLS_UPPER, 2-9
 NLSSORT, 2-9
 NTH_VALUE, 2-9
 NTILE, 2-9
 NULLIF, 2-9
 NUMTODSINTERVAL, 2-9
 NUMTOYMINTERVAL, 2-9
 NVL, 2-9
 NVL2, 2-9
 ORA_DST_AFFECTED, 2-9
 ORA_DST_CONVERT, 2-9
 ORA_DST_ERROR, 2-9
 ORA_HASH, 2-9
 PATH, 2-9
 PERCENT_RANK (aggregate), 2-9
 PERCENT_RANK (analytic), 2-10
 PERCENTILE_CONT, 2-10
 PERCENTILE_DISC, 2-10
 POWER, 2-10
 POWERMULTISET, 2-10
 POWERMULTISET_BY_CARDINALITY, 2-10
 PREDICTION, 2-10
 PREDICTION_BOUNDS, 2-10
 PREDICTION_COST, 2-10
 PREDICTION_DETAILS, 2-10
 PREDICTION_PROBABILITY, 2-10
 PREDICTION_SET, 2-10
 PRESENTNNV, 2-10
 PRESENTV, 2-11
 PREVIOUS, 2-11
 RANK (aggregate), 2-11
 RANK (analytic), 2-11
 RATIO_TO_REPORT, 2-11
 RAWTOHEX, 2-11
 RAWTONHEX, 2-11
 REF, 2-11
 REFTOHEX, 2-11
 REGEXP_COUNT, 2-11
 REGEXP_INSTR, 2-11
 REGEXP_REPLACE, 2-11
 REGEXP_SUBSTR, 2-12
 REGR_AVGX, 2-12
 REGR_AVGY, 2-12
 REGR_COUNT, 2-12
 REGR_INTERCEPT, 2-12
 REGR_R2, 2-12
 REGR_SLOPE, 2-12
 REGR_SXX, 2-12
 REGR_SXY, 2-12
 REGR_SYY, 2-12
 REMAINDER, 2-12
 REPLACE, 2-12
 ROUND (date), 2-12
 ROUND (number), 2-12
 ROW_NUMBER, 2-12
 ROWIDTOCHAR, 2-12
 ROWTONCHAR, 2-12
 RPAD, 2-12
 RTRIM, 2-13
 SCN_TO_TIMESTAMP, 2-13
 SESSIONTIMEZONE, 2-13
 SET, 2-13
 SIGN, 2-13
 SIN, 2-13
 SINH, 2-13
 SOUNDEX, 2-13
 SQRT, 2-13
 STATS_BINOMIAL_TEST, 2-13
 STATS_CROSSTAB, 2-13
 STATS_F_TEST, 2-13
 STATS_KS_TEST, 2-14
 STATS_MODE, 2-14
 STATS_MW_TEST, 2-14
 STATS_ONE_WAY_ANOVA, 2-14
 STATS_T_TEST_INDEP, 2-14
 STATS_T_TEST_INDEPU, 2-14
 STATS_T_TEST_ONE, 2-14
 STATS_T_TEST_PAIRED, 2-14
 STATS_WSR_TEST, 2-14
 STDDEV, 2-15
 STDDEV_POP, 2-15
 STDDEV_SAMP, 2-15
 SUBSTR, 2-15
 SUM, 2-15
 SYS_CONNECT_BY_PATH, 2-15
 SYS_CONTEXT, 2-15
 SYS_DBURIGEN, 2-15
 SYS_EXTRACT_UTC, 2-15
 SYS_GUID, 2-15
 SYS_TYPEID, 2-15
 SYS_XMLAGG, 2-15
 SYS_XMLGEN, 2-15

- SYSDATE, 2-16
- SYSTIMESTAMP, 2-16
- TAN, 2-16
- TANH, 2-16
- TIMESTAMP_TO_SCN, 2-16
- TO_BINARY_DOUBLE, 2-16
- TO_BINARY_FLOAT, 2-16
- TO_BLOB, 2-16
- TO_CHAR (character), 2-16
- TO_CHAR (datetime), 2-16
- TO_CHAR (number), 2-16
- TO_CLOB, 2-16
- TO_DATE, 2-16
- TO_DSINTERVAL, 2-16
- TO_LOB, 2-16
- TO_MULTI_BYTE, 2-16
- TO_NCHAR (character), 2-16
- TO_NCHAR (datetime), 2-17
- TO_NCHAR (number), 2-17
- TO_NCLOB, 2-17
- TO_NUMBER, 2-17
- TO_SINGLE_BYTE, 2-17
- TO_TIMESTAMP, 2-17
- TO_TIMESTAMP_TZ, 2-17
- TO_YMINTERVAL, 2-17
- TRANSLATE, 2-17
- TRANSLATE...USING, 2-17
- TREAT, 2-17
- TRIM, 2-17
- TRUNC (date), 2-17
- TRUNC (number), 2-17
- TZ_OFFSET, 2-18
- UID, 2-18
- UNISTR, 2-18
- UPDATEXML, 2-18
- UPPER, 2-18
- USER, 2-18
- user-defined functions, 2-18
- USERENV, 2-18
- VALUE, 2-18
- VAR_POP, 2-18
- VAR_SAMP, 2-18
- VARIANCE, 2-18
- VSIZE, 2-18
- WIDTH_BUCKET, 2-18
- XMLAGG, 2-19
- XMLCAST, 2-19
- XMLCDATA, 2-19
- XMLCOLATTVAL, 2-19
- XMLCOMMENT, 2-19
- XMLCONCAT, 2-19
- XMLDIFF, 2-19
- XMLELEMENT, 2-19
- XMLEXISTS, 2-19
- XMLFOREST, 2-19
- XMLISVALID, 2-19
- XMLPARSE, 2-19
- XMLPATCH, 2-19
- XMLPI, 2-20
- XMLQUERY, 2-20

- XMLROOT, 2-20
- XMLSEQUENCE, 2-20
- XMLSERIALIZE, 2-20
- XMLTABLE, 2-20
- XMLTRANSFORM, 2-20
- SQL statements, 1-1
 - ALTER CLUSTER, 1-1
 - ALTER DATABASE, 1-1
 - ALTER DATABASE LINK, 1-1
 - ALTER DIMENSION, 1-2
 - ALTER DISKGROUP, 1-2
 - ALTER FLASHBACK ARCHIVE, 1-2
 - ALTER FUNCTION, 1-2
 - ALTER INDEX, 1-3
 - ALTER INDEXTYPE, 1-3
 - ALTER JAVA, 1-3
 - ALTER LIBRARY, 1-3
 - ALTER MATERIALIZED VIEW, 1-3
 - ALTER MATERIALIZED VIEW LOG, 1-4
 - ALTER OPERATOR, 1-4
 - ALTER OUTLINE, 1-4
 - ALTER PACKAGE, 1-4
 - ALTER PROCEDURE, 1-4
 - ALTER PROFILE, 1-4
 - ALTER RESOURCE COST, 1-4
 - ALTER ROLE, 1-5
 - ALTER ROLLBACK SEGMENT, 1-5
 - ALTER SEQUENCE, 1-5
 - ALTER SESSION, 1-5
 - ALTER SYSTEM, 1-5
 - ALTER TABLE, 1-6
 - ALTER TABLESPACE, 1-6
 - ALTER TRIGGER, 1-6
 - ALTER TYPE, 1-6
 - ALTER USER, 1-6
 - ALTER VIEW, 1-7
 - ANALYZE, 1-7
 - ASSOCIATE STATISTICS, 1-7
 - AUDIT, 1-7
 - CALL, 1-7
 - COMMENT, 1-7
 - COMMIT, 1-8
 - CREATE CLUSTER, 1-8
 - CREATE CONTEXT, 1-8
 - CREATE CONTROLFILE, 1-8
 - CREATE DATABASE, 1-9
 - CREATE DATABASE LINK, 1-9
 - CREATE DIMENSION, 1-9
 - CREATE DIRECTORY, 1-9
 - CREATE DISKGROUP, 1-9
 - CREATE EDITION, 1-9
 - CREATE FLASHBACK ARCHIVE, 1-9
 - CREATE FUNCTION, 1-9
 - CREATE INDEX, 1-10
 - CREATE INDEXTYPE, 1-10
 - CREATE JAVA, 1-10
 - CREATE LIBRARY, 1-10
 - CREATE MATERIALIZED VIEW, 1-10
 - CREATE MATERIALIZED VIEW LOG, 1-10
 - CREATE OPERATOR, 1-11

CREATE OUTLINE, 1-11
 CREATE PACKAGE, 1-11
 CREATE PACKAGE BODY, 1-11
 CREATE PFILE, 1-11
 CREATE PROCEDURE, 1-11
 CREATE PROFILE, 1-11
 CREATE RESTORE POINT, 1-11
 CREATE ROLE, 1-12
 CREATE ROLLBACK SEGMENT, 1-12
 CREATE SCHEMA, 1-12
 CREATE SEQUENCE, 1-12
 CREATE SPFILE, 1-12
 CREATE SYNONYM, 1-12
 CREATE TABLE, 1-12
 CREATE TABLESPACE, 1-12
 CREATE TRIGGER, 1-13
 CREATE TYPE, 1-13
 CREATE TYPE BODY, 1-13
 CREATE USER, 1-13
 CREATE VIEW, 1-13
 DELETE, 1-13
 DISASSOCIATE STATISTICS, 1-13
 DROP CLUSTER, 1-14
 DROP CONTEXT, 1-14
 DROP DATABASE, 1-14
 DROP DATABASE LINK, 1-14
 DROP DIMENSION, 1-14
 DROP DIRECTORY, 1-14
 DROP DISKGROUP, 1-14
 DROP EDITION, 1-14
 DROP FLASHBACK ARCHIVE, 1-14
 DROP FUNCTION, 1-14
 DROP INDEX, 1-14
 DROP INDEXTYPE, 1-14
 DROP JAVA, 1-15
 DROP LIBRARY, 1-15
 DROP MATERIALIZED VIEW, 1-15
 DROP MATERIALIZED VIEW LOG, 1-15
 DROP OPERATOR, 1-15
 DROP OUTLINE, 1-15
 DROP PACKAGE, 1-15
 DROP PROCEDURE, 1-15
 DROP PROFILE, 1-15
 DROP RESTORE POINT, 1-15
 DROP ROLE, 1-15
 DROP ROLLBACK SEGMENT, 1-15
 DROP SEQUENCE, 1-15
 DROP SYNONYM, 1-15
 DROP TABLE, 1-15
 DROP TABLESPACE, 1-15
 DROP TRIGGER, 1-16
 DROP TYPE, 1-16
 DROP TYPE BODY, 1-16
 DROP USER, 1-16
 DROP VIEW, 1-16
 EXPLAIN PLAN, 1-16
 FLASHBACK DATABASE, 1-16
 FLASHBACK TABLE, 1-16
 GRANT, 1-16
 INSERT, 1-16
 LOCK TABLE, 1-16
 MERGE, 1-17
 NOAUDIT, 1-17
 PURGE, 1-17
 RENAME, 1-17
 REVOKE, 1-17
 ROLLBACK, 1-17
 SAVEPOINT, 1-17
 SELECT, 1-17
 SET CONSTRAINT[S], 1-17
 SET ROLE, 1-18
 SET TRANSACTION, 1-18
 TRUNCATE CLUSTER, 1-18
 TRUNCATE TABLE, 1-18
 UPDATE, 1-18
 SQL*Plus commands, A-1
 / (slash), A-2
 @ (at sign), A-2
 APPEND, A-2
 CHANGE, A-2
 CONNECT, A-2
 DEL, A-2
 DESCRIBE, A-2
 DISCONNECT, A-3
 EDIT, A-2
 EXECUTE, A-3
 EXIT, A-3
 GET, A-2
 HELP, A-1
 HOST, A-1
 INPUT, A-2
 LIST, A-2
 QUIT, A-3
 RUN, A-2
 SAVE, A-2
 SET, A-2
 SHOW, A-1
 SHUTDOWN, A-3
 SPOOL, A-2
 SQLPLUS, A-1
 START, A-2
 STARTUP, A-2
 sql_format of TO_DSINTERVAL function, 5-44
 SQL/DS data types
 restrictions on, 6-6
 SQLPLUS SQL*Plus command, A-1
 SQRT function, 2-13
 standby_database_clauses, 5-44
 START SQL*Plus command, A-2
 start_standby_clause, 5-44
 STARTUP SQL*Plus command, A-2
 startup_clauses, 5-45
 statements, 1-1
 see also SQL statements
 STATS_BINOMIAL_TEST function, 2-13
 STATS_CROSSTAB function, 2-13
 STATS_F_TEST function, 2-13
 STATS_KS_TEST function, 2-14
 STATS_MODE function, 2-14
 STATS_MW_TEST function, 2-14

- STATS_ONE_WAY_ANOVA function, 2-14
- STATS_T_TEST_INDEP function, 2-14
- STATS_T_TEST_INDEPU function, 2-14
- STATS_T_TEST_ONE function, 2-14
- STATS_T_TEST_PAIRED function, 2-14
- STATS_WSR_TEST function, 2-14
- STDDEV function, 2-15
- STDDEV_POP function, 2-15
- STDDEV_SAMP function, 2-15
- still_image_object_types, 5-45
- stop_standby_clause, 5-45
- storage_clause, 5-45
- storage_table_clause, 5-45
- string, 5-45
- striping_clause, 5-45
- SUBMULTISET condition, 4-3
- subpartition_by_hash, 5-45
- subpartition_by_list, 5-46
- subpartition_by_range, 5-46
- subpartition_extended_name, 5-46
- subpartition_template, 5-46
- subquery, 5-46
- subquery_factoring_clause, 5-46
- subquery_restriction_clause, 5-46
- substitutable_column_clause, 5-46
- SUBSTR function, 2-15
- SUM function, 2-15
- supplemental_db_logging, 5-46
- supplemental_id_key_clause, 5-46
- supplemental_log_grp_clause, 5-46
- supplemental_logging_props, 5-47
- supplemental_plsql_clause, 5-47
- supplemental_table_logging, 5-47
- supplied data types, 6-1, 6-5
- switch_logfile_clause, 5-47
- syntax for subclauses, 5-1
- SYS_CONNECT_BY_PATH function, 2-15
- SYS_CONTEXT function, 2-15
- SYS_DBURIGEN function, 2-15
- SYS_EXTRACT_UTC function, 2-15
- SYS_GUID function, 2-15
- SYS_TYPEID function, 2-15
- SYS_XMLAGG function, 2-15
- SYS_XMLGEN function, 2-15
- SYSDATE function, 2-16
- system_partitioning, 5-47
- SYSTIMESTAMP function, 2-16

T

- table_collection_expression, 5-47
- table_compression, 5-47
- table_index_clause, 5-47
- table_partition_description, 5-47
- table_partitioning_clauses, 5-48
- table_properties, 5-48
- table_reference, 5-48
- tablespace_clauses, 5-48
- tablespace_group_clause, 5-48
- tablespace_logging_clauses, 5-48

- tablespace_retention_clause, 5-48
- tablespace_state_clauses, 5-48
- TAN function, 2-16
- TANH function, 2-16
- temporary_tablespace_clause, 5-49
- TIME data type
 - DB2, 6-6
 - SQL/DS, 6-6
- time format models, 7-6
- time zone formatting, 7-6
- timeout_clause, 5-49
- TIMESTAMP data type
 - DB2, 6-6
 - SQL/DS, 6-6
- TIMESTAMP_TO_SCN function, 2-16
- TO_BINARY_DOUBLE function, 2-16
- TO_BINARY_FLOAT function, 2-16
- TO_BLOB function, 2-16
- TO_CHAR (character) function, 2-16
- TO_CHAR (datetime) function, 2-16
- TO_CHAR (number) function, 2-16
- TO_CLOB function, 2-16
- TO_DATE function, 2-16
- TO_DSINTERVAL function, 2-16
- TO_LOB function, 2-16
- TO_MULTI_BYTE function, 2-16
- TO_NCHAR (character) function, 2-16
- TO_NCHAR (datetime) function, 2-17
- TO_NCHAR (number) function, 2-17
- TO_NCLOB function, 2-17
- TO_NUMBER function, 2-17
- TO_SINGLE_BYTE function, 2-17
- TO_TIMESTAMP function, 2-17
- TO_TIMESTAMP_TZ function, 2-17
- TO_YMINTERVAL function, 2-17
- trace_file_clause, 5-49
- TRANSLATE function, 2-17
- TRANSLATE...USING function, 2-17
- TREAT function, 2-17
- TRIM function, 2-17
- TRUNC (date) function, 2-17
- TRUNC (number) function, 2-17
- TRUNCATE CLUSTER statement, 1-18
- TRUNCATE TABLE statement, 1-18
- truncate_partition_subpart, 5-49
- type constructor expressions, 3-3
- TZ_OFFSET function, 2-18

U

- UID function, 2-18
- UNDER_PATH condition, 4-3
- undo_tablespace, 5-49
- undo_tablespace_clause, 5-49
- undrop_disk_clause, 5-49
- UNISTR function, 2-18
- unpivot_clause, 5-49
- unpivot_in_clause, 5-49
- UPDATE statement, 1-18
- update_all_indexes_clause, 5-50

- update_global_index_clause, 5-50
- update_index_clauses, 5-50
- update_index_partition, 5-50
- update_index_subpartition, 5-50
- update_set_clause, 5-50
- UPDATEXML function, 2-18
- upgrade_table_clause, 5-50
- UPPER function, 2-18
- USER function, 2-18
- user_clauses, 5-50
- user-defined data types, 6-2
- user-defined functions, 2-18
- USERENV function, 2-18
- usergroup_clauses, 5-51
- using_function_clause, 5-51
- using_index_clause, 5-51
- using_statistics_type, 5-51
- using_type_clause, 5-51

V

- validation_clauses, 5-51
- VALUE function, 2-18
- values_clause, 5-51
- VAR_POP function, 2-18
- VAR_SAMP function, 2-18
- VARGRAPHIC data type
 - DB2, 6-6
 - SQL/DS, 6-6
- VARIANCE function, 2-18
- varray_col_properties, 5-51
- varray_storage_clause, 5-51
- virtual_column_definition, 5-51
- VSIZE function, 2-18

W

- where_clause, 5-51
- WIDTH_BUCKET function, 2-18
- windowing_clause, 5-51

X

- XML_attributes_clause, 5-52
- XML_namespaces_clause, 5-52
- XML_passing_clause, 5-52
- XML_table_column, 5-52
- XML_types, 6-5
- XMLAGG function, 2-19
- XMLCast function, 2-19
- XMLCDATA function, 2-19
- XMLCOLATTVAL function, 2-19
- XMLCOMMENT function, 2-19
- XMLCONCAT function, 2-19
- XMLDIFF function, 2-19
- XMLELEMENT function, 2-19
- XMLEXISTS function, 2-19
- XMLFOREST function, 2-19
- XMLindex_clause, 5-52
- XMLISVALID function, 2-19
- XMLPARSE function, 2-19

- XMLPATCH function, 2-19
- XMLPI function, 2-20
- XMLQUERY function, 2-20
- XMLROOT function, 2-20
- XMLSchema_spec, 5-52
- XMLSEQUENCE function, 2-20
- XMLSERIALIZE function, 2-20
- XMLTABLE function, 2-20
- XMLTABLE_options, 5-52
- XMLTRANSFORM function, 2-20
- XMLType_column_properties, 5-53
- XMLType_storage, 5-53
- XMLType_table, 5-53
- XMLType_view_clause, 5-53
- XMLType_virtual_columns, 5-53

Y

- ym_iso_format of TO_YMINTERVAL function, 5-53

